

SDS Number:
Page 1 of 7

UL5420, UL5460 Part A RESIN

Revision No.: 3
Revision Date: 12/30/2018

Section 1 IDENTIFICATION

Product Name: UL5420, UL5460 Part A RESIN

Manufacturer: Chemical Concepts

410 Pike Road
Huntingdon Valley, PA. 19006
Phone: 800.220.1966

Email: sales@chemical-concepts.com Website: www.chemical-concepts.com

Information department: Environment protection department.

Materials Uses: Epoxy RESIN used with an Epoxy Hardener (Part B) to Bond Various Substrates.

In Case of Emergency Contact: INFOTRAC: 800-535-1035

Section 2 HAZARD IDENTIFICATION

GHS Classification:

CATEGORY	SIGNAL WORD	HAZARD STATEMENT(S)
Health Skin Corrosion/Irritation, Category 2 Eye Irritation, Category 2A Skin Sensitization, Category 1 STOT SE, Category 3	WARNING WARNING WARNING WARNING	H315 – Causes skin irritation H319 – Causes serious eye irritation H317 – May cause an allergic skin reaction H335 – May cause respiratory irritation



GHS Precaution Statements:

Prevention:

- P261 – Avoid breathing dust/fume/mist/vapors/spray.
- P264 – Wash hands (or other affected skin surfaces) thoroughly after handling.
- P270 – Do not eat, drink, or smoke when using this product.
- P273 – Avoid release to the environment
- P280 – Wear protective gloves/protective clothing/eye protection/face protection.

Response:

- P305/P351/P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P301/P312 – IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
- P302/P352 – IF ON SKIN: Wash with plenty of soap and water.
- P333/P313 – If skin irritation or rash occurs get medical advice/attention.

Storage:

SDS Number:
Page 2 of 7

UL5420, UL5460 Part A RESIN

Revision No.: 3
Revision Date: 12/30/2018

- P403 – Store in a well-ventilated place.
- P410 – Protect from sunlight.
- P411 – Store at temperatures not exceeding 25°C (75°F).

Disposal:

P501 – Dispose of contents/containers in accordance with local/regional/national/international regulations.

Route of Entry: Eye contact, skin contact, inhalation, and ingestion.

Target Organs: Skin, eyes, respiratory tract, digestive tract, liver, kidney, olfactory and Central Nervous System (CNS).

Skin Contact: May cause irritation of the skin. Prolonged exposure may cause sensitization. Preexisting skin conditions may be aggravated by exposure to this material.

Eye Contact: May cause irritation and/or sensitization.

Respiratory Contact: Respiratory tract irritant. Prolonged exposure may result in dizziness, nausea, headache, and anesthetic effects. May cause sensitization. Preexisting respiratory conditions may be aggravated by exposure to this product. May cause CNS depression.


Ingestion: Call a physician or poison control center immediately. If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting. If vomiting occurs, the head should be kept low so that the stomach vomit doesn't enter the lungs.

Part B Hardener:

HMIS (United States)

Health 2
Flammability 1
Reactivity 0
PPE X

NFPA (United States)



WHMIS (Canada): C, D2B



Section 3 COMPOSITION / INFORMATION ON INGREDIENTS

Name: Mixtures, Adhesives	CAS #	% by Weight
Bisphenol A Epoxy Resin	25068-38-6	80 – 100%
Non-hazardous Ingredients	Not Applicable	< 10%

Section 4 FIRST-AID MEASURES

Skin: Remove contaminated clothing. Flush skin with water, then wash affected areas with soap and water. If irritation develops, seek medical attention. Wash or dispose of clothing before reuse.

Eye: Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush if possible. Seek immediate medical attention.

Respiratory: Loosen clothing as necessary and position individual in a comfortable position. Move exposed to fresh air. Give artificial respiration if necessary. If breathing is difficult give oxygen. Immediately get medical assistance.

Ingestion: Give patient water to dilute material in stomach. DO NOT induce vomiting. Seek immediate medical attention. If vomiting occurs naturally, have person lean forward to reduce risk of aspiration. DO NOT give anything by mouth to an unconscious person.

Section 5 FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: In case of fire, water spray, fog, dry chemical or CO₂, or alcohol resistant foam.

Specific Hazards Arising from the Chemical: Fire may produce irritating, corrosive and/or toxic gases.

Hazardous Thermal: Decomposition products may include the following materials: Carbon dioxide, carbon monoxide, halogenated compounds.

Special Protective Equipment and Precautions for Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, and rubber boots. In enclosed spaces, use self-contained breathing apparatus (SCBA) and protective clothing.

Flammability Classification: Combustible, Class IIIB estimated.

Risk of Explosion due to Mechanical Impact: Not Applicable.

Risk of Explosion due to Static Discharge: Not Applicable.

Autoignition Temp.: Not Available

LEL: Not Available

UEL: Not Available

Section 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: Keep unnecessary personnel away. Avoid contact with skin or inhalation of spillage, dust or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Eliminate all sources of ignition. For large spill or leak wear self-contained breathing apparatus (SCBA) and appropriate PPE.

Environmental Precautions: Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid releases to the environment. Retain and dispose of contaminated was water. Keep out of sewers and drains. Contact local authorities if case of spillage to drain/aquatic environment.

Clean-Up Methods and Materials: Absorb with an inert material and place in an appropriate container for disposal.

Section 7 HANDLING AND STORAGE

Handling Precautions: Avoid breathing vapors. Use in a well-ventilated area. Wear rubber gloves (nitrile or butyl) and chemical resistant apron. Wear chemical splash goggles. Do not reuse empty containers.

Storage Precautions: Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well ventilated area.

Section 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters and Exposures:

Material Name:

Bisphenol A Epoxy Resin (CAS: 25068-38-6)

Exposure Limits:

None

Engineering Controls: Provide adequate ventilation (general or local exhaust). Ensure that a working eyewash and safety shower are in the work area.

Individual Protection Measures and PPE:

Eye / Face Protection: Wear safety glasses with side shields or splash goggles.

Skin Protection: Chemical resistant gloves (nitrile or butyl) and chemical resistant apron are recommended.

SDS Number:
Page 4 of 7

UL5420, UL5460 Part A RESIN

Revision No.: 3
Revision Date: 12/30/2018

Respiratory Protection In case of insufficient ventilation, wear an approved (NIOSH) respirator with organic vapor cartridge and dust/mist pre-filter.

Thermal Hazards: None.

Section 9 PHYSICAL AND CHEMICAL PROPERTIES

	Part A RESIN
Appearance:	Viscous Liquid
Color:	Clear
Odor:	Not Available
Odor Threshold:	Not Available
pH:	Not Available
Melting Point / Freezing Point:	Not Available
Initial Boiling Point:	260°F (500°C)
Flash Point and Method:	Pensky-Martens Closed Cup: 251°C (>484°F) (ASTM D 93)
Flammability:	Not Available
Lower Explosion Limit:	Not Available
Upper Explosion Limit:	Not Available
Vapor Pressure:	.03 mm Hg @ 77°C (171°F)
Vapor Density:	Not Available
Relative Density:	1.17 (9.7 lbs./gallon)
Solubility in Water:	Negligible
Partition Coefficient (n-Octanol in Water):	Not Available
Auto-Ignition Temperature:	Not Available
Decomposition Temperature:	Not Available
Viscosity (Dynamic CPS/mPa-s):	8,000 to 10,000 CPS
Percent Volatile:	Not Available
Specific Gravity:	1.17

Section 10 STABILITY AND REACTIVITY

Reactivity: Product is stable under normal conditions.

Chemical Stability: The product is stable.

Possibility of Hazardous Reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to Avoid: Avoid exposure – obtain special instructions before use. Avoid all possible sources of ignition (spark or flame).

Materials to Avoid (Incompatibility): strong oxidizing materials, strong acids, strong alkalis.

Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Other hazards: Reacts with considerable heat release with some curing agents.

Section 11 TOXICOLOGICAL INFORMATION

Acute Toxicity to Animals:

Bisphenol A Epoxy Resin (CAS: 25068-38-6)

LD50 = 11,400 mg/kg (oral, rat)

LD50 = 2,000 mg/kg (dermal, rat)

SDS Number:
 Page 5 of 7

UL5420, UL5460 Part A RESIN

 Revision No.: 3
 Revision Date: 12/30/2018

Conclusion/Summary:

Not Available

Acute Toxicity to Humans: This product has not been tested for human effects. No additional information.

Chronic Toxicity to Animals: This product has not been tested for animal effects. No additional information.

Chronic Toxicity to Humans: This product has not been tested for human effects. No additional information.

Irritation/Corrosion:

Product/ingredient name	Result	Species	Score	Exposure	Observation
Bisphenol A Epoxy Resin (CAS: 25068-38-6)	Skin – Erythema/Eschar 404 Acute Dermal Irritation/Corrosion	Rabbit	1.5 – 2		
	Skin – Edema 404 Acute Dermal Irritation/Corrosion	Rabbit	1.0 – 1.5		
	Eyes – 405 Acute Eye Irritation/Corrosion	Rabbit	0		
	Eyes – Redness of the Conjunctivae	Rabbit	0.7		
	Skin – Moderate Irritation	Rabbit		24 hours	
	Skin – Severe Irritant	Rabbit		24 hours	
	Eyes – Mild Irritant	Rabbit			

Eye Damage / Irritation: Not Available.

Respiratory Sensitization: Not Available.

Skin Sensitization: Not Available.

Ingestion: Not Available.

Mutagenicity: Not Available.

Carcinogenicity: Not Available.

Reproductive Toxicity: Not Available.

Teratogenic Effects: Not Available.

STOST- Single Exposure:

Product/ingredient name	Category	Route of Exposure	Target Organ
Bisphenol A Epoxy Resin (CAS 26068-38-6)	Category 3		

STOST – Repeated Exposure: Not Available.

Aspiration Hazard: Not Available

Section 12 ECOLOGICAL INFORMATION

Ecotoxicity: This product contains components that may be toxic to aquatic organisms and may cause long term adverse effects in an aquatic environment.

Product/ingredient name	Result	Species	Exposure
Bisphenol A Epoxy Resin (CAS 25068-38-6)	Acute LC50 1.3 mg/l - 203 Fish, Acute Toxicity Test	Fish - Fish	96 hour
	Acute EC50 2.1 mg/l - 202 Daphnia sp. Acute Immobilization Test and Reproductive Test	Aquatic invertebrates. Water Flea	48 hour
	Acute No-observable-effect-concentration 0.3 mg/l – 211 Daphnia Magna Reproduction Test	Aquatic invertebrates. Water Flea	21 day
	Acute LC50 > 11 mg/l	Aquatic plants - Algae	72 hour

Persistence and Degradability: Not Available.

Bioaccumulative Potential:

SDS Number:

UL5420, UL5460 Part A RESIN

Revision No.: 3

Page 6 of 7

Revision Date: 12/30/2018

Product/ingredient name	LogPow	BCF	Potential
Bisphenol A Epoxy Resin (CAS 26068-38-6)	2.64 – 3.78	3 – 31 31.00	Low

Mobility in Soil: Not Available.

Other Adverse Effects: No known significant effects or critical hazards.

Section 13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Part A RESIN: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recycle-able products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14 TRANSPORT INFORMATION

CFR: Not Regulated

TDG: Not Regulated

DOT Classification: Not Regulated

IATA:

IMO:

Marine Pollutant: YES

Section 15 REGULATORY INFORMATION

U.S. Federal Regulations

United States – TSCA 12(b) – Chemical export notification: None required.

United States – TSCA 5(a)2 – Final significant new use rules: Not listed.

United States – TSCA 5(a)2 – Proposed significant new use rules: Not listed.

United States – TSCA 5(e) – Substances consent order: Not listed.

SARA 311/312 Chemical: Yes

Classification Hazard Categories: Immediate (acute) health hazard

SARA 313 (TRI reporting) Not regulated.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPS) List: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Not regulated.

Safe Drinking Water Act (SDWA): Not regulated.

State Regulations

California Proposition 65: **WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer. **WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

SDS Number:
Page 7 of 7

UL5420, UL5460 Part A RESIN

Revision No.: 3
Revision Date: 12/30/2018

Ingredient Name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Oxirane, 2-(phenoxyethyl)-	Yes	No	5 µg/day	No
Phenol, 4,4'-(1-methylethylidene)bis-	No	Yes	No	No

TSCA (Toxic Substances Control Act): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory Requirements.

International Regulations:

DSL (Canada Domestic Substance List): All components of this product are on the DSL (Canada Domestic Substance List) or are exempt from DSL.

EINECS: Not Available.



WHMIS: B2, C, D2B.

Section 16 OTHER INFORMATION

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

END OF SDS DOCUMENT

SDS Number:
Page 1 of 8

UL5420, UL5460 Part B Hardener

Revision No.: 3
Revision Date: 12/30/2018

Section 1 IDENTIFICATION

Product Name: UL5420, UL5460 Part B Hardener

Manufacturer: Chemical Concepts


**410 Pike Road
Huntingdon Valley, PA. 19006
Phone: 800.220.1966
Email: sales@chemical-concepts.com Website: www.chemical-concepts.com
Information department: Environment protection department.**

Materials Uses: Epoxy Hardener used with an Epoxy Resin to Bond Various Substrates.

In Case of Emergency Contact: INFOTRAC: 800-535-1035

Section 2 HAZARD IDENTIFICATION

GHS Classification:

CATEGORY	SIGNAL WORD	HAZARD STATEMENT(S)
Health Acute Oral Toxicity, Category 4 Acute Inhalation Toxicity, Category 4 Acute Dermal Toxicity, Category 4 Skin Corrosion/Irritation, Category 1B Serious Eye Damage Irritation, Category 1 Skin Sensitization, Category 1 STOT SE, Category 3 STOT RE, Category 1	WARNING WARNING WARNING DANGER DANGER WARNING WARNING DANGER	H302 – Harmful if swallowed H314 – Harmful if inhaled H312 – Harmful in contact with skin H314 – Causes severe skin burns and eye damage H318 – Causes serious eye damage H317 – May cause an allergic skin reaction H335 – May cause respiratory irritation H372 – Causes damage to organs through prolonged or repeated exposure
Environmental Acute, Category 2 Chronic, Category 2		H401 – Toxic to aquatic life H412 – Harmful to aquatic life with long lasting effects
		

GHS Precaution Statements:

Prevention:

- P261 – Avoid breathing dust/fume/mist/vapors/spray.
- P264 – Wash hands (or other affected skin surfaces) thoroughly after handling.
- P270 – Do not eat, drink, or smoke when using this product.
- P273 – Avoid release to the environment

SDS Number:
Page 2 of 8

UL5420, UL5460 Part B Hardener

Revision No.: 3
Revision Date: 12/30/2018

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P305/P351/P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P301/P312 – IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

P302/P352 – IF ON SKIN: Wash with plenty of soap and water.

P333/P313 – If skin irritation or rash occurs get medical advice/attention.

Storage:

P403 – Store in a well-ventilated place.

P410 – Protect from sunlight.

P411 – Store at temperatures not exceeding 25°C (75°F).

Disposal:

P501 – Dispose of contents/containers in accordance with local/regional/national/international regulations.

Route of Entry: Eye contact, skin contact, inhalation, and ingestion.

Target Organs: Skin, eyes, respiratory tract, digestive tract, liver, kidney, olfactory and Central Nervous System (CNS).

Skin Contact: May cause irritation of the skin. Prolonged exposure may cause sensitization. Preexisting skin conditions may be aggravated by exposure to this material.

Eye Contact: May cause irritation and/or sensitization.

Respiratory Contact: Respiratory tract irritant. Prolonged exposure may result in dizziness, nausea, headache, and anesthetic effects. May cause sensitization. Preexisting respiratory conditions may be aggravated by exposure to this product. May cause CNS depression.


Ingestion: Call a physician or poison control center immediately. If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting. If vomiting occurs, the head should be kept low so that the stomach vomit doesn't enter the lungs.

Part B Hardener:

HMIS (United States)

Health 3
Flammability 1
Reactivity 0
PPE X

NFPA (United States)



WHMIS (Canada): D-1B, D-2A, D-2B



Section 3 COMPOSITION / INFORMATION ON INGREDIENTS

Name: Mixtures, Adhesives	CAS #	% by Weight
Isophorone Diamine	2855-13-2	25 – 45%
Amine-Epoxy Resin Adduct (Proprietary)	Proprietary	25 - 35%
Benzyl Alcohol	100-51-6	25 – 50%
2,4,6 Tris[(dimethylamino)methyl]phenol	90-72-2	5 - 10%

Section 4 FIRST-AID MEASURES

SDS Number:
Page 3 of 8

UL5420, UL5460 Part B Hardener

Revision No.: 3
Revision Date: 12/30/2018

Skin: Remove contaminated clothing. Flush skin with water, then wash affected areas with soap and water. If irritation develops, seek medical attention. Wash or dispose of clothing before reuse.

Eye: Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush if possible. Seek immediate medical attention.

Respiratory: Loosen clothing as necessary and position individual in a comfortable position. Move exposed to fresh air. Give artificial respiration if necessary. If breathing is difficult give oxygen. Immediately get medical assistance.

Ingestion: Give patient water to dilute material in stomach. DO NOT induce vomiting. Seek immediate medical attention. If vomiting occurs naturally, have person lean forward to reduce risk of aspiration. DO NOT give anything by mouth to an unconscious person.

Section 5 FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: In case of fire, water spray, fog, dry chemical or CO₂, or alcohol resistant foam.

Specific Hazards Arising from the Chemical: Fire may produce irritating, corrosive and/or toxic gases.

Special Protective Equipment and Precautions for Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, and rubber boots. In enclosed spaces, use self-contained breathing apparatus (SCBA) and protective clothing.

Flammability Classification: Combustible, Class III B estimated.

Risk of Explosion due to Mechanical Impact: Not Applicable.

Risk of Explosion due to Static Discharge: Not Applicable.

Autoignition Temp.: 816°F (436°C).

LEL: Not Available

UEL: Not Available

Section 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures: Keep unnecessary personnel away. Avoid contact with skin or inhalation of spillage, dust or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Eliminate all sources of ignition. For large spill or leak wear self-contained breathing apparatus (SCBA) and appropriate PPE.

Environmental Precautions: Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid releases to the environment. Retain and dispose of contaminated water. Keep out of sewers and drains. Contact local authorities if case of spillage to drain/aquatic environment.

Clean-Up Methods and Materials: Absorb with an inert material and place in an appropriate container for disposal.

Section 7 HANDLING AND STORAGE

Handling Precautions: Avoid breathing vapors. Use in a well-ventilated area. Wear rubber gloves (nitrile or butyl) and chemical resistant apron. Wear chemical splash goggles. Do not reuse empty containers.

Storage Precautions: Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well ventilated area.

Section 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters and Exposures:

Material Name:

Exposure Limits:

UL5420, UL5460 Part B Hardener

Revision No.: 3
Revision Date: 12/30/2018

Isophorone Diamine (CAS 2855-13-2)	not available
Amine-Epoxy Resin Adduct (Proprietary)	not available
Benzyl Alcohol (CAS 100-51-6)	OSHA PEL TWA 10 ppm
2,4,6 Tris[(dimethylamino)methyl]phenol (CAS 90-72-2)	not available

Engineering Controls: Provide adequate ventilation (general or local exhaust). Ensure that a working eyewash and safety shower are in the work area.

Individual Protection Measures and PPE:

Eye / Face Protection: Wear safety glasses with side shields or splash goggles.

Skin Protection: Chemical resistant gloves (nitrile or butyl) and chemical resistant apron are recommended.

Respiratory Protection In case of insufficient ventilation, wear an approved (NIOSH) respirator with organic vapor cartridge and dust/mist pre-filter.

Thermal Hazards: None.

Section 9 PHYSICAL AND CHEMICAL PROPERTIES

	Part B Hardener
Appearance:	Liquid
Odor:	Amine Odor
Odor Threshold:	Not Available
pH:	Not Available
Melting Point / Freezing Point:	Not Available
Initial Boiling Point:	Not Available
Flash Point and Method:	Estimated 93.4 °C (>200 °F)
Flammability:	Combustible, Class IIIB
Lower Explosion Limit:	Not Available
Upper Explosion Limit:	Not Available
Vapor Pressure:	.09 mm Hg @ 68°F (20°C)
Vapor Density:	1 (Air = 1)
Relative Density:	7.7 – 8.8 lbs./gallon
Solubility in Water:	Slightly
Partition Coefficient (n-Octanol in Water):	Not Applicable
Auto-Ignition Temperature:	816°F (436°C)
Decomposition Temperature:	Not Available
Viscosity (Dynamic CPS/mPa-s):	50K – 150K
Percent Volatile:	Not Available
Specific Gravity:	0.95 – 1.05

Section 10 STABILITY AND REACTIVITY

Reactivity: Product is stable under normal conditions.

Chemical Stability: The product is stable.

Possibility of Hazardous Reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to Avoid: Avoid exposure – obtain special instructions before use. Avoid all possible sources of ignition (spark or flame).

Materials to Avoid (Incompatibility): strong oxidizing agents,

SDS Number:
Page 5 of 8

UL5420, UL5460 Part B Hardener

Revision No.: 3
Revision Date: 12/30/2018

Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Other hazards: Heating this substance above 300°F in the presence of air may cause slow oxidative decomposition; above 500°F polymerization may occur.

Section 11 TOXICOLOGICAL INFORMATION

Acute Toxicity to Animals:

Isophorone Diamine (CAS 2855-13-2)	LD50 = 1,030 mg/kg (oral, rat)
Benzyl Alcohol (CAS No. 100-51-6)	LD50 = 1,230 mg/kg (oral, rat) LC50 > 4.178 mg/l (Inhalation, rat, 4 hrs) LD50 = 2,000 mg/kg (dermal, rat)
2,4,6 Tris[(dimethylamino)methyl]phenol (CAS 90-72-2)	LD50 = 1,200 mg/kg (oral, rat) LD50 = 1,280 mg/kg (dermal, rat)

Conclusion/Summary: Not Available

Acute Toxicity to Humans: This product has not been tested for human effects. No additional information.

Chronic Toxicity to Animals: This product has not been tested for animal effects. No additional information.

Chronic Toxicity to Humans: This product has not been tested for human effects. No additional information.

Skin Corrosion / Irritation: Causes severe skin burns and eye damage

Product/ingredient name	Result	Species	Score	Exposure	Observation
Benzyl Alcohol (CAS 100-51-6)	Skin – Irritating to skin	Rabbit		24 hours	

Conclusion/Summary:

Skin: 49 CFR 173.136 & 137 Rabbit Severe skin Irritant (Read-across data)

Eye Damage / Irritation: Causes serious eye damage.

Respiratory Sensitization: Harmful if inhaled.

Skin Sensitization: Causes severe skin burns and eye damage

Ingestion: Harmful if swallowed.

Mutagenicity: Not Available.

Carcinogenicity: Not Available.

Reproductive Toxicity: Not Available.

Teratogenic Effects: Not Available.

STOT- Single Exposure:

Product/ingredient name	Category	Route of Exposure	Target Organs
Isophorone Diamine (CAS 2855-13-2)	Category 3		Respiratory tract irritation
Amine-Epoxy Resin Adduct (Proprietary)	Category 3		Respiratory tract irritation
Benzyl Alcohol (CAS 100-51-6)	Category 3		Respiratory tract irritation Narcotic effects

STOT – Repeated Exposure:

Product/ingredient name	Category	Route of Exposure	Target Organs
Benzyl Alcohol (CAS 100-51-6)	Category 1		Central nervous system (CNS)
Amine-Epoxy Resin Adduct (Proprietary)	Category 1		Skin – respiratory tract

SDS Number:
Page 6 of 8

UL5420, UL5460 Part B Hardener

Revision No.: 3
Revision Date: 12/30/2018

Aspiration Hazard: Not Available

Section 12 ECOLOGICAL INFORMATION

Ecotoxicity: This product contains components that may be toxic to aquatic organisms and may cause long term adverse effects in an aquatic environment.

Product/ingredient name	Result	Species	Exposure
Benzyl Alcohol (CAS 100-51-6)	Acute EC50 55 mg/l Fresh water	Aquatic Crustacea – Daphnia magna	24 hours
	Acute LC50 10 mg/l Fresh water	Aquatic Fish – Bluegill (Lepomis macrochirus)	96 hours
	Acute LC50 460 mg/l Fresh water		96 hours
2,4,6-Tris[(dimethylamino)methyl]phenol (CAS 90-72-2)	Acute LC50 447.82 mg/l Fresh water	Aquatic Fish – Fathead minnow (Pimephales promelas)	96 hours
2,4,6-Tris[(dimethylamino)methyl]phenol (CAS 90-72-2)	Acute LC50 28.198 mg/l Fresh water	Daphnia	48 hours
2,4,6-Tris[(dimethylamino)methyl]phenol (CAS 90-72-2)	Acute EC50 = 34.812 mg/l	Algae or other Aquatic plants	96 hours

Persistence and Degradability: Benzyl Alcohol (CAS 100-51-6) - Biodegradability Biotic/Aerobic – Result 92 to 96% - Readily Biodegradable.

Bioaccumulative Potential: This product contains components with the potential to bio-accumulate.

Product/ingredient name	Log Pow	BCF	Potential
Benzyl Alcohol (CAS 100-51-6)	1.1		Low
2,4,6-Tris[(dimethylamino)methyl]phenol (CAS 90-72-2)	0.77	3.162 Est.	Low

Mobility in Soil: Not Available.

Other Adverse Effects: Not Available.

Section 13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Part B Hardener: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recycle-able products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14 TRANSPORT INFORMATION

SDS Number:
Page 7 of 8

UL5420, UL5460 Part B Hardener

Revision No.: 3
Revision Date: 12/30/2018

Regulatory Information	UN/NA	Proper shipping name	Classes/*PG	Reportable Quantity (RQ)
CFR:	Not Regulated			
TDG:	Not Regulated			
DOT Classification:	Not Regulated			
IMO/IM/DG:	UN3082	ENVIRONMENTALLY HAZARD SUBSTANCE, LIQUID, N.O.S. (Amine-Epoxy Resin Adduct)	Class 9 III	
IATA (Cargo)	UN3082	ENVIRONMENTALLY HAZARD SUBSTANCE, LIQUID, N.O.S. (Amine-Epoxy Resin Adduct)	Class 9 III	

*PG: Packing Group

Environmentally hazardous and/or Marine Pollutant: YES



Special precautions for user: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15 REGULATORY INFORMATION

U.S. Federal Regulations

United States – TSCA 12(b) – Chemical export notification: None required.

United States – TSCA 5(a)2 – Final significant new use rules: Not listed.

United States – TSCA 5(a)2 – Proposed significant new use rules: Not listed.

United States – TSCA 5(e) – Substances consent order: Not listed.

SARA 311/312 Chemical: Yes

Classification Hazard Categories: Immediate (acute) health hazard
Acute Toxicity (any route of exposure)
Serious eye damage or eye irritation

SARA 313 (TRI reporting) Not regulated.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPS) List: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Not regulated.

Safe Drinking Water Act (SDWA): Not regulated.

State Regulations

California Proposition 65: None required.

TSCA (Toxic Substances Control Act): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory Requirements.

International Regulations:

SDS SAFETY DATA SHEET



SDS Number:
Page 8 of 8

BD5420, BD5460 Part B Hardener

Revision No.: 3
Revision Date: 12/30/2018

DSL (Canada Domestic Substance List): All components of this product are on the DSL (Canada Domestic Substance List) or are exempt from DSL.

EINECS: Not Available.



WHMIS: D-1B, D-2A, D-2B.

Section 16 OTHER INFORMATION

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

END OF SDS DOCUMENT



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006