

tesa® 50120



Product Information

General purpose masking tape

tesa® 50120 is a cost-efficient, creped paper masking tape, good for general-purpose bundling, holding, sealing, and surface protection applications. It provides excellent adhesion to a variety of surfaces.

Main Application

- Light-duty bundling
- Packaging and closing
- Light-duty masking
- Paint masking

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Thickness of tape	123 µm 4.8 mils	• Tensile strength	35 N/cm 20 lbs/in
• Type of adhesive	synthetic rubber	• Temperature resistance min.	16 °C 61 °F
• Elongation at break	12 %	• Temperature resistance max.	65 °C 149 °F

Adhesion to

- steel 2.7 N/cm
24.7 oz/in

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006