



Printing Date 11/18/2016 Revision Number 1 Revision Date 11/18/2016

### 1 Identification

- · Product identifier
- · Trade name: Quick-Tac 2 (Liquid)
- · Relevant identified uses of the substance or mixture.

Adhesive Activator

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Adhesive Systems, Inc.

A Division of Royal Adhesives & Sealants, LLC

9411 Corsair Road Frankfort, Illinois 60423 Phone Number: 800-552-0299

- · Information department: Environment protection department.
- · Emergency telephone number:

ChemTrec: Day or Night within USA and Canada: 1-800-424-9300. Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

  (Contd. on page 2)

Printing Date 11/18/2016 Revision Number 1 Revision Date 11/18/2016

Trade name: Quick-Tac 2 (Liquid)

(Contd. of page 1)

### · Hazard pictograms









GHS06 GHS07

#### · Signal word Danger

#### · Hazard statements

Highly flammable liquid and vapor.

Toxic if swallowed, in contact with skin or if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Do not breathe dust/fume/gas/mist/vapors/spray.

*Wear protective gloves / eye protection / face protection.* 

Wear protective gloves / protective clothing.

Ground/bond container and receiving equipment.

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

Call a POISON CENTER/doctor.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Rinse mouth.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

(Contd. on page 3)

Printing Date 11/18/2016 Revision Number 1 Revision Date 11/18/2016

Trade name: Quick-Tac 2 (Liquid)

· HMIS-ratings (scale 0 - 4)

(Contd. of page 2)

HEALTH 2 I

Health = 2Fire = 3

PHYSICAL HAZARD  $\boxed{0}$  Physical Hazard = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture

· Hazardous components:			
67-64-1	acetone	50-100%	
99-97-8	N,N-dimethyl-p-toluidine	≤1.0%	

### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse mouth with water.

Seek medical treatment.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

*Use fire fighting measures that suit the environment.* 

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters

Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

· Protective equipment: Protective clothing and respiratory protective device.

USA

Printing Date 11/18/2016 Revision Number 1 Revision Date 11/18/2016

Trade name: Quick-Tac 2 (Liquid)

(Contd. of page 3)

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Open and handle receptacle with care.

*Ensure good ventilation/exhaustion at the workplace.* 

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep container closed when not in use.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- · Information about storage in one common storage facility:

Store away from oxidizing agents.

Store as flammable liquid.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· *Specific end use*(s) *No further relevant information available.* 

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

(Contd. on page 5)

Printing Date 11/18/2016 Revision Number 1 Revision Date 11/18/2016

Trade name: Quick-Tac 2 (Liquid)

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
BEI

99-97-8 N,N-dimethyl-p-toluidine

WEEL Long-term value: 0.5 ppm

# · Ingredients with biological limit values:

### 67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### · Eye protection:

Face shield over protective glasses or goggles.

Safety glasses with side shields.



Tightly sealed goggles

· Body protection: Protective work clothing

USA

Printing Date 11/18/2016 Revision Number 1 Revision Date 11/18/2016

Trade name: Quick-Tac 2 (Liquid)

(Contd. of page 5)

injointation on busic physical and c	rhemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear, light amber
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point:	Undetermined.
Boiling point:	55 °C (131 °F)
Flash point:	-17 °C (1 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	465 °C (869 °F)
Decomposition temperature:	Not determined.
Auto igniting:	465C (869.0F)
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Flammable limits:	
Lower:	2.6 Vol %
Upper:	13.0 Vol %
Vapor pressure at 20 °C (68 °F):	245.3 hPa (184 mm Hg)
Specific gravity at 20 °C (68 °F):	0.791 g/cm³ (6.601 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined
Solubility in / Miscibility with	
Water:	Miscible
Partition coefficient (n-octanol/wate	e <b>r</b> ): Not determined.

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability

Kinematic:

· Solvent content:

· Other information

Organic solvents:

Solids content:

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

No further relevant information available.

Not determined.

Not available

Not available

· Possibility of hazardous reactions Forms explosive gas mixture with air.

(Contd. on page 7)

Printing Date 11/18/2016 Revision Number 1 Revision Date 11/18/2016

Trade name: Quick-Tac 2 (Liquid)

(Contd. of page 6)

· Conditions to avoid

Heat, flames, sparks.

Exposure to high temperatures.

Direct sunlight

· Incompatible materials:

Reacts with oxidizing agents.

Reacts with reducing agents.

Reacts with alkalis (bases)

Acetone reacts violently with phosphorous oxychloride.

· Hazardous decomposition products: Carbon monoxide and carbon dioxide

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:						
67-64-1	aceton	ne e				
Oral	LD50	5800 mg/kg (rat)				
Dermal	LD50	20000 mg/kg (rabbit)				

- · Primary irritant effect:
- · on the skin: May irritate the skin.
- · on the eye:

Irritating effect.

Vapors may be irritating to the eyes.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 8)

Printing Date 11/18/2016 Revision Number 1 Revision Date 11/18/2016

Trade name: Quick-Tac 2 (Liquid)

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

(Contd. of page 7)

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must be specially treated adhering to official regulations.
- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

1 4 700		C	
14 Trans	nort in	torma	tion
IT II WILLS		UI III W	עושעו

	$N_{1}$	

· DOT, IMDG, IATA

UN1090

· UN proper shipping name

Acetone

· IMDG, IATA **ACETONE** 

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

· Label

· IMDG, IATA



3 Flammable liquids · Class

· Label

· Packing group

II· DOT, IMDG, IATA

· Environmental hazards: Not applicable.

· Special precautions for user Warning: Flammable liquids

· Danger code (Kemler): 33

F-E,S-D· EMS Number:  $\boldsymbol{E}$ 

· Stowage Category

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

UN 1090 ACETONE, 3, II · UN "Model Regulation":

Printing Date 11/18/2016 Revision Number 1 Revision Date 11/18/2016

Trade name: Quick-Tac 2 (Liquid)

(Contd. of page 8)

# 15 Regulatory information · Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara · Section 355 (extremely hazardous substances): None of the ingredients is listed. · Section 313 (Specific toxic chemical listings): None of the ingredients is listed. · TSCA (Toxic Substances Control Act): All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements. · Proposition 65 · Chemicals known to cause cancer: 99-97-8 N,N-dimethyl-p-toluidine · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. · (DSL) Canada Dosmestic Substance List All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements. · New Jersey Right-to-Know List: 67-64-1 acetone · New Jersey Special Hazardous Substance List: 67-64-1 acetone F3 · Pennsylvania Right-to-Know List: 67-64-1 acetone · Pennsylvania Special Hazardous Substance List: E67-64-1 acetone · Cancerogenity categories · EPA (Environmental Protection Agency) 67-64-1 acetone Ι · TLV (Threshold Limit Value established by ACGIH) 67-64-1 acetone A4· MAK (German Maximum Workplace Concentration) None of the ingredients is listed. · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed.

· National regulations:

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 10)

Printing Date 11/18/2016 Revision Number 1 Revision Date 11/18/2016

Trade name: Quick-Tac 2 (Liquid)

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- · Department issuing SDS: Environment protection department.
- · Creation Date: 11/18/2016
- · Date of preparation / last revision 11/18/2016 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

 $DOT: \ US \ Department \ of \ Transportation$ 

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

USA