

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

**SECTION 1. IDENTIFICATION**

Product name : CONAP® CE-1170 Acrylic Coating

**Manufacturer or supplier's details**

Company : ELANTAS PDG, INC.  
5200 North 2nd Street  
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : [www.elantas.com](http://www.elantas.com)

E-mail address : [Todd.Thomas@altana.com](mailto:Todd.Thomas@altana.com)

Emergency telephone number : INFOTRAC - 1-800-535-5053

**Recommended use of the chemical and restrictions on use**

Recommended use :

Restrictions on use : Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2B

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2

**GHS label elements**

Hazard pictograms :



Signal word : Warning

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

- Hazard statements : H226 Flammable liquid and vapour.  
 H315 + H320 Causes skin and eye irritation.  
 H317 May cause an allergic skin reaction.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H361 Suspected of damaging fertility or the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements : **Prevention:**  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P362 Take off contaminated clothing and wash before reuse.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
**Storage:**  
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403 + P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
**Disposal:**

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**
**Hazardous components**

Component	CAS-No.	Concentration (%)
Toluene	108-88-3	>= 36 - < 37
Xylene	1330-20-7	>= 26 - < 27
Ethyl benzene (component of Xylene)	100-41-4	>= 6 - < 7
n-Butyl methacrylate	97-88-1	>= 0.1 - < 1

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

Dry chemical

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
 For safety reasons in case of fire, cans should be stored separately in closed containments.  
 Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
 Remove all sources of ignition.  
 Evacuate personnel to safe areas.  
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
 Prevent further leakage or spillage if safe to do so.  
 If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Avoid formation of aerosol.  
 Do not breathe vapours/dust.  
 Avoid exposure - obtain special instructions before use.  
 Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Take precautionary measures against static discharges.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Open drum carefully as content may be under pressure.

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

Dispose of rinse water in accordance with local and national regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.  
 No smoking.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m <sup>3</sup>	OSHA P0
		STEL	150 ppm 560 mg/m <sup>3</sup>	OSHA P0
Xylene	1330-20-7	TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
		STEL	150 ppm 655 mg/m <sup>3</sup>	OSHA P0
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
Ethyl benzene (component of Xylene)	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
		STEL	125 ppm 545 mg/m <sup>3</sup>	OSHA P0

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

- Engineering measures** : Use with adequate ventilation.  
All application areas should be ventilated in accordance with applicable OSHA regulations. (29 CFR 1910.94)
- Personal protective equipment**
- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available  
: > 203 °F (> 95 °C)
- Vapour pressure : No data available
- Flash point : 45 °F (7 °C)  
Method: No information available.  
Information taken from reference works and the literature.
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.93 g/cm <sup>3</sup> (77 °F (25 °C))
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 22 mm <sup>2</sup> /s (104 °F (40 °C))

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Hazardous decomposition products	: Carbon monoxide in a fire. Nitrogen oxides in a fire.

**SECTION 11. TOXICOLOGICAL INFORMATION**
**Information on likely routes of exposure**
**Acute toxicity**
**Product:**

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

Acute oral toxicity : Acute toxicity estimate : 4,253 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 33.51 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

**Components:****108-88-3 Toluene:**

Acute oral toxicity : LD50 (Rat): 2,600 mg/kg

**1330-20-7 Xylene:**Acute oral toxicity : LD50 (Rat, male): 3,523 mg/kg  
Method: Directive 67/548/EEC, Annex V, B.1.Acute inhalation toxicity : LC50 (Rat): 5000 ppm  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

**100-41-4 Ethyl benzene (component of Xylene):**

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

**97-88-1 n-Butyl methacrylate:**

Acute oral toxicity : LD50 (Rat): 18,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4910 ppm

Acute dermal toxicity : LD50 (Rabbit): 10,300 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation and/or dermatitis.

**Components:****1330-20-7 Xylene:**

Species: Rabbit

Result: Moderate skin irritation

**100-41-4 Ethyl benzene (component of Xylene):**

Species: Rabbit

Result: Moderate skin irritation



**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

**97-88-1 n-Butyl methacrylate:**

Species: Rabbit

Result: Severe skin irritation

**Serious eye damage/eye irritation****Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:****1330-20-7 Xylene:**

Species: Rabbit

Result: Eye irritation

**100-41-4 Ethyl benzene (component of Xylene):**

Species: Rabbit

Result: Moderate eye irritation

**97-88-1 n-Butyl methacrylate:**

Species: Rabbit

Result: Eye irritation

**Respiratory or skin sensitisation****Product:**

Remarks: Causes sensitisation.

**Components:****97-88-1 n-Butyl methacrylate:**

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Causes sensitisation.

GLP: yes

**Carcinogenicity****IARC**

Group 2B: Possibly carcinogenic to humans

Ethyl benzene (component of  
Xylene)

100-41-4

**ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: No data available

**SECTION 13. DISPOSAL CONSIDERATIONS**
**Disposal methods**

EPA Hazardous Waste Code(s)

: D001: D001: Ignitability  
D018: Benzene

Waste from residues

: Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

UN/ID No. : UN 1866  
Proper shipping name : Resin solution  
Class : 3  
Packing group : II  
Labels : Flammable liquid  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

**IMDG-Code**

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

UN/ID/NA number : UN 1866  
Proper shipping name : Resin solution  
Class : 3  
Packing group : II  
Labels : Flammable liquid  
ERG Code : 127  
Marine pollutant : no

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act**

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

**US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	382

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Toluene	108-88-3	36.8 %
Xylene	1330-20-7	26.1 %
Ethyl benzene (component of Xylene)	100-41-4	6.6 %

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Toluene	108-88-3	36.8 %
Xylene	1330-20-7	26.1 %
Ethyl benzene (component of Xylene)	100-41-4	6.6 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Toluene	108-88-3	36.8 %
Xylene	1330-20-7	26.1 %
Ethyl benzene (component of Xylene)	100-41-4	6.6 %

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017

Print Date 11/03/2017

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

**US State Regulations**
**Massachusetts Right To Know**

Toluene	108-88-3
Xylene	1330-20-7
Ethyl benzene (component of Xylene)	100-41-4
Benzene	71-43-2
Ethyl acrylate	140-88-5

**Pennsylvania Right To Know**

Toluene	108-88-3
Acrylic Polymers	Not Assigned
Xylene	1330-20-7
Ethyl benzene (component of Xylene)	100-41-4
Cumene (component of Solvent naphtha, petroleum, light aromatic)	98-82-8

**New Jersey Right To Know**

Toluene	108-88-3
Acrylic Polymers	Not Assigned
Xylene	1330-20-7
Ethyl benzene (component of Xylene)	100-41-4

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : Not Applicable

**California Prop 65**

WARNING! This product contains a chemical known to the State of California to cause cancer.

Ethyl benzene (component of Xylene)	100-41-4
Cumene (component of Solvent naphtha, petroleum, light aromatic)	98-82-8
Benzene	71-43-2
Ethyl acrylate	140-88-5

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Toluene	108-88-3
Benzene	71-43-2

**The components of this product are reported in the following inventories:**

TSCA : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

Section 4 / 12(b) : Not applicable

**CONAP® CE-1170 Acrylic Coating**

Version 1

Revision Date 09/28/2017


Print Date 11/03/2017

Section 5

Not applicable

DSL

: We certify that all of the components of this product are listed on the DSL.

**SECTION 16. OTHER INFORMATION**
**Further information**
**NFPA:**

**HMIS III:**

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

Revision Date

: 09/28/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.