

# product information

## tesa® 4334 Precision Mask®

High grade paper masking tape for precise and flat paint edges

The tesa® Precision Mask® 4334 reliably guarantees razor-sharp paint edges, and is extremely easy to use at the same time - thanks to the ideal combination of the special, supple backing and the perfectly balanced acrylic adhesive compound. This helps the tape to stick extremely flush to the surface and prevent paint tears. The combination of professional painting tape and your skilled expertise will result in paintwork to please your customers. In addition, the high quality of the painting tape will save you expensive touch-up work.

The tesa® Precision Mask® 4334 is also recommended for masking applications during spray painting with afterwards oven drying up to 120°C/ 30min. Due to the thin and low elongating backing it is perfectly suited for two-tone applications, e.g. straight and long lines.

### Main Application

- Indoor masking (up to 6 months) \* Outdoor masking (up to 8 weeks) \* For smooth and slightly textured surfaces \* For high-quality painting and lacquering work \* For spray painting with afterwards oven drying up to 120°C/30 min

### Technical Data

▪ Backing material	flat paper	▪ Elongation at break	4 %
▪ Total thickness	90 µm	▪ Tensile strength	30 N/cm
▪ Type of adhesive	acrylic	▪ UV-resistance	8 weeks
▪ Adhesion to steel	1.85 N/cm		

### Properties

▪ Hand tearability	●●●●	▪ Paint anchorage	●●●●
▪ Suitable for sensitive surfaces	●●●	▪ Sharp colour edge	●●●●
▪ Suitable for rough surfaces	●●●	▪ Conformability	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04334>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.