

HARDENER 2080 B

Version 1.0 Revision Date: 11/30/2020 SDS Number: 400000010343 Date of last issue: -
 Date of first issue: 11/30/2020

Print Date 12/07/2021

SECTION 1. IDENTIFICATION

Product name : HARDENER 2080 B

Manufacturer or supplier's details

Company name of supplier : Huntsman Advanced Materials Americas LLC
 Address : P.O. Box 4980
 The Woodlands,
 TX 77387

United States of America (USA)

Telephone : Non-Emergency: (800) 257-5547

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Short-term (acute) aquatic hazard : Category 1

Long-term (chronic) aquatic hazard : Category 1



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H410 Very toxic to aquatic life with long lasting effects.

HARDENER 2080 B

Version 1.0 Revision Date: 11/30/2020 SDS Number: 400000010343 Date of last issue: -
 Date of first issue: 11/30/2020

Print Date 12/07/2021

Precautionary statements : **Prevention:**
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.
Response:
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P391 Collect spillage.
Storage:
 Not available
Disposal:
 P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
aluminium hydroxide	21645-51-2	20 - 30
dibenzoyl peroxide	94-36-0	10 - 20
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	10 - 20
silicon dioxide	7631-86-9	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Treat symptomatically.

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

- Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Exercise caution when using a high volume water jet as it may scatter and spread fire
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Metal oxides
Carbon oxides
Halogenated compounds
- Specific extinguishing methods : No data is available on the product itself.

HARDENER 2080 B

Version 1.0 Revision Date: 11/30/2020 SDS Number: 400000010343 Date of last issue: -
Date of first issue: 11/30/2020

Print Date 12/07/2021

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Avoid dust formation. Avoid breathing dust. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. Avoid formation of respirable particles. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.
- Materials to avoid : For incompatible materials please refer to Section 10 of this

HARDENER 2080 B

Version 1.0 Revision Date: 11/30/2020 SDS Number: 400000010343 Date of last issue: -
Date of first issue: 11/30/2020

Print Date 12/07/2021

SDS.

Recommended storage temperature : 36 - 46 °F / 2 - 8 °C

Further information on storage stability : Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
aluminium hydroxide	21645-51-2	TWA (Respirable particulate matter)	1 mg/m ³ (Aluminium)	ACGIH
dibenzoyl peroxide	94-36-0	TWA	5 mg/m ³	ACGIH
		TWA	5 mg/m ³	OSHA Z-1
		TWA	5 mg/m ³	NIOSH REL
		TWA	5 mg/m ³	OSHA P0
silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL
		TWA	6 mg/m ³ (Silica)	NIOSH REL

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : butyl-rubber
Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 h

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

Material	: Nitrile rubber
Break through time	: 10 - 480 min
Remarks	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Colour	: grey
Odour	: slight
Odour Threshold	: No data is available on the product itself.
pH	: No data is available on the product itself.
Melting point/freezing point	: No data is available on the product itself.
Boiling point	: No data is available on the product itself.
Flash point	: No data is available on the product itself.
Evaporation rate	: No data is available on the product itself.
Flammability (solid, gas)	: No data is available on the product itself.
Flammability (liquids)	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

Lower explosion limit / Lower flammability limit	:	No data is available on the product itself.
Vapour pressure	:	No data is available on the product itself.
Relative vapour density	:	No data is available on the product itself.
Relative density	:	No data is available on the product itself.
Density	:	1.37 - 1.38 g/cm ³ (77 °F / 25 °C)
Solubility(ies)		
Water solubility	:	immiscible, insoluble
Solubility in other solvents	:	No data is available on the product itself.
Partition coefficient: n-octanol/water	:	No data is available on the product itself.
Auto-ignition temperature	:	No data is available on the product itself.
Decomposition temperature	:	Decomposition energy (mass): 260 KJ/kg
Self-Accelerating decomposition temperature (SADT)	:	122 °F / 50 °C
Viscosity		
Viscosity, dynamic	:	60,000 - 80,000 mPa.s (77 °F / 25 °C)
Explosive properties	:	No data is available on the product itself.
Oxidizing properties	:	No data is available on the product itself.
Particle size	:	No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Dust may form explosive mixture in air.
Conditions to avoid	:	None known.
Incompatible materials	:	None known.
Hazardous decomposition products	:	aluminium oxide carbon dioxide carbon monoxide Halogenated compounds

HARDENER 2080 B

Version 1.0 Revision Date: 11/30/2020 SDS Number: 400000010343 Date of last issue: -
Date of first issue: 11/30/2020

Print Date 12/07/2021

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxicity**Components:**

aluminium hydroxide:

Acute oral toxicityComponents : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

dibenzoyl peroxide:

Acute oral toxicityComponents : LD50 (Mouse, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicityComponents : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: No mortality observed at this dose.

silicon dioxide:

Acute oral toxicityComponents : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Components:

dibenzoyl peroxide:

Acute inhalation toxicity : LC50 (Rat, male): > 24.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

silicon dioxide:

Acute inhalation toxicity : LC50 (Rat, male and female): > 58.8 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Components:

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

silicon dioxide:

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation**Components:**

dibenzoyl peroxide:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Exposure time: 4 h

Assessment: Irritating to skin.

Method: OECD Test Guideline 404

Result: Irritating to skin.

silicon dioxide:

Species: Rabbit

Assessment: No skin irritation

Method: OECD Test Guideline 404

Result: No skin irritation

Serious eye damage/eye irritation**Components:**

dibenzoyl peroxide:

Species: Rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Result: Irritating to eyes.

Assessment: Irritating to eyes.

Method: OECD Test Guideline 405

silicon dioxide:

Species: Rabbit

Result: No eye irritation

Assessment: No eye irritation

Method: OECD Test Guideline 405

HARDENER 2080 B

Version 1.0 Revision Date: 11/30/2020 SDS Number: 400000010343 Date of last issue: -
 Date of first issue: 11/30/2020

Print Date 12/07/2021

Respiratory or skin sensitisation**Components:**

dibenzoyl peroxide:
 Exposure routes: Skin
 Species: Mouse
 Assessment: May cause sensitisation by skin contact.
 Method: OECD Test Guideline 429
 Result: Causes sensitisation.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Test Type: Local lymph node assay (LLNA)
 Exposure routes: Skin
 Species: Mouse
 Method: OECD Test Guideline 429
 Result: The product is a skin sensitiser, sub-category 1B.

Assessment: No data available

Germ cell mutagenicity**Components:**

dibenzoyl peroxide:
 Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 476
 Result: negative

Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
 Test system: mouse lymphoma cells
 Metabolic activation: without metabolic activation
 Result: positive

Test Type: reverse mutation assay
 Test system: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
 Result: negative

silicon dioxide:
 Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 473
 Result: negative

Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 476
 Result: negative

Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative

HARDENER 2080 B

Version 1.0 Revision Date: 11/30/2020 SDS Number: 400000010343 Date of last issue: -
Date of first issue: 11/30/2020

Print Date 12/07/2021

Components:

dibenzoyl peroxide:
Genotoxicity in vivo : Cell type: Somatic
Application Route: Intraperitoneal injection
Dose: 0, 50, 100, 200 mg/kg b.w.
Method: OECD Test Guideline 474
Result: negative

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo : Test Type: in vivo assay
Species: Mouse (male)
Cell type: Germ
Application Route: Oral
Dose: 3333, 10000 mg/kg
Result: negative

Test Type: gene mutation test
Species: Rat (male)
Cell type: Somatic
Application Route: Oral
Dose: 50,250,500,1000 mg/kg bw/day
Method: OECD Test Guideline 488
Result: negative

silicon dioxide:
Genotoxicity in vivo : Application Route: Inhalation
Dose: 50 mg/m³
Result: negative

Germ cell mutagenicity-
Assessment : No data available

Carcinogenicity**Components:**

dibenzoyl peroxide:
Species: Mouse, male and female
Application Route: Dermal
Exposure time: 104 weeks
Result: negative

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male
Application Route: Oral
Exposure time: 24 month(s)
Dose: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment: 7 days/week
NOAEL: 15 mg/kg bw/day

Method: OECD Test Guideline 453
Result: negative
Target Organs: Digestive organs

Species: Mouse, male

HARDENER 2080 B

Version 1.0 Revision Date: 11/30/2020 SDS Number: 400000010343 Date of last issue: -
Date of first issue: 11/30/2020

Print Date 12/07/2021

Application Route: Dermal
Exposure time: 24 month(s)
Dose: 0, 0.1, 10, 100 mg/kg bw/day
Frequency of Treatment: 3 days/week
NOEL: 0.1 mg/kg body weight

Method: OECD Test Guideline 453
Result: negative
Target Organs: Digestive organs

Species: Rat, female
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 0.1, 100, 1000 mg/kg bw/day
Frequency of Treatment: 5 days/week
NOEL: 100 mg/kg body weight

Method: OECD Test Guideline 453
Result: negative

Species: Rat, female
Application Route: Oral
Exposure time: 24 month(s)
Dose: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment: 7 days/week
NOAEL: 100 mg/kg bw/day

Method: OECD Test Guideline 453
Result: negative
Target Organs: Digestive organs

Species: Rat, females
Application Route: Oral
Exposure time: 24 month(s)
Dose: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment: 7 days/week
NOEL: 2 mg/kg bw/day

Method: OECD Test Guideline 453
Result: negative
Target Organs: Digestive organs

silicon dioxide:
Species: Rat, male and female
Application Route: Oral
Exposure time: 103 weeks
Dose: 1800 - 3200 mg/kg
Frequency of Treatment: 7 daily
Method: OECD Test Guideline 453
Result: negative

Carcinogenicity - Assessment : No data available

IARC Group 1: Carcinogenic to humans
silicon dioxide

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

(Silica dust, crystalline)

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Known to be human carcinogen
silicon dioxide
(Silica, Crystalline (Respirable Size))

Reproductive toxicity**Components:**

dibenzoyl peroxide:
Effects on fertility

: Species: Rat, male and female
Application Route: Oral
Dose: 0, 250, 500, 1,000 mg/kg b.w/
General Toxicity - Parent: No observed adverse effect level:
500 mg/kg body weight
General Toxicity F1: No observed adverse effect level: 500
mg/kg body weight
Method: OECD Test Guideline 422

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 0, 50, 180, 540 or 750 milligram per kilogram
Duration of Single Treatment: 238 d
Frequency of Treatment: 1 daily
General Toxicity - Parent: No-observed-effect level: 540
mg/kg body weight
General Toxicity F1: No-observed-effect level: 750 mg/kg
body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic
development were detected.

Components:

dibenzoyl peroxide:
Effects on foetal
development

: Species: Rat
Dose: 100, 300 or 1000 mg/kg/day
General Toxicity Maternal: No observed adverse effect level:
300 mg/kg body weight
Developmental Toxicity: No observed adverse effect level:
300 mg/kg body weight
Method: OECD Test Guideline 414

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit, female
Application Route: Dermal

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

Dose: 0, 30, 100 or 300 milligram per kilogram
Duration of Single Treatment: 28 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level:
30 mg/kg body weight
Developmental Toxicity: No observed adverse effect level:
300 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rabbit, female
Application Route: Oral
Dose: 0, 20, 60 or 180 milligram per kilogram
Duration of Single Treatment: 13 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level:
60 mg/kg body weight
Developmental Toxicity: No observed adverse effect level:
180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 0, 60, 180 and 540 milligram per kilogram
Duration of Single Treatment: 10 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level:
180 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: >
540 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

silicon dioxide:

Species: Mouse
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
1,340 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rabbit
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
1,600 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
1,350 mg/kg body weight
Method: OECD Test Guideline 414

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity**Components:**

dibenzoyl peroxide:

Species: Rat, male and female

NOAEL: > 100 mg/kg

Application Route: Skin contact

Number of exposures: 2 years

Method: OECD Test Guideline 451

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: oral (gavage)

Exposure time: 14 Weeks

Number of exposures: 7 d

Dose: 0, 50, 250, 1000 mg/kg/day

Method: OECD Test Guideline 408

Species: Rat, male and female

NOAEL: >= 10 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks

Number of exposures: 5 d

Dose: 0, 10, 100, 1000 mg/kg/day

Method: OECD Test Guideline 411

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks

Number of exposures: 3 d

Dose: 0, 1, 10, 100 mg/kg/day

Method: OECD Test Guideline 411

silicon dioxide:

Species: Rat, male and female

NOEC: 4000 - 4500 mg/m³

Application Route: Ingestion

Test atmosphere: dust/mist

Exposure time: 13 Weeks

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

Number of exposures: 7 d
Method: OECD Test Guideline 413

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:**

aluminium hydroxide:

Toxicity to fish : LC50: > 10,000 mg/l
Exposure time: 96 h

dibenzoyl peroxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.0602 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

HARDENER 2080 B

Version 1.0 Revision Date: 11/30/2020 SDS Number: 400000010343 Date of last issue: -
Date of first issue: 11/30/2020

Print Date 12/07/2021

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

silicon dioxide:
Toxicity to fish : LL50 (Brachydanio rerio (zebrafish)): > 10,000 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Components:

aluminium hydroxide:
Toxicity to daphnia and other : EC50: > 10,000 mg/l
aquatic invertebrates Exposure time: 48 h

dibenzoyl peroxide:
Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.11 mg/l
aquatic invertebrates Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

silicon dioxide:
Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): >= 1,000 mg/l
aquatic invertebrates Exposure time: 24 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Components:

dibenzoyl peroxide:
Toxicity to algae/aquatic : EbC50 (Selenastrum capricornutum (green algae)): 0.0422
plants mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Toxicity to algae/aquatic : EC50: 11 mg/l
plants Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

NOEC: 4.2 mg/l
Exposure time: 72 h

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

Test Type: static test
 Test substance: Fresh water
 Method: EPA-660/3-75-009

silicon dioxide:

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
 Exposure time: 72 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 201

Components:

dibenzoyl peroxide:
 M-Factor (Acute aquatic toxicity) : 10
 Toxicity to fish (Chronic toxicity) : No data available

Components:

dibenzoyl peroxide:
 Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 0.001 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Method: OECD Test Guideline 211

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.3 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 211

Components:

dibenzoyl peroxide:
 M-Factor (Chronic aquatic toxicity) : 10

Components:

dibenzoyl peroxide:
 Toxicity to microorganisms : EC50 (activated sludge): 35 mg/l
 Exposure time: 0.5 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 209

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
 Exposure time: 3 h
 Test Type: static test
 Test substance: Fresh water

Toxicity to soil dwelling organisms : No data available

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment
Acute aquatic toxicity : No data available**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Persistence and degradability**Components:**

dibenzoyl peroxide:

Biodegradability : Inoculum: activated sludge
Concentration: 4 mg/l
Result: Readily biodegradable.
Biodegradation: 68 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge, non-adapted
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

HARDENER 2080 B

Version 1.0 Revision Date: 11/30/2020 SDS Number: 400000010343 Date of last issue: -
Date of first issue: 11/30/2020

Print Date 12/07/2021

Physico-chemical
removability : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Stability in water : Degradation half life(DT50): 4.83 d (77 °F / 25 °C) pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life(DT50): 7.1 d (77 °F / 25 °C) pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life(DT50): 3.58 d (77 °F / 25 °C) pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

Photodegradation : No data available

Impact on Sewage
Treatment : No data available

Bioaccumulative potential**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Components:

dibenzoyl peroxide:
Partition coefficient: n-
octanol/water : log Pow: 3.2 (72 °F / 22 °C)
pH: 7.02
Method: OECD Test Guideline 117

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Partition coefficient: n-
octanol/water : log Pow: 3.242 (77 °F / 25 °C)
pH: 7.1
Method: OECD Test Guideline 117

Mobility in soil

Mobility : No data available

Components:

dibenzoyl peroxide:
Distribution among
environmental compartments : Koc: 6309.57
Method: OECD Test Guideline 121

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Distribution among
environmental compartments : Koc: 445
Stability in soil : No data available

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

Other adverse effects

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information - Product : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulations**

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

IATA

UN/ID No.	: UN 3077
Proper shipping name	: Environmentally hazardous substance, solid, n.o.s. (DIBENZOYL PEROXIDE)
Class	: 9
Packing group	: III
Labels	: Miscellaneous
Packing instruction (cargo aircraft)	: 956
Packing instruction (passenger aircraft)	: 956
Environmentally hazardous	: yes

IMDG

UN number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (DIBENZOYL PEROXIDE)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**DOT Classification**

UN/ID/NA number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (DIBENZOYL PEROXIDE)
Class	: 9
Packing group	: III
Labels	: CLASS 9
ERG Code	: 171
Marine pollutant	: yes(DIBENZOYL PEROXIDE)
Remarks	: Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

SECTION 15. REGULATORY INFORMATION**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 311/312 Hazards : Respiratory or skin sensitisation
 Skin corrosion or irritation
 Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

dibenzoyl peroxide 94-36-0 >= 10 - < 20 %

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

WARNING: This product can expose you to chemicals including silicon dioxide, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL	: This product contains one or several components that are not on the Canadian DSL nor NDSL.
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: Not in compliance with the inventory
PICCS	: Not in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On or in compliance with the active portion of the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.

HARDENER 2080 B

Version 1.0 Revision Date: 11/30/2020 SDS Number: 400000010343 Date of last issue: -
 Date of first issue: 11/30/2020

Print Date 12/07/2021


US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

- Revision Date : 11/30/2020
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-3 / TWA : 8-hour time weighted average

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

HARDENER 2080 B

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/30/2020	400000010343	Date of first issue: 11/30/2020

Print Date 12/07/2021

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006