

product information

tesa® 4985 Tacky transfer tape

tesa® 4985 is a transparent transfer tape using a modified acrylic adhesive. It offers good immediate grab to uneven surfaces.

tesa® 4985 features especially:

- Excellent conformability due to transfer tape construction
- Good dispensing properties

Main Application

- Mounting of posters and photos
- Mounting of fabric for pattern books
- Splicing of paper

Technical Data

▪ Backing material	none	▪ Colour of liner	brown
▪ Total thickness	50 µm	▪ Thickness of liner	71 µm
▪ Type of adhesive	tackified acrylic	▪ Weight of liner	80 g/m ²
▪ Type of liner	glassine		

Adhesion to

▪ Steel (initial)	8.0 N/cm	▪ Steel (after 14 days)	11.1 N/cm
▪ ABS (initial)	6.9 N/cm	▪ ABS (after 14 days)	9.3 N/cm
▪ Aluminium (initial)	7.1 N/cm	▪ Aluminium (after 14 days)	10.0 N/cm
▪ PC (initial)	7.6 N/cm	▪ PC (after 14 days)	9.7 N/cm
▪ PE (initial)	4.1 N/cm	▪ PE (after 14 days)	4.9 N/cm
▪ PET (initial)	4.9 N/cm	▪ PET (after 14 days)	6.4 N/cm
▪ PP (initial)	3.5 N/cm	▪ PP (after 14 days)	5.7 N/cm
▪ PS (initial)	7.2 N/cm	▪ PS (after 14 days)	9.5 N/cm
▪ PVC (initial)	6.8 N/cm	▪ PVC (after 14 days)	9.4 N/cm

Properties

▪ Temperature resistance short term	200 °C	▪ Softener resistance	●●●●
▪ Temperature resistance long term	80 °C	▪ Static shear resistance at 23°C	●●
▪ Tack	●●●●	▪ Static shear resistance at 40°C	●
▪ Ageing resistance (UV)	●●●●		
▪ Humidity resistance	●●●●		
▪ Resistance to chemicals	●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04985>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.