

Safety Data Sheet
acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

1 Identification

- **Product identifier**
- **Trade name:** *MP54190 Grey (Epoxy Resin)*
- **Relevant identified uses of the substance or mixture.** *Adhesive*
- **Application of the substance / the mixture** *Adhesive*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Adhesive Systems, Inc.
A Division of Royal Adhesives & Sealants, LLC
9411 Corsair Road
Frankfort, Illinois 60423
Phone Number: 800-552-0299*
- **Information department:** *Environment protection department.*
- **Emergency telephone number:**
*ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)*

2 Hazard(s) identification

- **Classification of the substance or mixture**



- Skin Irrit. 2 H315 Causes skin irritation.*
- Eye Irrit. 2A H319 Causes serious eye irritation.*
- Skin Sens. 1 H317 May cause an allergic skin reaction.*
- STOT SE 3 H335 May cause respiratory irritation.*

- **Label elements**
- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



- **Signal word** *Warning*
- **Hazard statements**
*Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.*
- **Precautionary statements**
*Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves / eye protection / face protection.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.*

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Grey (Epoxy Resin)

(Contd. of page 1)

Contaminated work clothing must not be allowed out of the workplace.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**




Health = 2

Fire = 1

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 1

Physical Hazard = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Adhesive

· **Hazardous components:**

25068-38-6	Bisphenol A Epoxy Resin	50-100%
25036-25-3	epoxy resin	2.5-10%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Seek medical treatment.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Grey (Epoxy Resin)

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
- **Protective equipment:** Protective clothing and respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

25068-38-6	Bisphenol A Epoxy Resin	90 mg/m ³
25036-25-3	epoxy resin	12 mg/m ³
106-89-8	1-chloro-2,3-epoxypropane	1.7 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m ³

· **PAC-2:**

25068-38-6	Bisphenol A Epoxy Resin	990 mg/m ³
25036-25-3	epoxy resin	130 mg/m ³
106-89-8	1-chloro-2,3-epoxypropane	24 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m ³

· **PAC-3:**

25068-38-6	Bisphenol A Epoxy Resin	5,900 mg/m ³
25036-25-3	epoxy resin	790 mg/m ³
106-89-8	1-chloro-2,3-epoxypropane	72 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m ³

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Grey (Epoxy Resin)

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Open and handle receptacle with care.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location away from direct heat.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment (see listings below)**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:** Not necessary if room is well-ventilated.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
Nitrile rubber, NBR
Chloroprene rubber, CR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Grey (Epoxy Resin)

(Contd. of page 4)

- Safety glasses with side shields.
- **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Color:	Not determined.
· Odor:	Characteristic
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· **Melting point:** Undetermined.

· **Boiling point:** >113 °C (>235 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** Not determined

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Flammable limits:**

· Lower:	Not determined
· Upper:	Not determined

· **Vapor pressure:** < 0.01 hPa

· **Specific gravity at 20 °C (68 °F):** 1.37 g/cm³ (11.433 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· Dynamic:	50000 mPas
· Kinematic:	Not determined.

· **Solvent content:**

· **Organic solvents:** 0.0 %

· **Solids content:** Not available

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Grey (Epoxy Resin)

(Contd. of page 5)

- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
 - **Possibility of hazardous reactions** No dangerous reactions known.
 - **Conditions to avoid** Avoid high temperatures. Avoid freezing.
 - **Incompatible materials:**
 - Reacts with oxidizing agents.
 - Reacts with amines.
 - Reacts with strong acids.
 - Reacts with bases.
 - **Hazardous decomposition products:**
 - Carbon monoxide
 - Carbon dioxide
 - Aldehydes
 - Acids
- At very high temperatures the following may be formed:
Formaldehyde

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Causes eye irritation.
- **Sensitization:** Skin Contact - Sensitization possible through skin contact.
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

106-89-8	1-chloro-2,3-epoxypropane	2A
----------	---------------------------	----

- **NTP (National Toxicology Program)**

106-89-8	1-chloro-2,3-epoxypropane	R
----------	---------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** At present there are no ecotoxicological assessments.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Grey (Epoxy Resin)

(Contd. of page 6)

- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

* 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

* 14 Transport information

- | | |
|--|---|
| · UN-Number | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · DOT, ADN, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · DOT, IMDG, IATA | not regulated |
| · Environmental hazards: | |
| · Marine pollutant: | Yes |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | The above DOT information applies to non-bulk containers. Not regulated by D.O.T. if in a container of 119 gallon capacity or less. |
| · UN "Model Regulation": | not regulated |

* 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

106-89-8	1-chloro-2,3-epoxypropane
----------	---------------------------

· **Section 313 (Specific toxic chemical listings):**

106-89-8	1-chloro-2,3-epoxypropane
----------	---------------------------

· **TSCA (Toxic Substances Control Act):**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Grey (Epoxy Resin)

(Contd. of page 7)

· **Proposition 65**

· **Chemicals known to cause cancer:**

106-89-8	1-chloro-2,3-epoxypropane
----------	---------------------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

106-89-8	1-chloro-2,3-epoxypropane
----------	---------------------------

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **(DSL) Canada Domestic Substance List**

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· **New Jersey Right-to-Know List:**

106-89-8	1-chloro-2,3-epoxypropane
----------	---------------------------

· **New Jersey Special Hazardous Substance List:**

106-89-8	1-chloro-2,3-epoxypropane	CA, MU, F3, R2
----------	---------------------------	----------------

· **Pennsylvania Right-to-Know List:**

106-89-8	1-chloro-2,3-epoxypropane
----------	---------------------------

· **Pennsylvania Special Hazardous Substance List:**

106-89-8	1-chloro-2,3-epoxypropane	ES
----------	---------------------------	----

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

106-89-8	1-chloro-2,3-epoxypropane	B2
----------	---------------------------	----

· **TLV (Threshold Limit Value established by ACGIH)**

106-89-8	1-chloro-2,3-epoxypropane	A3
----------	---------------------------	----

· **MAK (German Maximum Workplace Concentration)**

106-89-8	1-chloro-2,3-epoxypropane	2
----------	---------------------------	---

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

106-89-8	1-chloro-2,3-epoxypropane
----------	---------------------------

· **National regulations:**

· **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

· **Department issuing SDS:** Environment protection department.

· **Creation Date:** 02/22/2017

· **Date of preparation / last revision** 02/22/2017 / -

(Contd. on page 9)

USA

Safety Data Sheet
acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Grey (Epoxy Resin)

(Contd. of page 8)

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

USA

Safety Data Sheet
acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

1 Identification

- **Product identifier**
- **Trade name: MP54190 Gray Part B (Hardener)**
- **Relevant identified uses of the substance or mixture. Hardener**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Adhesive Systems, Inc.
A Division of Royal Adhesives & Sealants, LLC
9411 Corsair Road
Frankfort, Illinois 60423
Phone Number: 800-552-0299
- **Information department: Environment protection department.**
- **Emergency telephone number:**
ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

- **Classification of the substance or mixture**



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Warning
- **Hazard statements**
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
- **Precautionary statements**
Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves / eye protection / face protection.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Specific treatment (see on this label).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Gray Part B (Hardener)

(Contd. of page 1)

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 1

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2
FIRE	1
PHYSICAL HAZARD	0

Health = 2

Fire = 1

Physical Hazard = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description: Mixture**

· **Hazardous components:**

	polyamide	25-50%
61788-32-7	Hydrogenated Terphenyl	2.5-10%
	amino ethers	2.5-10%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Call a doctor immediately.

Overexposure, remove to fresh air and seek medical attention.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.

· **After swallowing:**

Rinse mouth with water.

Seek medical treatment.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

USA

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Gray Part B (Hardener)

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
- **Protective equipment:** Protective clothing and respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

	Polyamide	30 mg/m ³
26140-60-3	Terphenyl	0.45 mg/m ³
112-24-3	3,6-diazaoctanethylenediamin	3 ppm

· PAC-2:

	Polyamide	330 mg/m ³
26140-60-3	Terphenyl	5 mg/m ³
112-24-3	3,6-diazaoctanethylenediamin	14 ppm

· PAC-3:

	Polyamide	2,000 mg/m ³
26140-60-3	Terphenyl	1,400 mg/m ³
112-24-3	3,6-diazaoctanethylenediamin	83 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Open and handle receptacle with care.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Gray Part B (Hardener)

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location away from direct heat.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

61788-32-7 Hydrogenated Terphenyl

REL	Long-term value: 5 mg/m ³ , 0.5 ppm
TLV	Long-term value: 4.9 mg/m ³ , 0.5 ppm nonirradiated

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment (see listings below)**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Breathing equipment:**
Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**
Safety glasses with side shields.



Tightly sealed goggles

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Gray Part B (Hardener)

(Contd. of page 4)

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Liquid
· Color:	Black
· Odor:	Characteristic
· Odor threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

· Melting point:	Undetermined.
· Boiling point:	>221 °C (>430 °F)

· **Flash point:** >93 °C (>199 °F)· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 373 °C (703 °F)· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product does not present an explosion hazard.· **Flammable limits:**

· Lower:	Not determined
· Upper:	Not determined

· **Vapor pressure:** Not determined.· **Specific gravity at 20 °C (68 °F):** 1.31 g/cm³ (10.932 lbs/gal)· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**· **Water:** Not miscible or difficult to mix.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

· Dynamic:	70000 mPas
· Kinematic:	Not determined.

· **Solvent content:**· **Organic solvents:** 0.0 %· **Solids content:** Not available· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Gray Part B (Hardener)

(Contd. of page 5)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Avoid high temperatures. Avoid freezing.
- **Incompatible materials:** Reacts with oxidizing agents.
- **Hazardous decomposition products:**
Carbon monoxide
Carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Causes serious eye irritation.
- **Sensitization:** Skin Contact - Sensitization possible through skin contact.
- **Additional toxicological information:**
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1333-86-4 Carbon black

2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** At present there are no ecotoxicological assessments.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must be specially treated adhering to official regulations.

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Gray Part B (Hardener)

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

* 14 Transport information

- | | |
|--|---|
| · UN-Number
· DOT, ADN, IMDG, IATA | not regulated |
| · UN proper shipping name
· DOT, ADN, IMDG, IATA | not regulated |
| · Transport hazard class(es)
· DOT, ADN, IMDG, IATA
· Class | not regulated |
| · Packing group
· DOT, IMDG, IATA | not regulated |
| · Environmental hazards:
· Marine pollutant: | Yes |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | The above DOT information applies to non-bulk containers. Not regulated by D.O.T. if in a container of 119 gallon capacity or less. |
| · UN "Model Regulation": | not regulated |

* 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.
- **Section 313 (Specific toxic chemical listings):**
None of the ingredients is listed.
- **TSCA (Toxic Substances Control Act):**
All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.
- **Proposition 65**
- **Chemicals known to cause cancer:**
None of the ingredients is listed.
- **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.
- **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Gray Part B (Hardener)

(Contd. of page 7)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· (DSL) Canada Domestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· New Jersey Right-to-Know List:

26140-60-3	Terphenyl
112-24-3	3,6-diazaoctanethylenediamin
1333-86-4	Carbon black

· New Jersey Special Hazardous Substance List:

112-24-3	3,6-diazaoctanethylenediamin	CO
1333-86-4	Carbon black	CA

· Pennsylvania Right-to-Know List:

26140-60-3	Terphenyl
112-24-3	3,6-diazaoctanethylenediamin

· Pennsylvania Special Hazardous Substance List:

None of the ingredients is listed.

· Cancerogenity categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

1333-86-4	Carbon black	A4
-----------	--------------	----

· MAK (German Maximum Workplace Concentration)

1333-86-4	Carbon black	3B
-----------	--------------	----

· NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4	Carbon black
-----------	--------------

· National regulations:

- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* 16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

· **Department issuing SDS:** Environment protection department.

· **Creation Date:** 02/22/2017

· **Date of preparation / last revision** 02/22/2017 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing Date 02/22/2017

Revision Number 1

Revision Date 02/22/2017

Trade name: MP54190 Gray Part B (Hardener)

(Contd. of page 8)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1

USA