

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : Rodding Bonder  
 Product code : RD50

#### 1.2. Recommended use and restrictions on use

Recommended use : Adhesives, sealants  
 Restrictions on use : No additional information available

#### 1.3. Supplier

Integra Adhesives  
 600 Ellis Road  
 Durham, NC 27703 - USA  
 T 1-919-598-2400  
[www.integra-adhesives.com](http://www.integra-adhesives.com)

#### 1.4. Emergency telephone number

Emergency number : Transportation and Medical: CHEMTEL Tel. 800-255-3924; +1 813-248-0585 (International)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Flammable liquids, Category 2	H225 Highly flammable liquid and vapour.
Acute toxicity (oral), Category 4	H302 Harmful if swallowed.
Skin corrosion/irritation, Category 2	H315 Causes skin irritation.
Skin sensitisation, Category 1	H317 May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361 Suspected of damaging fertility or the unborn child.
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335 May cause respiratory irritation.

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapour.  
 H302 - Harmful if swallowed.  
 H315 - Causes skin irritation.  
 H317 - May cause an allergic skin reaction.  
 H335 - May cause respiratory irritation.  
 H361 - Suspected of damaging fertility or the unborn child.

Precautionary statements (GHS) :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 - Keep container tightly closed.  
 P240 - Ground/bond container and receiving equipment  
 P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P264 - Wash hands, forearms and face thoroughly after handling.  
 P270 - Do not eat, drink or smoke when using this product.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P272 - Contaminated work clothing must not be allowed out of the workplace.  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.

# Rodding Bonder

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - If on skin: Wash with plenty of water.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P312 - Call a poison center/doctor if you feel unwell  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P330 - Rinse mouth.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P363 - Wash contaminated clothing before reuse.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS\_US)

0.48% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS classification
Methyl methacrylate	(CAS-No.) 80-62-6	25 - 45	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)	(CAS-No.) 25068-38-6	1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
1,4 BUTANEDIOL DIMETHACRYLATE	(CAS-No.) 2082-81-7	1 - 2	Skin Sens. 1B, H317
DIBENZOYL PEROXIDE	(CAS-No.) 94-36-0	0.1 - 1	Org. Perox. B, H241 Eye Irrit. 2, H319 Skin Sens. 1, H317
Tricresylphosphate	(CAS-No.) 1330-78-5	0.1 - 1	Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,1'-(P-TOLYLIMINO)DIPROPAN-2-OL	(CAS-No.) 38668-48-3	0.1 - 1	Acute Tox. 2 (Oral), H300 Eye Irrit. 2A, H319 Aquatic Chronic 3, H412
pentaerythritol tetra(mercaptoacetate)	(CAS-No.) 10193-99-4	0.1 - 1	Acute Tox. 4 (Oral), H302 Skin Sens. 1A, H317

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: If skin irritation or rash occurs: Get medical advice/attention. Take off immediately all contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. Wash skin thoroughly with mild soap and water.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell.

# Rodding Bonder

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: Suspected of damaging fertility or the unborn child.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour. Flammable vapours may accumulate in the container.
Explosion hazard	: May form flammable/explosive vapour-air mixture. Heat may build pressure, rupturing closed containers.
Reactivity	: No dangerous reactions known under normal conditions of use.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Do not breathe aerosol. Do not breathe vapour. Do not get in eyes, on skin, or on clothing. Do NOT taste or swallow. Do not touch spilled material. Ensure adequate ventilation. Use personal protective equipment as required.
------------------	---

#### 6.1.1. For non-emergency personnel

Protective equipment	: Refer to section 8.2.
Emergency procedures	: Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment	: Refer to section 8.2.
Emergency procedures	: Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Use only non-sparking tools. Do not breathe vapours. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Do not breathe aerosol. Use personal protective equipment as required.

# Rodding Bonder

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.

Storage conditions : Keep only in the original container. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids. Strong oxidizers. Peroxides. amines. Halogens. Reducing agents.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Prohibitions on mixed storage : Incompatible materials.

Storage area : Store in dry, cool, well-ventilated area.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>Methyl methacrylate (80-62-6)</b>		
ACGIH	Local name	Methyl methacrylate
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	205 mg/m <sup>3</sup>
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	410 mg/m <sup>3</sup>
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; body weight eff; pulm edema. Notations: DSEN; A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	410 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	410 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
<b>1,4 BUTANEDIOL DIMETHACRYLATE (2082-81-7)</b>		
Not applicable		
<b>pentaerythritol tetra(mercaptoacetate) (10193-99-4)</b>		
Not applicable		
<b>1,1'-(P-TOLYLIMINO)DIPROPAN-2-OL (38668-48-3)</b>		
Not applicable		
<b>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</b>		
Not applicable		
<b>DIBENZOYL PEROXIDE (94-36-0)</b>		
ACGIH	Local name	Benzoyl peroxide
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	TLV® Basis: URT & skin irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
<b>Tricresylphosphate (1330-78-5)</b>		
Not applicable		

# Rodding Bonder

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Avoid creating mist or spray. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure good ventilation of the work station.
- Environmental exposure controls : Prevent leakage or spillage.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Butyl rubber gloves. Breakthrough time: > 66 min

#### Eye protection:

Chemical goggles or safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Approved organic vapour respirator. Appropriate dust or mist respirator should be used if airborne particles are generated when handling this material

#### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Viscous liquid.
- Colour : white
- Odour : Solvent
- Odour threshold : No data available
- pH : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : No data available
- Relative evaporation rate (butylacetate=1) : No data available
- Flammability (solid, gas) : Highly flammable liquid and vapour.
- Vapour pressure : No data available
- Relative vapour density at 20 °C : No data available
- Relative density : No data available
- Solubility : No data available
- Log Pow : No data available
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Viscosity, kinematic : No data available
- Viscosity, dynamic : 20000 – 160000 cP
- Explosive limits : No data available
- Explosive properties : No data available
- Oxidising properties : No data available

### 9.2. Other information

No additional information available

# Rodding Bonder

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

#### 10.2. Chemical stability

Stable under normal conditions. Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

#### 10.3. Possibility of hazardous reactions

Hazardous Polymerization may occur.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

#### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers. Peroxides. amines. Halogens. Reducing agents.

#### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>). Methyl methacrylate. hydrocarbons.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

ATE (oral)	1095.948 mg/kg bodyweight
Unknown acute toxicity (GHS_US)	0.48% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

<b>Methyl methacrylate (80-62-6)</b>	
LD50 oral rat	7900 – 9400 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
ATE (oral)	7900 mg/kg bodyweight
ATE (dust,mist)	29.8 mg/l/4h

<b>pentaerythritol tetra(mercaptoacetate) (10193-99-4)</b>	
LD50 oral rat	> 1000 (≤ 2000) mg/kg
LC50 inhalation rat (mg/l)	> 3363 mg/m <sup>3</sup>
ATE (oral)	2000 mg/kg bodyweight

<b>1,1'-(P-TOLYLIMINO)DIPROPAN-2-OL (38668-48-3)</b>	
ATE (oral)	5 mg/kg bodyweight

<b>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5 mg/l

<b>DIBENZOYL PEROXIDE (94-36-0)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight

<b>Tricresylphosphate (1330-78-5)</b>	
LD50 oral rat	> 20000 mg/kg
LC50 inhalation rat (mg/l)	> 11.1 mg/l 1 h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

<b>Methyl methacrylate (80-62-6)</b>	
IARC group	3 - Not classifiable

<b>DIBENZOYL PEROXIDE (94-36-0)</b>	
IARC group	3 - Not classifiable

# Rodding Bonder

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity : Suspected of damaging fertility or the unborn child.  
STOT-single exposure : May cause respiratory irritation.

### Methyl methacrylate (80-62-6)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Likely routes of exposure : Skin and eye contact. Inhalation.

Symptoms/effects : Suspected of damaging fertility or the unborn child.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Causes skin irritation. May cause an allergic skin reaction.

Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Methyl methacrylate (80-62-6)

LC50 fish 1 : > 79 mg/l 96 h

EC50 crustacea : 69 mg/l 48 h

#### pentaerythritol tetra(mercaptoacetate) (10193-99-4)

LC50 fish 1 : > 100 mg/l 96 h

EC50 crustacea : > 1.06 mg/l 48 h

#### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (25068-38-6)

LC50 fish 1 : 1.2 mg/l 96 h

EC50 crustacea : 2.8 mg/l 48 h

ErC50 (algae) : 101 ( $\geq$  100) mg/l

LOEC (acute) : 3.2 mg/l

NOEC (acute) : 1 mg/l

#### Tricresylphosphate (1330-78-5)

LC50 fish 1 : 0.6 mg/l 4 d

EC50 crustacea : 0.146 mg/l 2 d

NOEC (acute) : 0.56 mg/l 4 d

### 12.2. Persistence and degradability

#### Rodding Bonder

Persistence and degradability : May cause long-term adverse effects in the environment.

#### Methyl methacrylate (80-62-6)

Persistence and degradability : Readily biodegradable.

BOD (% of ThOD) : 94.3 % ThOD

#### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (25068-38-6)

Persistence and degradability : Readily biodegradable.

### 12.3. Bioaccumulative potential

#### Rodding Bonder

Bioaccumulative potential : Not established.

#### Methyl methacrylate (80-62-6)

Log Pow : 1.38

#### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (25068-38-6)

Log Pow :  $\geq$  2.918

Bioaccumulative potential : Not expected to bioaccumulate.

# Rodding Bonder

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Tricresylphosphate (1330-78-5)

Log Kow 5.93

#### 12.4. Mobility in soil

##### Rodding Bonder

Ecology - soil Not established.

#### 12.5. Other adverse effects

Other information : Avoid release to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Handle empty containers with care because residual vapours are flammable. Hazardous waste due to potential risk of explosion.  
Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1133 ADHESIVES, 3, II  
UN-No.(DOT) : UN1133  
Proper Shipping Name (DOT) : ADHESIVES  
Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Packing group (DOT) : II - Medium Danger  
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173  
DOT Packaging Bulk (49 CFR 173.xxx) : 242  
DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packagings may be increased to 5 L (1.3 gallons).  
383 - Packages containing toy plastic or paper caps for toy pistols described as "UN0349, Articles, explosive, n.o.s. (Toy caps), 1.4S" or "NA0337, Toy caps, 1.4S" are not subject to the subpart E (labeling) requirements of this part when offered for transportation by motor vehicle, rail freight, cargo vessel, and cargo aircraft and, notwithstanding the packing method assigned in §173.62 of this subchapter, in conformance with the following conditions:  
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).  
DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L



# Rodding Bonder

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

### Transport by sea

Transport document description (IMDG) : UN 1133 ADHESIVES, 3, II  
UN-No. (IMDG) : 1133  
Proper Shipping Name (IMDG) : ADHESIVES  
Class (IMDG) : 3 - Flammable liquids  
Packing group (IMDG) : II - substances presenting medium danger  
Limited quantities (IMDG) : 5 L

### Air transport

Transport document description (IATA) : UN 1133 ADHESIVES, 3, II  
UN-No. (IATA) : 1133  
Proper Shipping Name (IATA) : ADHESIVES  
Class (IATA) : 3 - Flammable Liquids  
Packing group (IATA) : II - Medium Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### Methyl methacrylate (80-62-6)

Subject to reporting requirements of United States SARA Section 313

EPA TSCA Regulatory Flag : T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.

CERCLA RQ : 1000 lb

#### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (25068-38-6)

EPA TSCA Regulatory Flag : XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

SARA Section 311/312 Hazard Classes : Immediate (acute) health hazard

#### DIBENZOYL PEROXIDE (94-36-0)

Subject to reporting requirements of United States SARA Section 313

#### Tricresylphosphate (1330-78-5)

EPA TSCA Regulatory Flag : T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.

### 15.2. International regulations

#### CANADA

#### Methyl methacrylate (80-62-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### 1,4 BUTANEDIOL DIMETHACRYLATE (2082-81-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### pentaerythritol tetra(mercaptoacetate) (10193-99-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### 1,1'-(P-TOLYLIMINO)DIPROPAN-2-OL (38668-48-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

# Rodding Bonder

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **DIBENZOYL PEROXIDE (94-36-0)**

Listed on the Canadian DSL (Domestic Substances List) inventory.

### **Tricresylphosphate (1330-78-5)**

Listed on the Canadian DSL (Domestic Substances List) inventory.

### **EU-Regulations**

#### **Methyl methacrylate (80-62-6)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### **1,4 BUTANEDIOL DIMETHACRYLATE (2082-81-7)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### **pentaerythritol tetra(mercaptoacetate) (10193-99-4)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### **1,1'-(P-TOLYLIMINO)DIPROPAN-2-OL (38668-48-3)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### **DIBENZOYL PEROXIDE (94-36-0)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### **Tricresylphosphate (1330-78-5)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### **National regulations**

#### **Methyl methacrylate (80-62-6)**

Listed on the Chinese Catalog of Hazardous Chemicals.  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

#### **1,4 BUTANEDIOL DIMETHACRYLATE (2082-81-7)**

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on Taiwan National Chemical Inventory  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

#### **pentaerythritol tetra(mercaptoacetate) (10193-99-4)**

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on Taiwan National Chemical Inventory  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

#### **1,1'-(P-TOLYLIMINO)DIPROPAN-2-OL (38668-48-3)**

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on Taiwan National Chemical Inventory  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

### **DIBENZOYL PEROXIDE (94-36-0)**

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on the Korea Designated Existing Substances List (First Batch).  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Chinese Catalog of Hazardous Chemicals.  
China List of Hazardous Chemicals for Priority Management- SAWS

# Rodding Bonder

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### DIBENZOYL PEROXIDE (94-36-0)

Not listed on Taiwan National Chemical Inventory.  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

### Tricresylphosphate (1330-78-5)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on Taiwan National Chemical Inventory  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Chinese Catalog of Hazardous Chemicals.  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

### 15.3. US State regulations

**WARNING:** This product can expose you to Dimethyl-p-toluidine, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Dimethyl-p-toluidine(99-97-8)	X					

Component	State or local regulations
Methyl methacrylate(80-62-6)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances; U.S. - Pennsylvania - RTK (Right to Know) List
DIBENZOYL PEROXIDE(94-36-0)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Tricresylphosphate(1330-78-5)	U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.  
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. Manufacturer Information. United Nations Economic Commission for Europe: About the GHS. Accessed at [http://www.unece.org/trans/danger/publi/ghs/ghs\\_welcome\\_e.html](http://www.unece.org/trans/danger/publi/ghs/ghs_welcome_e.html).

Other information : None.

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H241	Heating may cause a fire or explosion.
H300	Fatal if swallowed.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

# Rodding Bonder

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	European List of Waste (LoW) code
	LD50: Lethal Dose for 50% of the test population
	TWA: Time Weighted Average
	STEL: Short Term Exposure Limits
	PBT: Persistent, Bioaccumulative, Toxic
	WEL: Workplace Exposure Limit
vPvB	Very Persistent and Very Bioaccumulative

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.

NFPA reactivity

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



**SDS Prepared by:** The Redstone Group, dba SafeBridge Consultants, Inc.

110 Polaris Pkwy  
Suite 200  
Westerville, OH USA 43082  
P: +1 (614) 923-7472  
www.redstonegrp.com

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*