

Revision Number 1

Revision Date 11/14/2016

1 Identification

- · Product identifier
- · Trade name: Rodmaster 6600
- · Relevant identified uses of the substance or mixture. Adhesive
- · Application of the substance / the mixture Adhesives
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Chemical Concepts, Inc.

410 Pike Road

Huntingdon Valley, PA. 19006 Phone Number: 800.220.1966

· Emergency telephone number:

InfoTrac: 1.800.535.5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Muta. 2 H341 Suspected of causing genetic defects.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

 (Contd. on page 2)

- USA

Printing Date 11/17/2016 Revision Number 1 Revision Date 11/14/2016

Trade name: Rodmaster 6600

(Contd. of page 1)

· Hazard pictograms









GHS05

· Signal word Danger

Hazard statements

Highly flammable liquid and vapor.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

May cause respiratory irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dusts or mists.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If swallowed: Rinse mouth. Do NOT induce vomiting.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3

Reactivity = 2

· HMIS-ratings (scale 0 - 4)



2 Health = 2

Fire = 3

PHYSICAL HAZARD $\boxed{2}$ Physical Hazard = 2

(Contd. on page 3)

Printing Date 11/17/2016 Revision Number 1 Revision Date 11/14/2016

Trade name: Rodmaster 6600

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture

· Hazardous components:	
80-62-6 methyl methacrylate	25-50%
79-41-4 methacrylic acid	2.5-10%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Overexposure, remove to fresh air and seek medical attention.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- **Protective equipment:** Protective clothing and respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations. Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

Printing Date 11/17/2016 Revision Number 1 Revision Date 11/14/2016

Trade name: Rodmaster 6600

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Open and handle receptacle with care.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm REL Long-term value: 410 mg/m³, 100 ppm

TLV Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm DSEN

79-41-4 methacrylic acid

REL Long-term value: 70 mg/m³, 20 ppm Skin

TLV Long-term value: 70 mg/m³, 20 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

(Contd. on page 5)

Revision Date 11/14/2016 Printing Date 11/17/2016 Revision Number 1

Trade name: Rodmaster 6600

· Protection of hands:





Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

Face protection (face shield)

Body protection:

Protective work clothing

Emergency showers and eye wash stations should be available.

9 Physical and chemical properties

· Infori	mation	on basic	e physical	and c	chemical	properties
~						

· General Information

· Appearance:

Form: Liquid Off White Color: · Odor: Characteristic · Odor threshold: Not determined.

· pH-value at 20 °C (68 °F): 3.3

· Change in condition

Melting point: Undetermined. **Boiling point:** 101 °C (214 °F)

· Flash point: 10 °C (50 °F)

· Flammability (solid, gaseous): Not applicable.

430 °C (806 °F) · Ignition temperature:

Not determined. · Decomposition temperature:

Not determined.

· Auto igniting: Not determined.

· Danger of explosion:

· Flammable limits:

2.1 Vol % Lower: 12.5 Vol % *Upper:*

· Vapor pressure at 20 °C (68 °F): 28 mm Hg

· Specific gravity at 20 °C (68 °F): 1 g/cm³ (8.345 lbs/gal)

(Contd. on page 6)

Printing Date 11/17/2016 Revision Number 1 Revision Date 11/14/2016

Trade name: Rodmaster 6600

		(Contd. of page
Relative density	Not determined.	
Vapor density	>1 at 20C	
Evaporation rate	3	
Solubility in / Miscibility with		
Water:	Insoluble	
Partition coefficient (n-octano	l/water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.0 %	
Solids content:	Not available	
Other information	<20 grams/liter [mixed]	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Heat, flames, sparks.

Avoid high temperatures. Avoid freezing.

Avoid oxygen free atmospheres or inert blanketing.

· Incompatible materials:

Reacts with acids.

Reacts with oxidizing agents.

Reacts with alkalis (bases)

Halogens

Avoid contact with copper, brass and black iron.

· Hazardous decomposition products:

Carbon monoxide

Carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC5	0 valu	es that are relevant for classification:
		l methacrylate
Oral	<i>LD50</i>	7872 mg/kg (rat)
		crylic acid
Oral	LD50	1332 mg/kg (mouse)
Dermal	LD50	500 mg/kg (rabbit)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.

(Contd. on page 7)

Printing Date 11/17/2016 Revision Number 1 Revision Date 11/14/2016

Trade name: Rodmaster 6600

(Contd. of page 6)

- · Sensitization: Skin Contact Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

80-62-6 methyl methacrylate

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · **Recommendation:** Must be specially treated adhering to official regulations.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

11					•
14	Trans	nort i	ทรก	vun an	\boldsymbol{m}
		$\nu \nu \iota \iota \iota$			1411
			-7		

	T 7 % 7	A 7	7	
•	UN	-/Vu	mber	

· **DOT, IMDG, IATA** UN1133

· UN proper shipping name

DOT Adhesives
IMDG, IATA ADHESIVES

(Contd. on page 8)

USA

Printing Date 11/17/2016 Revision Number 1 Revision Date 11/14/2016

Trade name: Rodmaster 6600

(Contd. of page 7)

· Transport hazard class(es)

 $\cdot DOT$



ClassLabel3 Flammable liquids3

· IMDG, IATA



Class 3 Flammable liquids

· Label 3

· Packing group

· **DOT, IMDG, IATA**

• Environmental hazards: Not applicable.

· Special precautions for user Warning: Flammable liquids

Danger code (Kemler):
EMS Number:
Stowage Category

33
F-E,S-D
B

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

• Transport/Additional information: Limited Quantities are allowed. Refer to 49 CFR for conditions that

apply.

· UN "Model Regulation": UN 1133 ADHESIVES, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 9)

Printing Date 11/17/2016 Revision Number 1 Revision Date 11/14/2016

Trade name: Rodmaster 6600

(Contd. of page 8) · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. · (DSL) Canada Dosmestic Substance List All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements. · New Jersey Right-to-Know List: 80-62-6 methyl methacrylate 79-41-4 methacrylic acid · New Jersey Special Hazardous Substance List: 80-62-6 methyl methacrylate F3. R2 79-41-4 methacrylic acid CO, F2, R2 · Pennsylvania Right-to-Know List: 80-62-6 methyl methacrylate 79-41-4 methacrylic acid Pennsylvania Special Hazardous Substance List: 80-62-6 methyl methacrylate E· Cancerogenity categories · EPA (Environmental Protection Agency) 80-62-6 methyl methacrylate E, NL· TLV (Threshold Limit Value established by ACGIH) 80-62-6 methyl methacrylate A4· MAK (German Maximum Workplace Concentration) None of the ingredients is listed. · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed. · National regulations:

- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Chemical Concepts makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Chemical Concepts or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- · Creation Date: 11/14/2016
- · Date of preparation / last revision 11/17/2016 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

(Contd. on page 10)

Printing Date 11/17/2016 Revision Number 1 Revision Date 11/14/2016

Trade name: Rodmaster 6600

(Contd. of page 9)

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

USA



Revision Number 1

Revision Date 02/02/2017

1 Identification

- · Product identifier
- · Trade name: Rodmaster 6600
- · Relevant identified uses of the substance or mixture. Adhesive
- · Application of the substance / the mixture Adhesives
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Chemical Concepts, Inc.

410 Pike Road

Huntingdon Valley, PA. 19006 Phone Number: 800.220.1966

· Emergency telephone number:

InfoTrac: 1.800.535.5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

(Contd. on page 2)

Printing Date 02/02/2017 Revision Number 1 Revision Date 02/02/2017

Trade name: Rodmaster 6600

(Contd. of page 1)

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eve protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.


Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 2

· HMIS-ratings (scale 0 - 4)



2 Health = 2

PHYSICAL HAZARD 2 Physical Hazard = 2

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture
- · Hazardous components:

80-62-6 methyl methacrylate

50-100%

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

Printing Date 02/02/2017 Revision Number 1 Revision Date 02/02/2017

Trade name: Rodmaster 6600

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

Use fire fighting measures that suit the environment.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters

Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

· Protective equipment: Protective clothing and respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

• PAC-1:	
80-62-6 methyl methacrylate	17 ppm
· PAC-2:	
80-62-6 methyl methacrylate	120 ppm
· PAC-3:	
80-62-6 methyl methacrylate	570 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Open and handle receptacle with care.

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Printing Date 02/02/2017 Revision Number 1 Revision Date 02/02/2017

Trade name: Rodmaster 6600a

(Contd. of page 3)

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep container closed when not in use.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions:

Protect product from freezing.

Protect from heat and direct sunlight.

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm
REL Long-term value: 410 mg/m³, 100 ppm
TLV Short-term value: 410 mg/m³, 100 ppm
Long-term value: 205 mg/m³, 50 ppm
DSEN

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing Date 02/02/2017 Revision Number 1 Revision Date 02/02/2017

Trade name: Rodmaster 6600

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Face protection (face shield) Safety glasses with side shields.



Tightly sealed goggles

· Body protection:

Emergency showers and eye wash stations should be available. Protective work clothing

9 Physical and chemical properties

Information on basic physical and c	hemical properties
· General Information	
· Appearance: Form:	Paste
Form: Color:	Not determined.
· Odor:	Noi determined. Characteristic
· Odor: · Odor threshold:	Not determined.
· Ouor inresnoia:	Noi determined.
· pH-value:	5
· Change in condition	
Melting point:	Undetermined.
Boiling point:	101 °C (214 °F)
· Flash point:	10 °C (50 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	430 °C (806 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Flammable limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapor pressure at 20 °C (68 °F):	47 hPa (35 mm Hg)
· Specific gravity at 20 °C (68 °F):	0.96 g/cm³ (8.011 lbs/gal)
· Relative density	Not determined.
· Vapor density	3.5
· Evaporation rate	3
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	r): Not determined.

(Contd. on page 6)

Printing Date 02/02/2017 Revision Number 1 Revision Date 02/02/2017

Trade name: Rodmaster 6600

		(Contd. of page
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
Solids content:	Not available	
· Other information	<20 grams/liter [mixed]	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Avoid high temperatures. Avoid freezing.

Heat, flames, sparks.

Direct sunlight

· Incompatible materials:

Reacts with acids.

Reacts with oxidizing agents.

Reacts with alkalis (bases)

Copper and copper alloys.

· Hazardous decomposition products:

Carbon monoxide

Carbon dioxide

Nitrogen oxides

Hydrocarbons

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

80-62-6 methyl methacrylate

Oral LD50 7872 mg/kg (rat)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye:

May irritate the eye.

Vapors may be irritating to the eyes.

- · Sensitization: Skin Contact Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 7)

Printing Date 02/02/2017 Revision Number 1 Revision Date 02/02/2017

Trade name: Rodmaster 6600

(Contd. of page 6)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

80-62-6 methyl methacrylate

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must be specially treated adhering to official regulations.
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · **DOT, IMDG, IATA** UN1133
- · UN proper shipping name
- · **DOT** Adhesives
- · IMDG, IATA ADHESIVES mixture
- · Transport hazard class(es)
- \cdot **DOT**



Class 3 Flammable liquids

(Contd. on page 8)

Printing Date 02/02/2017 Revision Number 1 Revision Date 02/02/2017

Trade name: Rodmaster 6600

	(Contd. of pag
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Stowage Category	В
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Limited Quantities are allowed. Refer to 49 CFR for conditions that apply.
· UN "Model Regulation":	UN 1133 ADHESIVES MIXTURE, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- · Proposition 65
- Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

(Contd. on page 9)

Printing Date 02/02/2017 Revision Number 1 Revision Date 02/02/2017

Trade name: Rodmaster 6600

	(Contd. of pa
New Jersey Right-to-Know List:	
80-62-6 methyl methacrylate	
New Jersey Special Hazardous Substance List:	
80-62-6 methyl methacrylate	F3,
Pennsylvania Right-to-Know List:	
80-62-6 methyl methacrylate	
Pennsylvania Special Hazardous Substance List:	
80-62-6 methyl methacrylate	
Cancerogenity categories	
EPA (Environmental Protection Agency)	
80-62-6 methyl methacrylate	<i>E</i> , .
TLV (Threshold Limit Value established by ACGIH)	
80-62-6 methyl methacrylate	
oo oz o menyi menaeryiare	<u> </u>
MAK (German Maximum Workplace Concentration)	
MAK (German Maximum Workplace Concentration)	

- 1 tational regulations.
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Chemical Concepts makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Chemical Concepts or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- · Department issuing SDS: Environment protection department.
- · Creation Date: 02/02/2017
- · Date of preparation / last revision 02/02/2017 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

(Contd. on page 10)

Page 10/10

Safety Data Sheet acc. to OSHA HCS

Printing Date 02/02/2017 Revision Number 1 *Revision Date 02/02/2017*

Trade name: Rodmaster 6600

(Contd. of page 9)

Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3