SAFETY DATA SHEET



1. Identification

Product identifier DEVCON® Tile Adhesive Resin

Other means of identification

5057 SKU#

Recommended use Not available. Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name **ITW Performance Polymers**

30 Endicott Street **Address**

Danvers, MA 01923

United States

978-777-1100 **Telephone Customer Service**

Website www.itwperformancepolymers.com

E-mail Not available. **Contact person EHS** Department

Chemtrec 800-424-9300 **Emergency phone number**

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1

Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. **Hazard statement**

Precautionary statement

Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the Prevention

workplace. Wear eye protection/face protection. Wear protective gloves.

If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Response

Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take

off contaminated clothing and wash it before reuse.

Store away from incompatible materials. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Material name: DEVCON® Tile Adhesive Resin SDS US

Chemical name	Common name and synonyms	CAS number	%
Calcium Carbonate		1317-65-3	40 - 60
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)	EPOXY RESIN	25068-38-6	40 - 60
Quartz		14808-60-7	0.1 - 1
Other components below reportable	levels		10 - 20

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

the chemical Special protective equipment

and precautions for firefighters Fire fighting

Specific methods

equipment/instructions

General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

US OSHA Table 7.1 Limits for Air Contaminants (20 CER 1010 1000)

Occupational exposure limits

Components	Туре `	Value	Form
Calcium Carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Quartz (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR 1910.10	000)		
Components	Туре	Value	Form
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chemic	al Hazards		
Components	Туре	Value	Form

Biological limit values

1317-65-3)

Appropriate engineering

Calcium Carbonate (CAS

Quartz (CAS 14808-60-7)

controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety

5 ma/m3

10 mg/m3

0.05 mg/m3

Respirable.

Respirable dust.

Total

shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. **Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

TWA

TWA

General hygiene

considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Viscous. Liquid.

Physical state Liquid.

Form Viscous. Liquid.
Color Not available.

Odor Slight.

Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.

Initial boiling point and boiling

range

608 °F (320 °C) estimated

Flash point 265.0 °F (129.4 °C) estimated

Material name: DEVCON® Tile Adhesive Resin

Not available. **Evaporation rate** Not applicable. Flammability (solid, gas)

Upper/lower flammability or explosive limits

(%)

Flammability limit - upper

Flammability limit - lower

(%)

Not available.

Not available.

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Vapor pressure Not available. Not available. Vapor density

Relative density Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. Not available. **Viscosity**

Other information

Density 1.90 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible IIIB estimated

Oxidizing properties Not oxidizing. Specific gravity 1.9 estimated

VOC 0 g/I

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Knowledge about health hazard is incomplete.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Knowledge about health hazard is incomplete.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis, Rash.

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Material name: DEVCON® Tile Adhesive Resin

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityDue to partial or complete lack of data the classification is not possible.

Carcinogenicity Due to partial or complete lack of data the classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (CAS 14808-60-7) Cance

US. National Toxicology Program (NTP) Report on Carcinogens

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - Due to partial or complete lack of data the classification is not possible. **single exposure**

Specific target organ toxicity - [repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazardDue to partial or complete lack of data the classification is not possible.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SDS US

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (CAS 14808-60-7) Cancer lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Skin corrosion or irritation

categories

Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to Quartz, which is known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

Quartz (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Quartz (CAS 14808-60-7)

International Inventories

Country(s) or region

Country(s) or region	inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-28-2019

Material name: DEVCON® Tile Adhesive Resin

On inventory (yes/no)*

Revision date 04-29-2020

Version # 02

HMIS® ratings Health: 2

Flammability: 1 Physical hazard: 0

Health: 2 **NFPA** ratings

Flammability: 1 Instability: 0

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

> product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: DEVCON® Tile Adhesive Resin

SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Tile Adhesive Hardener

Other means of identification

SKU# 5326

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923

United States

Telephone Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious

eye damage.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat,

drink or smoke when using this product. Contaminated work clothing must not be allowed out of

the workplace. Wear eye protection/face protection. Wear protective gloves.

Response If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin: Wash with

plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it

before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: DEVCON® Tile Adhesive Hardener

SDS US

Supplemental information

92.71% of the mixture consists of component(s) of unknown acute oral toxicity. 92.71% of the mixture consists of component(s) of unknown acute dermal toxicity. 95.43% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 92.71% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Calcium Carbonate		1317-65-3	40 - 60
3,6,9-triazaundecamethylenediamin e	3,6,9-triazaundecamethyleendiamine	112-57-2	2.5 - 10
TRIETHYLENETETRAMINE	TETA	112-24-3	2.5 - 10
Titanium Dioxide	TITANIUM DIOXIDE	13463-67-7	1 - 2.5
Quartz		14808-60-7	0.1 - 1
Other components below reportable	levels		30 - 60

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire.

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special

treatment needed

General information

Ingestion

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting

Specific methods General fire hazards

Use water spray to cool unopened containers. equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: DEVCON® Tile Adhesive Hardener 5326 Version #: 02 Revision date: 04-29-2020 Issue date: 05-28-2019

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not get this material in contact with eyes. Do not taste or swallow. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air (Components	Туре	Value	Form
Calcium Carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Quartz (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910. ⁻	1000)		
Components	Туре	Value	Form
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction
US. ACGIH Threshold Limit Values			
	Туре	Value	Form
Components		Value 0.025 mg/m3	
US. ACGIH Threshold Limit Values Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7)	Туре		
Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7)	Type TWA TWA	0.025 mg/m3	
Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemi	Type TWA TWA	0.025 mg/m3	
Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemic Components Calcium Carbonate (CAS	Type TWA TWA ical Hazards	0.025 mg/m3 10 mg/m3	Respirable fraction
Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemic Components Calcium Carbonate (CAS	Type TWA TWA ical Hazards Type	0.025 mg/m3 10 mg/m3 Value	Respirable fraction. Form
Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS	Type TWA TWA ical Hazards Type	0.025 mg/m3 10 mg/m3 Value 5 mg/m3	Form Respirable.
Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemic Components Calcium Carbonate (CAS 1317-65-3) Quartz (CAS 14808-60-7)	Type TWA TWA ical Hazards Type TWA TWA	0.025 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3	Form Respirable. Total
Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemic Components Calcium Carbonate (CAS 1317-65-3) Quartz (CAS 14808-60-7) US. Workplace Environmental Expension	Type TWA TWA ical Hazards Type TWA TWA	0.025 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3	Form Respirable. Total
Components Quartz (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7) US. NIOSH: Pocket Guide to Chemic Components Calcium Carbonate (CAS 1317-65-3)	Type TWA TWA ical Hazards Type TWA TWA TWA cosure Level (WEEL) Guides	0.025 mg/m3 10 mg/m3 Value 5 mg/m3 10 mg/m3 0.05 mg/m3	Form Respirable. Total Respirable dust.

Material name: DEVCON® Tile Adhesive Hardener

SDS US

US. Workplace Environmental Exposure Level (WEEL) Guides

 Components
 Type
 Value
 Form

 TRIETHYLENETETRAMIN
 TWA
 6 mg/m3

1 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

E (CAS 112-24-3)

US WEEL Guides: Skin designation

3,6,9-triazaundecamethylenediamine (CAS 112-57-2)

TRIETHYLENETETRAMINE (CAS 112-24-3)

Can be absorbed through the skin.

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield. Face shield is

recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Paste.
Physical state Solid.
Form Paste.
Color White

Odor Ammoniacal.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling 392°

range

392 °F (200 °C) estimated

Flash point 200.1 °F (93.4 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure4.8 hPa estimatedVapor densityNot available.Relative densityNot available.

SDS US

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 1.83 g/cm3 estimated

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 1.83 estimated

VOC 0 g/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidAvoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause

redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Components Species Test Results

3,6,9-triazaundecamethylenediamine (CAS 112-57-2)

Acute Dermal

LD50 Rabbit 0.66 g/kg

TRIETHYLENETETRAMINE (CAS 112-24-3)

<u>Acute</u> Dermal

Liquid

LD50 Rat 1465 mg/kg

Oral *Liquid*

LD50 Rat 1716 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye Causes serious eye damage.

irritation

Respiratory or skin sensitization

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Carcinogenicity Due to partial or complete lack of data the classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (CAS 14808-60-7)

US. National Toxicology Program (NTP) Report on Carcinogens

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible. **Aspiration hazard**

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

3,6,9-triazaundecamethylenediamine 1.503

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the **Disposal instructions**

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Material name: DEVCON® Tile Adhesive Hardener

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State

of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (CAS 14808-60-7) Listed: October 1, 1988 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Quartz (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

SDS US

Country(s) or region Inventory name On inventory (yes/no)*

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 05-28-2019

 Revision date
 04-29-2020

Version # 02

HMIS® ratings Health: 3

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 1 Instability: 0

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material

designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information Composition/information on ingredients: Component information

Stability and reactivity: Conditions to avoid Toxicological information: Aspiration hazard Toxicological information: Carcinogenicity Toxicological information: Mutagenicity Toxicological information: Reproductivity

Toxicological information: Respiratory sensitization

Toxicological information: Skin contact

Toxicological information: Specific target organ toxicity - repeated exposure Toxicological information: Specific target organ toxicity - single exposure



Material name: DEVCON® Tile Adhesive Hardener sps us 5326 Version #: 02 Revision date: 04-29-2020 Issue date: 05-28-2019 8 / 8