

ITW Performance Polymers

SAFETY DATA SHEET

MA2090 Adhesive

Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MA2090 Adhesive
Product number IT195
UFI UFI: 1MC0-6003-W00J-4USD



1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier ITW Performance Polymers
 Bay 150
 Shannon Industrial Estate
 Co. Clare
 Ireland
 V14 DF82
 353(61)771500
 353(61)471285
 customerservice.shannon@itwpp.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335
Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H411 Toxic to aquatic life with long lasting effects.

MA2090 Adhesive

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p>
Contains	METHYL METHACRYLATE, DODECYL METHACRYLATE, METHACRYLIC ACID, 2-DIETHYLAMINOETHYL METHACRYLATE
Supplementary precautionary statements	<p>P240 Ground and bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use non-sparking tools.</p> <p>P243 Take action to prevent static discharges.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P391 Collect spillage.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

methyl methacrylate		30-60%
CAS number: 80-62-6	EC number: 201-297-1	REACH registration number: 01-2119452498-28-0000
Classification		
Flam. Liq. 2 - H225		
Skin Irrit. 2 - H315		
Skin Sens. 1 - H317		
STOT SE 3 - H335		

MA2090 Adhesive

dodecyl methacrylate		5-10%
CAS number: 142-90-5	EC number: 205-570-6	
Classification		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
STOT SE 3 - H335		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		
TRIMETHYLOLPROPANE, TRIMETHACRYLATE ESTERS		1-5%
CAS number: 3290-92-4		
Classification		
Aquatic Chronic 2 - H411		
methacrylic acid		1-5%
CAS number: 79-41-4	EC number: 201-204-4	REACH registration number: 01-2119463884-26-0000
Classification		
Acute Tox. 4 - H302		
Acute Tox. 4 - H312		
Skin Corr. 1A - H314		
Eye Dam. 1 - H318		
STOT SE 3 - H335		
2-DIETHYLAMINOETHYL METHACRYLATE		<1%
CAS number: 105-16-8		EC number: 203-275-7
Classification		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Get medical attention immediately. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

MA2090 Adhesive

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.

Unsuitable extinguishing media Do not use water, if avoidable.

5.2. Special hazards arising from the substance or mixture

Specific hazards Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid contact with skin and eyes.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame. Store away from incompatible materials (see Section 10).

7.3. Specific end use(s)

MA2090 Adhesive

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

methyl methacrylate

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

methacrylic acid

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³

Short-term exposure limit (15-minute): WEL 40 ppm 143 mg/m³

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Use approved respirator if air contamination is above an acceptable level. Ensure operatives are trained to minimise exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves made of the following material: Rubber or plastic. To protect hands from chemicals, gloves should comply with European Standard EN374. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. It is recommended that gloves are made of the following material: Butyl rubber. Laminate of polyethylene and ethylene vinyl alcohol (PE/EVOH). Neoprene. Frequent changes are recommended. The selected gloves should have a breakthrough time of at least 6 hours.

Other skin and body protection

Wear apron or protective clothing in case of contact.

Hygiene measures

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P2. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Paste.

MA2090 Adhesive

Colour	White/off-white.
Odour	Mild.
pH	pH (diluted solution): 7
Melting point	-47.7°C
Initial boiling point and range	100.5°C @
Flash point	10 degree C°C Tag closed cup.
Evaporation rate	3 (Butyl Acetate=1)
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 12.5 Lower flammable/explosive limit: 1.7
Vapour pressure	28 mm Hg @ °C
Vapour density	>1
Relative density	0.93 - 1.05 @ °C
Auto-ignition temperature	789 Degree F°C
9.2. Other information	
Other information	Not available.
Volatility	«184»
Volatile organic compound	This product contains a maximum VOC content of <50 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Strong oxidising agents. Amines. Alkalis.

10.2. Chemical stability

Stability Unstable.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat. Avoid contact with the following materials: Strong oxidising agents. Avoid contact with acids and alkalis.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 1,666,667.0

Acute toxicity - dermal

ATE dermal (mg/kg) 3,666,667.0

MA2090 Adhesive

Inhalation	Irritating to respiratory system. Vapours may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing.
Ingestion	May cause internal injury. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. Gastrointestinal symptoms, including upset stomach.
Skin contact	Irritating to skin. Prolonged and frequent contact may cause redness and irritation. May cause sensitisation by skin contact.
Eye contact	Irritating to eyes. Repeated exposure may cause chronic eye irritation.
Acute and chronic health hazards	The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.
Route of exposure	Inhalation Ingestion. Skin and/or eye contact
Target organs	Eyes Skin Respiratory system, lungs

Toxicological information on ingredients.

methyl methacrylate

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

STYRENE-BUTADIENE BLOCK COPOLYMER

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

methacrylic acid

Acute toxicity - oral

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

ATE dermal (mg/kg) 1,100.0

SECTION 12: Ecological information

Ecotoxicity Avoid releasing into the environment.

12.1. Toxicity

Toxicity Not considered toxic to fish.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential Not determined.

12.4. Mobility in soil

Mobility The product is miscible with water and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

MA2090 Adhesive

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General No other information known.

14.1. UN number

UN No. (ADR/RID) 1133

UN No. (IMDG) 1133

UN No. (ICAO) 1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ADHESIVES

Proper shipping name (IMDG) ADHESIVES

Proper shipping name (ICAO) ADHESIVES

Proper shipping name (ADN) ADHESIVES

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID label 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-D

Emergency Action Code •3YE

MA2090 Adhesive

Hazard Identification Number 33
(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 19/03/2021

Revision 10

Supersedes date 05/04/2018

Hazard statements in full

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.