



# SAFETY DATA SHEET

chemical-concepts.com

**800.220.1966**

410 Pike Road • Huntingdon Valley, PA 19006

Date Issued : 02/19/2020

SDS No : SP100

Date Revised : 06/05/2020

Revision No : 2

## Big Sticky LVOC Air Assist Canister

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Big Sticky LVOC Air Assist Canister

#### MANUFACTURER

ITW Polymers Sealants North America  
56 Air Station Industrial Park  
Rockland, MA 02370

**Customer Service:** 800-878-7876

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

International: (703) 527-3887

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Skin Irritation, Category 2  
Eye Irritation, Category 2A  
Reproductive Toxicity, Category 2  
Target Organ Toxicity (Single exposure), Category 3  
Target Organ Toxicity (Repeated exposure), Category 2  
Aspiration Hazard, Category 1

##### Environmental:

Acute Hazards to the Aquatic Environment, Category 2  
Chronic Hazards to the Aquatic Environment, Category 2

##### Physical:

Flammable Liquids, Category 1  
Liquefied Gases

#### GHS LABEL



Flame



Exclamation  
mark



Health  
hazard



Environment



Gas cylinder

**SIGNAL WORD:** DANGER

#### HAZARD STATEMENTS

H224: Extremely flammable liquid and vapour.  
H280: Contains gas under pressure; may explode if heated.  
H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.  
H361: Suspected of damaging fertility or the unborn child (state specific effect if known)(state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).  
H373: May cause damage to organs ( state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).  
H401: Toxic to aquatic life.  
H411: Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

Date Issued : 02/19/2020

SDS No : SP100

Date Revised : 06/05/2020

Revision No : 2

## Big Sticky LVOC Air Assist Canister

### PRECAUTIONARY STATEMENTS

#### General:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P410: Protect from sunlight.

#### Prevention:

[201]: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash ... thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P284: [In case of inadequate ventilation] wear respiratory protection.

#### Response:

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P302+P352: IF ON SKIN: Wash with plenty of water/...

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/ attention.

P312: Call a POISON CENTER/doctor/...if you feel unwell.

P314: Get medical advice/attention if you feel unwell.

P321: Specific treatment (see ... on this label).

P331: Do NOT induce vomiting.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER/doctor/...

P362: Take off contaminated clothing.

P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381: In case of leakage, eliminate all ignition sources.

#### Disposal:

P501: Dispose of contents/container to ...

### EMERGENCY OVERVIEW

**IMMEDIATE CONCERNS:** DANGER! Extremely flammable liquid and vapor. Vapor may cause flash fire and explosion. Contents under pressure. Harmful or fatal if swallowed. Intentional misuse or deliberate inhalation may cause death without warning. Vapor reduces oxygen available for breathing and is heavier than air. Vapors may cause dizziness, headache, nausea, drowsiness, unconsciousness and respiratory irritation. Can cause eye and skin irritation.

### POTENTIAL HEALTH EFFECTS

# SAFETY DATA SHEET

Date Issued : 02/19/2020

SDS No : SP100

Date Revised : 06/05/2020

Revision No : 2

## Big Sticky LVOC Air Assist Canister

**EYES:** Can cause severe eye irritation.

**SKIN:** Causes defatting and skin irritation. Can cause dermatitis.

**SKIN ABSORPTION:** May be absorbed through the skin in harmful amounts.

**INGESTION:** Can cause gastrointestinal irritation, nausea and vomiting. Aspiration of material into the lungs may cause chemical pneumonitis, which can be fatal. Harmful or fatal if swallowed.

**INHALATION:** High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

**ROUTES OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, and Skin Contact

**TARGET ORGAN STATEMENT:** Central Nervous System (CNS)

**IRRITANCY:** Eyes, nose, throat, respiratory tract, and skin irritation.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Methyl Acetate	45 - 50	79-20-9
n-Hexane	1 - 10	110-54-3
Low Boiling Point Hydrogen Treated Naphtha - Naphtha (petroleum), Hydrotreated Light	1 - 5	64742-49-0
n-Heptane	1 - 5	142-82-5
Nitrogen	< 5	7727-37-9
Cyclohexane	< 1	110-82-7

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

**INGESTION:** Do not induce vomiting, keep person warm, quiet and get medical attention immediately. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Aspiration of this material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Liquid and vapor can severely irritate the eyes depending on type of exposure (splash, vapor) and exposure time.

**SKIN:** Mild to moderate skin irritant.

**SKIN ABSORPTION:** May be absorbed through the skin and can contribute to overall exposure. Effects are similar to CNS depression.

**INGESTION:** May result in central nervous system (CNS) depression with symptoms such as headaches, nausea, vomiting, diarrhea, dizziness, incoordination and unconsciousness. Aspiration of material into lungs may cause chemical pneumonitis which can be fatal.

**INHALATION:** High vapor concentrations may cause CNS depression with symptoms including light headedness, giddiness, nausea, drowsiness, headache, nose, throat and respiratory tract irritation, reduced appetite, confusion, and unconsciousness.

**ACUTE EFFECTS:** High vapor concentrations may cause central nervous system (CNS) depression with symptoms including light headedness, giddiness, nausea, drowsiness, headache, nose, throat and respiratory tract irritation, reduced appetite, confusion

# SAFETY DATA SHEET

Date Issued : 02/19/2020

SDS No : SP100

Date Revised : 06/05/2020

Revision No : 2

## Big Sticky LVOC Air Assist Canister

and unconsciousness.

**CHRONIC EFFECTS:** Damage to the nervous system of the extremities, peripheral neuropathy, with symptoms including numbness, tingling and weakness in the toes and fingers, sensory impairment to touch, pain, vibration and temperature, muscular weakness, blurred vision, coldness of extremities, loss of body weight and reflexes, and even paralysis. Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

### 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Class IB

**GENERAL HAZARD:** Flammable liquid and vapor. Contents under pressure.

**EXTINGUISHING MEDIA:** Foam, dry chemical, carbon dioxide, water spray or fog.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon Monoxide, Carbon Dioxide, Aldehydes

**EXPLOSION HAZARDS:** Avoid fire, sparks, static electricity and hot surfaces. Liquid readily evaporates at room/ambient temperature. Vapors are invisible, flammable, heavier than air, and may accumulate in low areas and spread long distances. Distant ignition and flashback are possible.

**FIRE FIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

**SENSITIVE TO STATIC DISCHARGE:** Likely to catch fire from near-by spark. Static charge may accumulate by flow or agitation. Grounding and bonding of containers is required.

**SENSITIVITY TO IMPACT:** None known.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Monoxide and Carbon Dioxide may form when heated to decomposition.

### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

**LARGE SPILL:** Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof mechanical means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

**HANDLING:** Use adequate ventilation and appropriate respiratory protection to avoid breathing vapors when cover is removed.

# SAFETY DATA SHEET

**Date Issued** : 02/19/2020**SDS No** : SP100**Date Revised** : 06/05/2020**Revision No** : 2

## Big Sticky LVOC Air Assist Canister

---

Ground and bond all equipment when handling flammable solvent-borne material.

**STORAGE:** Keep container closed when not in use. Store in a dry, well ventilated area, out of the sun and away from ignition sources. Do not remove or deface label. Prevent water or moist air from entering container.

**STORAGE TEMPERATURE:** 15.5°C (60°F) Minimum to 35°C (95°F) Maximum

**SHELF LIFE:** 1 year from manufacture date

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

# SAFETY DATA SHEET

Date Issued : 02/19/2020

SDS No : SP100

Date Revised : 06/05/2020

Revision No : 2

## Big Sticky LVOC Air Assist Canister

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	EXPOSURE LIMITS			
	Type		ppm	mg/m <sup>3</sup>
Methyl Acetate	OSHA PEL	TWA	200 ppm	610
		STEL	NL <sup>[1]</sup>	NL <sup>[1]</sup>
	ACGIH TLV	TWA	200 ppm	606
		STEL	250 ppm	757
n-Hexane	OSHA PEL	TWA	500 ppm <sup>[2]</sup>	1800 mg/m <sup>3</sup> <sup>[2]</sup>
		STEL	NL <sup>[1]</sup>	NL <sup>[1]</sup>
	ACGIH TLV	TWA	50 ppm	176 mg/m <sup>3</sup>
		STEL	NL <sup>[1]</sup>	NL <sup>[1]</sup>
Low Boiling Point Hydrogen Treated Naphtha - Naphtha (petroleum), Hydrotreated Light	OSHA PEL	TWA	500 ppm	NL
		STEL	NL <sup>[1]</sup>	NL <sup>[1]</sup>
	ACGIH TLV	TWA	200 ppm	NL
		STEL	NL <sup>[1]</sup>	NL <sup>[1]</sup>
n-Heptane	OSHA PEL	TWA	500 ppm <sup>[2]</sup>	2000 mg/m <sup>3</sup> <sup>[2]</sup>
		STEL	NL <sup>[1]</sup>	NL <sup>[1]</sup>
	ACGIH TLV	TWA	400 ppm	1640 mg/m <sup>3</sup>
		STEL	500 ppm	2050 mg/m <sup>3</sup>
Nitrogen	OSHA PEL	TWA	NL <sup>[1]</sup>	NL <sup>[1]</sup>
		STEL	NL <sup>[1]</sup>	NL <sup>[1]</sup>
	ACGIH TLV	TWA	NL <sup>[1]</sup>	NL <sup>[1]</sup>
		STEL	NL <sup>[1]</sup>	NL <sup>[1]</sup>
Cyclohexane	OSHA PEL	TWA	300 ppm <sup>[2]</sup>	1050 mg/m <sup>3</sup> <sup>[2]</sup>
		STEL	NL <sup>[1]</sup>	NL <sup>[1]</sup>
	ACGIH TLV	TWA	100 ppm	334 mg/m <sup>3</sup>
		STEL	NL <sup>[1]</sup>	NL <sup>[1]</sup>

**Footnotes:**

1. NL = Not Listed
2. OSHA limits per 29 CFR 1910.1000 Table Z-1 & Z-2

**ENGINEERING CONTROLS:** Provide sufficient explosion proof mechanical (general and/or local exhaust) ventilation to maintain exposure below the occupational exposure limit and exposure concentration.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Wear safety glasses with side shields (or goggles) and a face shield.

# SAFETY DATA SHEET

Date Issued : 02/19/2020

SDS No : SP100

Date Revised : 06/05/2020

Revision No : 2

## Big Sticky LVOC Air Assist Canister

**SKIN:** Wear chemical protective clothing & boots to prevent repeated or prolonged skin contact. Wear impervious gloves, if needed, to prevent repeated or prolonged skin contact.

**RESPIRATORY:** NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

**PROTECTIVE CLOTHING:** Wear chemical resistant gloves, such as nitrile rubber.

**WORK HYGIENIC PRACTICES:** Use good hygiene practices when handling this material. Wash hands thoroughly after use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Aerosol

**ODOR:** Solvent-like

**COLOR:** Clear

**pH:** Not Determined

**PERCENT VOLATILE:** 65.0

**Notes:** by weight

**FLASH POINT AND METHOD:** -30.5°C (-22.9°F) TAG CC

**FLAMMABLE LIMITS:** 3 to 16

**AUTOIGNITION TEMPERATURE:** Not Available

**VAPOR PRESSURE:** Not Determined

**VAPOR DENSITY:** Not Determined

**BOILING POINT:** 55.8°C (132.4°F) to 58.2°C (136.8°F)

**FREEZING POINT:** Not Determined

**MELTING POINT:** Not Determined

**POUR POINT:** Not Determined

**SOLUBILITY IN WATER:** Slight

**PARTITION COEFFICIENT: N-OCTANOL/WATER:** Not Determined

**EVAPORATION RATE:** > 1.0 (n-Butyl Acetate=1)

**DENSITY:** 7.445 lbs/gal

**PARTICLE SIZE:** Not Determined

**SPECIFIC GRAVITY:** 0.893

**VISCOSITY:** Not Determined

**MOLECULAR WEIGHT:** Not Determined

**(VOC):** 273.1 gr/L EPA Method 24 VOC

**Notes:** Photochemically Reactive Only VOC: 145.1 gr/L

VOC (wt %) = 16.3%

**OXIDIZING PROPERTIES:** Not Determined

### 10. STABILITY AND REACTIVITY

**REACTIVITY:** Yes

# SAFETY DATA SHEET

Date Issued : 02/19/2020

SDS No : SP100

Date Revised : 06/05/2020

Revision No : 2

## Big Sticky LVOC Air Assist Canister

**HAZARDOUS POLYMERIZATION:** Product will not undergo polymerization.

**STABILITY:** Stable.

**CONDITIONS TO AVOID:** Avoid fire, sparks, static electricity and hot surfaces.

**POSSIBILITY OF HAZARDOUS REACTIONS:** None Expected.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide and carbon dioxide may form when heated to decomposition.

**INCOMPATIBLE MATERIALS:** Strong oxidizing agents, strong acids and strong bases.

### 11. TOXICOLOGICAL INFORMATION

#### ACUTE TOXICITY

Chemical Name	ORAL LD <sub>50</sub>	DERMAL LD <sub>50</sub>	INHALATION LC <sub>50</sub>
Methyl Acetate	> 5000 mg/kg	> 5000 mg/kg	> 16000 ppm (4-hr dose)
n-Hexane	25000 mg/kg	No data	48000 ppm (4-hr dose)
n-Heptane	> 15000 mg/kg	> 2001 mg/kg	103000 mg/cub m (4-hr dose)
Nitrogen	No data	No data	No data
Cyclohexane	29820 mg/kg	No data	No data

**SERIOUS EYE DAMAGE/IRRITATION:** Eyes, nose, throat, respiratory tract irritation.

### 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** This product contains components that will normally float on water. These components may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

**ECOTOXICOLOGICAL INFORMATION:** Contains components that are potentially toxic to freshwater and saltwater ecosystems.

**BIOACCUMULATION/ACCUMULATION:** Contains components with the potential to bio-accumulate.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of in accordance with all local, state and federal regulations.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Chemical Under Pressure, Flammable, n.o.s.

**PRIMARY HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN3501

**PACKING GROUP:** NA

**NAERG:** 115

**MARINE POLLUTANT #1:** None

**OTHER SHIPPING INFORMATION:** contains (Methyl Acetate, n-Heptane)

#### AIR (ICAO/IATA)

**SHIPPING NAME:** Chemical Under Pressure, Flammable, n.o.s.

**TECHNICAL NAME:** contains (Methyl Acetate, n-Heptane)

**UN/NA NUMBER:** UN3501



# SAFETY DATA SHEET

Date Issued : 02/19/2020

SDS No : SP100

Date Revised : 06/05/2020

Revision No : 2

## Big Sticky LVOC Air Assist Canister

PRIMARY HAZARD CLASS/DIVISION: 2.1

ERG: 115

VESSEL (IMO/IMDG)

SHIPPING NAME: Chemical Under Pressure, Flammable, n.o.s.

TECHNICAL NAME: contains (Methyl Acetate, n-Heptane)

UN/NA NUMBER: UN3501

PRIMARY HAZARD CLASS/DIVISION: 2.1

### 15. REGULATORY INFORMATION

#### UNITED STATES

##### DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Flammable  
Gas

#### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

##### EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
n-Hexane	1 - 10	110-54-3

#### CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
n-Hexane	1 - 10	5,000 lbs.
Cyclohexane	< 1	1,000 lbs.

#### TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS	TSCA SECTION
Methyl Acetate	79-20-9	
n-Hexane	110-54-3	
Low Boiling Point Hydrogen Treated Naphtha - Naphtha (petroleum), Hydrotreated Light	64742-49-0	
n-Heptane	142-82-5	12b,
Nitrogen	7727-37-9	
Cyclohexane	110-82-7	

#### CLEAN AIR ACT

Chemical Name	Wt.%	CAS
n-Hexane	1 - 10	110-54-3

# SAFETY DATA SHEET

Date Issued : 02/19/2020

SDS No : SP100

Date Revised : 06/05/2020

Revision No : 2

## Big Sticky LVOC Air Assist Canister

### STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
n-Hexane	New Jersey Right to Know List Pennsylvania Right to Know List Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical
Low Boiling Point Hydrogen Treated Naphtha - Naphtha (petroleum), Hydrotreated Light	New Jersey Right to Know List
n-Heptane	New Jersey Right to Know List Pennsylvania Right to Know List
Nitrogen	New Jersey Right to Know List
Cyclohexane	New Jersey Right to Know List Pennsylvania Right to Know List Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical

### CANADA

#### WHMIS HAZARD SYMBOL AND CLASSIFICATION



Flammable  
Gas



Toxic

### 16. OTHER INFORMATION

Date Revised: 06/05/2020


INFORMATION CONTACT: (800) 878-7876

REVISION SUMMARY: This SDS replaces the 02/26/2020 SDS. Revised: **Section 1**: SDS No.

#### HMIS RATING

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL HAZARD		0
PERSONAL PROTECTION		B

#### NFPA CODES



**GENERAL STATEMENTS:** Keep out of reach of children

For professional or industrial use only

**MANUFACTURER DISCLAIMER:** This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or



# SAFETY DATA SHEET

chemical-concepts.com

**800.220.1966**

410 Pike Road • Huntingdon Valley, PA 19006

**Date Issued** : 02/19/2020

**SDS No** : SP100

**Date Revised** : 06/05/2020

**Revision No** : 2

## Big Sticky LVOC Air Assist Canister

---

completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.