Revision date: 10/10/2019 Revision: 3





SAFETY DATA SHEET Tensorbond C302 Non Flam Sprayable Liquid Contact Adhesive

1. Identification

Product identifier

Product name Tensorbond C302 Non Flam Sprayable Liquid Contact Adhesive

Product number USA

Recommended use of the chemical and restrictions on use

Application Solvent-based Adhesive

Details of the supplier of the safety data sheet

Supplier Quin Global USA

5710 F St.

Omaha, NE 68117 (402) 731 3636 (402) 731 1473

marketing.us@quin-global.com

Emergency telephone number

Emergency telephone Chemtrec: 1 800 424 9300

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 -

H351 STOT SE 3 - H335, H336 STOT RE 2 - H373

Environmental hazards Not Classified

Human health The liquid may be irritating to eyes, respiratory system and skin. Symptoms following

overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

Label elements

Hazard symbols







Signal word

Danger

Revision date: 10/10/2019 Revision: 3 Supersedes date: 10/12/2016

Tensorbond C302 Non Flam Sprayable Liquid Contact Adhesive

Hazard statements H301 Toxic if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements P260 Do not breathe vapor/ spray.

P301+P310 If swallowed: Immediately call a poison center/ doctor.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. P312 Call a poison center/ doctor if you feel unwell.

Contains Methylene Chloride

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Methylene Chloride 60-100%

CAS number: 75-09-2

Classification

Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 - H351

STOT SE 3 - H335, H336 STOT RE 2 - H373

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Get medical attention if any

discomfort continues.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen. Get medical attention.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Move

affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Get medical attention.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Revision date: 10/10/2019 Revision: 3 Supersedes date: 10/12/2016

Tensorbond C302 Non Flam Sprayable Liquid Contact Adhesive

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Get medical attention promptly if symptoms occur after washing.

Most important symptoms and effects, both acute and delayed

Inhalation May cause coughing and difficulties in breathing. May cause eye and respiratory system

irritation. Overexposure may depress the central nervous system, causing dizziness and

intoxication.

Ingestion Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may

cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may

cause chemical pneumonitis.

Skin contact May be absorbed through the skin. Product has a defatting effect on skin. The product is

irritating to eyes and skin. A single exposure may cause the following adverse effects:

Dryness and/or cracking.

Eye contact Causes serious eye irritation. Burns can occur. A single exposure may cause the following

adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged

contact causes serious eye and tissue damage.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with Carbon Dioxide, Dry Chemical and Foam.

Advice for firefighters

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8.

Environmental precautions

Environmental precautions Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-

combustible material.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff

entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place

into containers. Wash thoroughly after dealing with a spillage.

7. Handling and storage

Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation

of vapors. Use approved respirator if air contamination is above an acceptable level.

Container must be kept tightly closed when not in use.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage precautions Keep container tightly closed. Keep only in the original container.

Tensorbond C302 Non Flam Sprayable Liquid Contact Adhesive

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

Methylene Chloride

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm

А3

Short-term exposure limit (15-minute): OSHA 125 ppm Long-term exposure limit (8-hour TWA): OSHA 25 ppm

ACGIH = American Conference of Governmental Industrial Hygienists. A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans. OSHA = Occupational Safety and Health Administration.

Exposure controls

Protective equipment





Appropriate engineering

controls

This product must not be handled in a confined space without adequate ventilation. Provide adequate general and local exhaust ventilation.

Eye/face protection Wear chemical splash goggles.

Hand protection Use protective gloves.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapor contact.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating,

smoking and using the toilet. Wash promptly with soap and water if skin becomes

contaminated. Promptly remove any clothing that becomes contaminated. When using do not

eat, drink or smoke.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended

occupational exposure limit. If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level

exposures, compressed airline breathing apparatus should be used.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Liquid.

Color Clear. Blue.

Odor Organic solvents.

Initial boiling point and range Not determined.

Flash point None.

Upper/lower flammability or explosive limits

None.

Vapor pressure Not determined.

Vapor density Not determined.

Relative density 1.22

Revision date: 10/10/2019 Revision: 3 Supersedes date: 10/12/2016

Tensorbond C302 Non Flam Sprayable Liquid Contact Adhesive

Solubility(ies) Negligibly soluble in water

10. Stability and reactivity

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous

reactions

Will not polymerize.

Conditions to avoid Avoid contact with the following materials: Oxidizing agents. Reducing agents.

Materials to avoid None known.

Hazardous decomposition

products

gases (NOx).

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 131.96093956

Acute toxicity - dermal

ATE dermal (mg/kg) 1,451.57033518

Toxicological information on ingredients.

Methylene Chloride

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). Nitrous

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg) **Species**

Rat

2,000.0

ATE oral (mg/kg) 100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.0

mg/kg)

Species Rat

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ vapours mg/l)

52.0

Species Rat

ATE inhalation (vapours

mg/l)

11.0

Carcinogenicity

Carcinogenicity Cancinogenicity - rat - inhalation Limited evidence of carcinogenicity in animal

studies

Tensorbond C302 Non Flam Sprayable Liquid Contact Adhesive

Target organ for

Tumerigenic: Carcinogenic by RTECS criteria. Endochrine: Tumors

carcinogenicity

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

Specific target organ toxicity - single exposure

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Inhalation - May cause damage to organs through prolonged or repeated exposure

-Central nervous system Oral - May cause damage to organs through prolonged or

repeated exposure -Liver, blood.

General information RTECS: PA8050000

12. Ecological information

13. Disposal considerations

Waste treatment methods

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

UN Number

UN No. (DOT) UN 1593

UN proper shipping name

Proper shipping name (DOT) UN 1593 Dichloromethane, 6.1

Transport hazard class(es)

TDG class 6.1

IMDG Class 6.1

ICAO class/division 6.1

Transport labels



Packing group

TDG Packing Group

Packing group (International) Not applicable.

Ш

IMDG packing group

ICAO packing group

DOT packing group III

15. Regulatory information

Revision date: 10/10/2019 Revision: 3 Supersedes date: 10/12/2016

Tensorbond C302 Non Flam Sprayable Liquid Contact Adhesive

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009

No. 716).

Guidance CHIP for everyone HSG228.

Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

Approved Classification and Labelling Guide (Sixth edition) L131.

US Federal Regulations

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

Present.

SARA 313 Emission Reporting

Present.

SARA (311/312) Hazard Categories

Present.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Present.

Inventories

US - TSCA

Present.

16. Other information

Revision date 10/10/2019

Revision 3

Supersedes date 10/12/2016

SDS No. 21304

Hazard statements in full H301 Toxic if swallowed.

H312 Harmful in contact with skin. H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs (Oral (Category 2), Inhalation (Category 2), Blood,

Central nervous system, Liver) through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure.

ACA HMIS Health rating. Moderate hazard. (2)

ACA HMIS Flammability

rating.

Will not burn. (0)

ACA HMIS Physical hazard

rating.

Normally stable. (0)

ACA HMIS Personal

protection rating.

В

DIRECTIONS FOR USE

Tensorbond C302 Non Flam Sprayable Liquid Contact Adhesive

PRODUCT LOGO



The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the manufacturer of this product is fit for a particular purpose and suitable for users' method of use or application. It is essential that the user evaluate this product, not the manufacturer, to determine whether it is fit for a particular purpose and suitable for users' method of use or application