



Technical Data Sheet

AW307 Red

AW307 Red is a high-quality contact cement for decorative laminate to plywood and particleboard. Its outstanding features include high tack and long open time, low VOC's, and excellent green strength.

TYPICAL PROPERTIES

Viscosity, cPs:	140
Solids, wt%:	36.5
Volatile, wt%:	63.5
Specific Gravity:	0.90
Wt. per Gal., lb/gal:	7.46
VOC, lb/gal:	1.06
VOC, g/l:	126.6
VOC, wt%:	14.19
HAP, wt%:	14.19
VHAP, wt%:	14.19
HAP, lb/lb solids:	0.38
Shipping Class:	UN1133

Additional information regarding other specific applications is available upon request. Consult SDS for health and safety information. For further information or questions, please contact our technical representatives.



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006

FOR INDUSTRIAL USE ONLY

IMPORTANT: The information contained herein is correct to the best of our knowledge and tests. The recommendations and suggestions contained herein are made without guarantee or representation as to results. We recommend that adequate tests be made by the purchaser to determine if a product is suitable for the intended purpose and use. Our only obligations shall be to replace or pay for any material proved defective by our laboratory within our published shelf life period. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind and the user accepts the product "as is" and without any other warranties expressed or implied. The suitability of these products to an intended use shall be solely up to the user.