

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® 2051 RESIN

Unique Formula Identifier (UFI) : C2R5-V02E-T00Q-RHF4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Adhesives

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium

Telephone : +41 61 299 20 41
Telefax : +40 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300
NVIC: 030 274 88 88. Intended solely for First-Aid professionals following acute poisonings.



SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Chronic aquatic toxicity, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

methyl methacrylate

methacrylic acid

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
methyl methacrylate	80-62-6 201-297-1 607-035-00-6 01-2119452498-28	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 50 - < 70
methacrylic acid	79-41-4 201-204-4 607-088-00-5 01-2119463884-26	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 3; H311 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) specific concentration limit STOT SE 3; H335 >= 1 %	>= 5 - < 10
2,6-Di-tert-butyl-p-cresol	128-37-0 204-881-4 01-2119555270-46	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2,5
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	52628-03-2 258-053-2 01-2119980575-25	Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317	>= 1 - < 3
alpha,alpha-dimethylbenzyl hydroperoxide	80-15-9 201-254-7	Org. Perox. E; H242 Acute Tox. 4; H302	>= 0,25 - < 1

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

	<p>617-002-00-8 01-2119475796-19</p>	<p>Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 STOT RE 2; H373 Aquatic Chronic 2; H411</p> <hr/> <p>specific concentration limit Skin Corr. 1B; H314 >= 10 % Skin Irrit. 2; H315 3 - < 10 % Eye Dam. 1; H318 3 - < 10 % Eye Irrit. 2; H319 1 - < 3 % STOT SE 3; H335 >= 1 %</p>
--	--	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Exercise caution when using a high volume water jet as it may scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Sulphur oxides
Hydrogen chloride

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.02.2021	400000011295	Date of first issue: 17.02.2021

Print Date 04.08.2022

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Refer to protective measures listed in sections 7 and 8.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU
Further information	Indicative			
		STEL	100 ppm	2009/161/EU
Further information	Indicative			
		TLV-8hr	205 mg/m ³	NL WG
		TLV-15 min	410 mg/m ³	NL WG

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,6-di-tert-butyl-p-cresol	Workers	Inhalation	Long-term systemic effects	3,5 mg/m ³
	Workers	Dermal	Long-term systemic effects	0,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,86 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESINVersion
1.0Revision Date:
17.02.2021SDS Number:
400000011295Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

	Consumers	Dermal	Long-term systemic effects	0,25 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,25 mg/kg bw/day
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	Workers	Inhalation	Long-term systemic effects	7,04 mg/m ³
	Workers	Dermal	Long-term systemic effects	1 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,74 mg/m ³
	Consumers	Dermal	Long-term systemic effects	0,5 mg/kg bw/day
methacrylic acid	Workers	Inhalation	Long-term systemic effects	29,6 mg/m ³
	Workers	Inhalation	Long-term local effects	88 mg/m ³
	Workers	Dermal	Long-term systemic effects	4,25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	6,3 mg/m ³
	Consumers	Inhalation	Long-term local effects	6,55 mg/m ³
	Consumers	Dermal	Long-term systemic effects	2,55 mg/kg bw/day
Silica, amorphous, fumed, cryst.-free	Workers	Inhalation	Long-term systemic effects	4 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,6-di-tert-butyl-p-cresol	Fresh water	0,199 µg/l
Remarks:	Assessment Factors	
	Marine water	0,02 µg/l
	Assessment Factors	
	Sewage treatment plant	0,17 mg/l
	Assessment Factors	
	Fresh water sediment	0,0996 mg/kg dry weight (d.w.)
	Equilibrium method	
	Marine sediment	0,00996 mg/kg dry weight (d.w.)
	Equilibrium method	
	Soil	0,04769 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version
1.0

Revision Date:
17.02.2021

SDS Number:
400000011295

Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

		dry weight (d.w.)
	Equilibrium method	
	Oral	8,33 mg/kg
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	Fresh water	0,068 mg/l
	Assessment Factors	
	Marine water	0,007 mg/l
	Assessment Factors	
	Sewage treatment plant	0,546 mg/l
	Assessment Factors	
	Fresh water sediment	0,481 mg/kg dry weight (d.w.)
	Equilibrium method	
	Marine sediment	0,048 mg/kg dry weight (d.w.)
	Equilibrium method	
	Soil	0,056 mg/kg dry weight (d.w.)
	Equilibrium method	
methacrylic acid	Fresh water	0,82 mg/l
	Assessment Factors	
	Marine water	0,82 mg/l
	Assessment Factors	
	Freshwater - intermittent	0,82 mg/l
	Assessment Factors	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Soil	1,2 mg/kg
	Equilibrium method	

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Remarks

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines

Filter type : Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : off-white

Odour : like methacrylic acid

Odour Threshold : No data is available on the product itself.

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flash point : 10 °C
Method: estimated

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Burning rate : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

Density : 1,02 - 1,05 g/cm³

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : No data is available on the product itself.

Viscosity
Viscosity, dynamic : 40 - 70 Pas

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

Hazardous decomposition products : carbon dioxide
carbon monoxide

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.02.2021	400000011295	Date of first issue: 17.02.2021

Print Date 04.08.2022

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 2 000 mg/kg
Method: Calculation method

Acute inhalation toxicity - Product : Acute toxicity estimate : > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity - Product : Acute toxicity estimate : > 2 000 mg/kg
Method: Calculation method

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Product:

Method: OECD Test Guideline 431
Result: Causes burns.
GLP: yes

Serious eye damage/eye irritation

Components:

methacrylic acid:
Species: Rabbit
Assessment: Risk of serious damage to eyes.
Method: Draize Test
Result: Irreversible effects on the eye
GLP: no

2,6-di-tert-butyl-p-cresol:
Species: Rabbit
Assessment: No eye irritation
Method: OECD Test Guideline 405
Result: No eye irritation

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate:
Result: Corrosive

alpha,alpha-dimethylbenzyl hydroperoxide:
Assessment: Risk of serious damage to eyes.
Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Components:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.02.2021	400000011295	Date of first issue: 17.02.2021

Print Date 04.08.2022

methyl methacrylate:
Exposure routes: Skin
Species: Mouse
Assessment: May cause sensitisation by skin contact.
Method: OECD Test Guideline 429
Result: May cause sensitisation by skin contact.

methacrylic acid:
Test Type: Buehler Test
Exposure routes: Skin
Species: Guinea pig
Assessment: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 406
Result: Did not cause sensitisation on laboratory animals.

2,6-di-tert-butyl-p-cresol:
Exposure routes: Skin
Species: Humans
Result: Does not cause skin sensitisation.

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate:
Test Type: Local lymph node assay (LLNA)
Species: Mouse
Method: OECD Test Guideline 429
Result: The product is a skin sensitiser, sub-category 1B.
GLP: yes

Assessment: No data available

Germ cell mutagenicity

Components:

methyl methacrylate:
Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)
Test system: Salmonella typhimurium
Method: OECD Test Guideline 471
Result: negative

methacrylic acid:
Genotoxicity in vitro : Test Type: reverse mutation assay
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

2,6-di-tert-butyl-p-cresol:
Genotoxicity in vitro : Test Type: reverse mutation assay
Metabolic activation: with and without metabolic activation
Result: negative

: Test Type: Chromosome aberration test in vitro

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.02.2021	400000011295	Date of first issue: 17.02.2021

Print Date 04.08.2022

Metabolic activation: with and without metabolic activation
Result: negative

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella tryphimurium and E. coli
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

: Test Type: In vitro mammalian cell gene mutation test
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes

: Test Type: Chromosome aberration test in vitro
Test system: Human lymphocytes
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative
GLP: yes

Components:

methacrylic acid:

Genotoxicity in vivo : Test Type: in vivo assay
Test species: Rat (male)
Cell type: Somatic
Application Route: Inhalation
Exposure time: 2 h
Dose: 0.4, 1.6, 2.8 and 4 mg/L
Method: OECD Test Guideline 475
Result: Not classified due to inconclusive data.
GLP: no

Test Type: dominant lethal test
Test species: Mouse (male)
Application Route: Inhalation
Exposure time: 6 h
Dose: 0.405, 4.05 and 36.45 mg/L
Method: OECD Test Guideline 478
Result: negative
GLP: no

2,6-di-tert-butyl-p-cresol:

Genotoxicity in vivo : Application Route: Intraperitoneal injection

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.02.2021	400000011295	Date of first issue: 17.02.2021

Print Date 04.08.2022

Dose: 75 mg/kg
Result: negative

Application Route: Oral
Exposure time: 9 Months
Dose: ca 750 mg/kg
Result: negative

Germ cell mutagenicity-
Assessment : No data available

Carcinogenicity

Components:

methyl methacrylate:
Species: Rat, male and female
Application Route: Oral
Exposure time: 2 Years
Dose: 6, 60, 2000 ppm
Frequency of Treatment: once daily
No observed adverse effect level: 90,3 mg/kg bw/day
Result: negative

methacrylic acid:
Species: Rat, male and female
Application Route: inhalation (vapour)
Exposure time: 102 weeks
Frequency of Treatment: 5 days/week
No observed adverse effect level: $\geq 2,05$ mg/kg body weight
Method: OECD Test Guideline 451

Species: Mouse, male and female
Application Route: inhalation (vapour)
Exposure time: 102 weeks
Dose: ca. 2.05 and 4.1 mg/L
Frequency of Treatment: 5 days/week
Lowest observed adverse effect level: ca. 2,05 mg/l
Method: OECD Test Guideline 451

2,6-di-tert-butyl-p-cresol:
Species: Rat, male and female
Application Route: Oral
Result: negative

Carcinogenicity -
Assessment : No data available

Reproductive toxicity

Components:

methacrylic acid:
Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.02.2021	400000011295	Date of first issue: 17.02.2021

Print Date 04.08.2022

Application Route: Oral
Dose: 0, 50, 150, 450 mg/kg/day
General Toxicity - Parent: No observed adverse effect level:
50 mg/kg body weight
Fertility: No observed adverse effect level F1: 400 mg/kg body
weight
Symptoms: Reduced body weight
Method: OECD Test Guideline 416
GLP: yes

2,6-di-tert-butyl-p-cresol:

Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 25/100/500 mg/kg bw/day
General Toxicity - Parent: No observed adverse effect level:
100 mg/kg body weight
General Toxicity F1: No observed adverse effect level: 25
mg/kg body weight
Result: negative

Components:

methyl methacrylate:
Effects on foetal
development

: Species: Rat
Application Route: Inhalation
Dose: 99, 304, 1178 ppm
Teratogenicity: No observed adverse effect concentration F1:
8 300 mg/m³
Embryo-foetal toxicity: No observed adverse effect
concentration F1: 8 300 mg/m³
Method: OECD Test Guideline 414
Result: No teratogenic effects

methacrylic acid:

Test Type: Pre-natal
Species: Rat, female
Application Route: Inhalation
Dose: 0, 50, 100, 200 or 300 ppm
Duration of Single Treatment: 14 d
Frequency of Treatment: 7 days/week
General Toxicity Maternal: No observed adverse effect level:
200 ppm
Developmental Toxicity: No observed adverse effect level: >=
300 ppm
Embryo-foetal toxicity: No observed adverse effect
concentration F1: 300 ppm
Method: OECD Test Guideline 414
Result: No effects on fertility and early embryonic
development were detected.

Test Type: Pre-natal
Species: Rabbit, male and female
Application Route: Oral
Dose: 50, 150, 450 milligram per kilogram

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.02.2021	400000011295	Date of first issue: 17.02.2021

Print Date 04.08.2022

Duration of Single Treatment: 23 d
Frequency of Treatment: 7 days/week
General Toxicity Maternal: No observed adverse effect level:
50 mg/kg body weight
Developmental Toxicity: No observed adverse effect level F1:
450 mg/kg body weight
Result: No effects on fertility and early embryonic
development were detected.

2,6-di-tert-butyl-p-cresol:

Test Type: Pre-natal
Species: Mouse, female
Application Route: Oral
Duration of Single Treatment: 7 d
General Toxicity Maternal: No observed adverse effect level:
240 mg/kg body weight
Developmental Toxicity: No observed adverse effect level:
800 mg/kg body weight
Target Organs: spleen, Kidney

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate:

Test Type: Pre-natal
Species: Rat, females
Application Route: Oral
Dose: 100/300/1000 mg/kg bw/day
General Toxicity Maternal: No observed adverse effect level:
300 mg/kg body weight
Developmental Toxicity: No-observed-effect level: 1 000
mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes

Reproductive toxicity - Assessment : No data available

STOT - single exposure

Components:

methyl methacrylate:
Exposure routes: Inhalation
Target Organs: Respiratory Tract
Assessment: May cause respiratory irritation.

methacrylic acid:

Exposure routes: Inhalation
Target Organs: Respiratory Tract
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

STOT - repeated exposure

Components:

alpha,alpha-dimethylbenzyl hydroperoxide:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.02.2021	400000011295	Date of first issue: 17.02.2021

Print Date 04.08.2022

Exposure routes: Inhalation
Target Organs: Lungs
Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Repeated dose toxicity

Components:

methyl methacrylate:
Species: Rat, male and female
NOAEL: 124,1 mg/kg
Application Route: oral (drinking water)
Exposure time: 2 years Number of exposures: daily
Dose: 6, 60, 2000 ppm

methacrylic acid:
Species: Rat, male and female
NOEC: 352 - 1232
Application Route: inhalation (vapour)
Test atmosphere: vapour
Exposure time: 90 d Number of exposures: 6 h
Dose: 70/352/1232 mg/m³
Subsequent observation period: 5 days/week
Method: OECD Test Guideline 413
GLP: yes

2,6-di-tert-butyl-p-cresol:
Species: Pig, male and female
NOAEL: >= 61 mg/kg
Application Route: oral (feed)
Exposure time: daily Method: Chronic toxicity

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate:
Species: Rat, male and female
NOEL: 100 mg/kg
Application Route: oral (gavage)
Exposure time: 28 d Number of exposures: 7 days/week
Dose: 0, 100, 300, or 1000 MKD
Method: OECD Test Guideline 407
GLP: yes
Target Organs: Kidney, Stomach

Repeated dose toxicity - : No data available
Assessment

Aspiration toxicity

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

methyl methacrylate:

Toxicity to fish : LC50 : 191 mg/l
Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: Fish Early-life Stage Toxicity Test

Toxicity to daphnia and other : EC50 : 69 mg/l
aquatic invertebrates Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

- Toxicity to algae/aquatic plants : EC50 : > 110 mg/l
Exposure time: 72 h
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 37 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: flow-through test
Method: OECD Test Guideline 211
- methacrylic acid:
- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 85 mg/l
End point: mortality
Exposure time: 96 h
Test Type: flow-through test
Test substance: Fresh water
Method: Fish Acute Toxicity Test
GLP: yes
Remarks: Toxic to aquatic organisms.
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 130 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: flow-through test
Analytical monitoring: yes
Test substance: Fresh water
Method: Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids
GLP: yes
- Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 45 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes
- NOEC (Selenastrum capricornutum (green algae)): 8,2 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes
- Toxicity to microorganisms : EC50 (Pseudomonas putida): 270 mg/l
Exposure time: 16,5 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: DIN 38 412 Part 8
GLP: yes
- Toxicity to fish (Chronic) : NOEC: 10 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

toxicity) Exposure time: 35 d
Species: Brachydanio rerio (zebrafish)
Test Type: flow-through test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 210
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 53 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: flow-through test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 211
GLP: yes

2,6-di-tert-butyl-p-cresol:
Toxicity to fish : LC50 (Fish): 0,199 mg/l
Exposure time: 96 h
Test substance: Fresh water
Method: QSAR

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,48 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0,24 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,24 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to microorganisms : ErC50 (activated sludge): 1,7 mg/l
Exposure time: 24 h
Test Type: static test

Toxicity to fish (Chronic toxicity) : NOEC: 0,053 mg/l
Exposure time: 30 d
Species: Oryzias latipes (Orange-red killifish)
Test substance: Fresh water
Method: OECD Test Guideline 210

NOEC: >= 23,8 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

Exposure time: 70 d
Species: Fish
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 0,096 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Fresh water
Method: OECD Test Guideline 211

NOEC: 0,069 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Fresh water
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 112 mg/l
Exposure time: 96 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 68 mg/l
Exposure time: 48 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 120 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes

NOEC (Pseudokirchneriella subcapitata (algae)): > 30 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes

alpha,alpha-dimethylbenzyl hydroperoxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3,9 mg/l
Exposure time: 96 h
Test Type: semi-static test
Analytical monitoring: no
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 18,84 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

aquatic invertebrates Exposure time: 48 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 3,1 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 201

12.2 Persistence and degradability

Components:

methyl methacrylate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 60 %
Exposure time: 28 d

methacrylic acid:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Concentration: 3 mg/l
Result: Readily biodegradable.
Biodegradation: 86 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
GLP: yes

2,6-di-tert-butyl-p-cresol:

Biodegradability : Result: Not biodegradable

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge, non-adapted
Concentration: 54,6 mg/l
Result: Readily biodegradable.
Biodegradation: 91,8 %
Related to: Dissolved organic carbon (DOC)
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

alpha,alpha-dimethylbenzyl hydroperoxide:

Biodegradability : Result: Not readily biodegradable.

12.3 Bioaccumulative potential

Components:

methyl methacrylate:

Bioaccumulation : Bioconcentration factor (BCF): 3

Partition coefficient: n- : log Pow: 1,38

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.02.2021	400000011295	Date of first issue: 17.02.2021

Print Date 04.08.2022

octanol/water
methacrylic acid:
Partition coefficient: n-
octanol/water : log Pow: 0,93 (22 °C)
pH: 2,2

2,6-di-tert-butyl-p-cresol:
Bioaccumulation : Species: Cyprinus carpio (Carp)
Exposure time: 28 d
Bioconcentration factor (BCF): 330 - 1 800
Method: flow-through test

Partition coefficient: n-
octanol/water : log Pow: 5,2

12.4 Mobility in soil

Components:

2,6-di-tert-butyl-p-cresol:
Distribution among : Koc: 8183
environmental compartments

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

IATA

14.1 UN number or ID number : UN 2924
14.2 UN proper shipping name : Flammable liquid, corrosive, n.o.s.
(METHYL METHACRYLATE, METHACRYLIC ACID)
14.3 Transport hazard class(es) : 3
Subsidiary risk : 8
14.4 Packing group : II
Labels : Flammable Liquids, Corrosive
Packing instruction (cargo aircraft) : 363
Packing instruction (passenger aircraft) : 352

IMDG

14.1 UN number or ID number : UN 2924
14.2 UN proper shipping name : FLAMMABLE LIQUID, CORROSIVE, N.O.S.
(METHYL METHACRYLATE, METHACRYLIC ACID)
14.3 Transport hazard class(es) : 3
Subsidiary risk : 8
14.4 Packing group : II
Labels : 3 (8)
EmS Code : F-E, S-C
14.5 Environmental hazards
Marine pollutant : no

ADR

14.1 UN number or ID number : UN 2924
14.2 UN proper shipping name : FLAMMABLE LIQUID, CORROSIVE, N.O.S.
(METHYL METHACRYLATE, METHACRYLIC ACID)
14.3 Transport hazard class(es) : 3
Subsidiary risk : 8

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

14.4 Packing group : II
Labels : 3 (8)

14.5 Environmental hazards
Environmentally hazardous : no

RID

14.1 UN number or ID number : UN 2924

14.2 UN proper shipping name : FLAMMABLE LIQUID, CORROSIVE, N.O.S.
(METHYL METHACRYLATE, METHACRYLIC ACID)

14.3 Transport hazard class(es) : 3

Subsidiary risk : 8

14.4 Packing group : II
Labels : 3 (8)

14.5 Environmental hazards
Environmentally hazardous : no

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
P5c FLAMMABLE LIQUIDS

General Assessment Methodology (GAM)

Aquatic harmfulness : A3 Hazardous for aquatic organisms, may have long-term hazardous effects in aquatic environment.

Abatement effort : A

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 17.02.2021 SDS Number: 400000011295 Date of last issue: -
Date of first issue: 17.02.2021

Print Date 04.08.2022

- DSL : All components of this product are on the Canadian DSL
- AIIC : On the inventory, or in compliance with the inventory
- NZIoC : Not in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory
- TSCA : All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOIC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

- H225 : Highly flammable liquid and vapour.
- H242 : Heating may cause a fire.
- H302 : Harmful if swallowed.
- H311 : Toxic in contact with skin.
- H312 : Harmful in contact with skin.
- H314 : Causes severe skin burns and eye damage.
- H315 : Causes skin irritation.
- H317 : May cause an allergic skin reaction.
- H318 : Causes serious eye damage.
- H331 : Toxic if inhaled.
- H332 : Harmful if inhaled.
- H335 : May cause respiratory irritation.
- H373 : May cause damage to organs through prolonged or repeated

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.02.2021	400000011295	Date of first issue: 17.02.2021

Print Date 04.08.2022

exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Chronic aquatic toxicity
Eye Dam. : Serious eye damage
Flam. Liq. : Flammable liquids
Org. Perox. : Organic peroxides
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2009/161/EU : Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
NL WG : Netherlands. Law on Labour conditions - Occupational Exposure Limits
2009/161/EU / TWA : Limit Value - eight hours
2009/161/EU / STEL : Short term exposure limit
NL WG / TLV-8hr : Time Weighted Average
NL WG / TLV-15 min : Short Term Exposure Limit

Further information

Classification of the mixture:

Flam. Liq. 2	H225
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
STOT SE 3	H335
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	17.02.2021	400000011295	Date of first issue: 17.02.2021

Print Date 04.08.2022

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 20.05.2021
1.4	03.09.2021	400000001213	Date of first issue: 17.09.2015

Print Date 04.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® 2051 HARDENER

Unique Formula Identifier (UFI) : 49G2-N0RD-700Q-5RAD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Adhesives

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium

Telephone : +41 61 299 20 41
Telefax : +40 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300
NVIC: 088 755 8000. Intended solely for First-Aid professionals following acute poisonings.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Respiratory H335: May cause respiratory irritation.

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

system

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:
methyl methacrylate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
methyl methacrylate	80-62-6 201-297-1 607-035-00-6 01-2119452498-28	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 70 - < 90
3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine	34562-31-7 252-091-3 01-2120769712-47	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Chronic 4; H413	>= 2,5 - < 10
2,6-Di-tert-butyl-p-cresol	128-37-0 204-881-4 01-2119555270-46	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 20.05.2021
1.4	03.09.2021	400000001213	Date of first issue: 17.09.2015

Print Date 04.08.2022

If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Exercise caution when using a high volume water jet as it may scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 20.05.2021
1.4	03.09.2021	400000001213	Date of first issue: 17.09.2015

Print Date 04.08.2022

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Refer to protective measures listed in sections 7 and 8.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Further information on storage stability : Stable under normal conditions.

Recommended storage temperature : 2 - 8 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU
Further information	Indicative			
		STEL	100 ppm	2009/161/EU
Further information	Indicative			
		TLV-8hr	205 mg/m3	NL WG
		TLV-15 min	410 mg/m3	NL WG

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,6-di-tert-butyl-p-cresol	Workers	Inhalation	Long-term systemic effects	3,5 mg/m3
	Workers	Dermal	Long-term systemic effects	0,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,86 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,25 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

				bw/day
	Consumers	Oral	Long-term systemic effects	0,25 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,6-di-tert-butyl-p-cresol	Fresh water	0,199 µg/l
Remarks:	Assessment Factors	
	Marine water	0,02 µg/l
	Assessment Factors	
	Sewage treatment plant	0,17 mg/l
	Assessment Factors	
	Fresh water sediment	0,0996 mg/kg dry weight (d.w.)
	Equilibrium method	
	Marine sediment	0,00996 mg/kg dry weight (d.w.)
	Equilibrium method	
	Soil	0,04769 mg/kg dry weight (d.w.)
	Equilibrium method	
	Oral	8,33 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection
Material : butyl-rubber

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 h

Material : Nitrile rubber
Break through time : 10 - 480 min

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines
Equipment should conform to EN 14387
- Filter type : Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : paste
- Colour : yellow
- Odour : acrylic-like
- Odour Threshold : No data is available on the product itself.
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : No data is available on the product itself.
- Boiling point/boiling range : > 100 °C
Method: estimated
- Flash point : 10 °C
- Evaporation rate : No data is available on the product itself.
- Flammability (solid, gas) : No data is available on the product itself.
- Burning rate : No data is available on the product itself.
- Upper explosion limit / Upper flammability limit : No data is available on the product itself.
- Lower explosion limit / Lower flammability limit : No data is available on the product itself.
- Vapour pressure : No data is available on the product itself.
- Relative vapour density : No data is available on the product itself.
- Relative density : No data is available on the product itself.
- Density : 0,94 - 0,95 g/cm³ (23 °C)
- Solubility(ies)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 20.05.2021
1.4	03.09.2021	400000001213	Date of first issue: 17.09.2015

Print Date 04.08.2022

Water solubility : insoluble

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : No data is available on the product itself.

Viscosity
Viscosity, dynamic : 30 000 - 55 000 mPa.s (20 °C)
thixotropic

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide
carbon monoxide

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 2 000 mg/kg
Method: Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

Components:

methyl methacrylate:
Acute inhalation toxicity : LC50 (Rat, male and female): 29,8 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Directive 67/548/EEC, Annex V, B.2.

Components:

methyl methacrylate:
Acute dermal toxicity : LD50 (Rabbit, male): > 5 000 mg/kg
Method: OECD Test Guideline 402

3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine:
Acute dermal toxicity : LD50 (Rabbit, male and female): > 1 000 mg/kg
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

2,6-di-tert-butyl-p-cresol:
Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Components:

methyl methacrylate:
Species: Rabbit
Method: OPPTS 870.2500
Result: Skin irritation

3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine:
Species: Rabbit
Exposure time: 4 h
Method: Other guidelines
Result: Skin irritation
GLP: yes

2,6-di-tert-butyl-p-cresol:
Species: Rabbit
Assessment: No skin irritation
Method: OECD Test Guideline 404
Result: No skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

Serious eye damage/eye irritation

Components:

3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Mild eye irritation

GLP: yes

2,6-di-tert-butyl-p-cresol:

Species: Rabbit

Assessment: No eye irritation

Method: OECD Test Guideline 405

Result: No eye irritation

Respiratory or skin sensitisation

Components:

methyl methacrylate:

Exposure routes: Skin

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine:

Test Type: Local lymph node assay (LLNA)

Species: Mouse

Assessment: Did not cause sensitisation on laboratory animals.

Method: OECD Test Guideline 429

Result: Did not cause sensitisation on laboratory animals.

GLP: yes

2,6-di-tert-butyl-p-cresol:

Exposure routes: Skin

Species: Humans

Result: Does not cause skin sensitisation.

Assessment: No data available

Germ cell mutagenicity

Components:

methyl methacrylate:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)
Test system: Salmonella typhimurium
Method: OECD Test Guideline 471
Result: negative

3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine:

Genotoxicity in vitro : Test Type: reverse mutation assay
Test system: Salmonella typhimurium and E. coli
Metabolic activation: with and without metabolic activation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

Method: OECD Test Guideline 471
Result: negative
GLP: yes

2,6-di-tert-butyl-p-cresol:
Genotoxicity in vitro

: Test Type: reverse mutation assay
Metabolic activation: with and without metabolic activation
Result: negative

: Test Type: Chromosome aberration test in vitro
Metabolic activation: with and without metabolic activation
Result: negative

Components:

2,6-di-tert-butyl-p-cresol:
Genotoxicity in vivo

: Application Route: Intraperitoneal injection
Dose: 75 mg/kg
Result: negative

Application Route: Oral
Exposure time: 9 Months
Dose: ca 750 mg/kg
Result: negative

Germ cell mutagenicity-
Assessment

: No data available

Carcinogenicity

Components:

methyl methacrylate:

Species: Rat, male and female

Application Route: Oral

Exposure time: 2 Years

Dose: 6, 60, 2000 ppm

Frequency of Treatment: once daily

No observed adverse effect level: 90,3 mg/kg bw/day

Result: negative

2,6-di-tert-butyl-p-cresol:

Species: Rat, male and female

Application Route: Oral

Result: negative

Carcinogenicity -
Assessment

: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

Reproductive toxicity

Components:

2,6-di-tert-butyl-p-cresol:
Effects on fertility

: Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 25/100/500 mg/kg bw/day
General Toxicity - Parent: No observed adverse effect level:
100 mg/kg body weight
General Toxicity F1: No observed adverse effect level: 25
mg/kg body weight
Result: negative

Components:

methyl methacrylate:
Effects on foetal
development

: Species: Rat
Application Route: Inhalation
Dose: 99, 304, 1178 ppm
Teratogenicity: No observed adverse effect concentration F1:
8 300 mg/m³
Embryo-foetal toxicity: No observed adverse effect
concentration F1: 8 300 mg/m³
Method: OECD Test Guideline 414
Result: No teratogenic effects

2,6-di-tert-butyl-p-cresol:

Test Type: Pre-natal
Species: Mouse, female
Application Route: Oral
Duration of Single Treatment: 7 d
General Toxicity Maternal: No observed adverse effect level:
240 mg/kg body weight
Developmental Toxicity: No observed adverse effect level:
800 mg/kg body weight
Target Organs: spleen, Kidney

Reproductive toxicity -
Assessment

: No data available

STOT - single exposure

Components:

methyl methacrylate:
Exposure routes: Inhalation
Target Organs: Respiratory Tract
Assessment: May cause respiratory irritation.

STOT - repeated exposure

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 20.05.2021
1.4	03.09.2021	400000001213	Date of first issue: 17.09.2015

Print Date 04.08.2022

Repeated dose toxicity

Components:

methyl methacrylate:

Species: Rat, male and female

NOAEL: 124,1 mg/kg

Application Route: oral (drinking water)

Exposure time: 2 years Number of exposures: daily

Dose: 6, 60, 2000 ppm

2,6-di-tert-butyl-p-cresol:

Species: Pig, male and female

NOAEL: ≥ 61 mg/kg

Application Route: oral (feed)

Exposure time: daily Method: Chronic toxicity

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

Neurological effects

No data available

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

Components:

methyl methacrylate:

Toxicity to fish : LC50 : 191 mg/l
Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: Fish Early-life Stage Toxicity Test

Toxicity to daphnia and other aquatic invertebrates : EC50 : 69 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 : > 110 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 37 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: flow-through test
Method: OECD Test Guideline 211

3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine:

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 22 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 40 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes

NOEC (Pseudokirchneriella subcapitata (green algae)): 16 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

2,6-di-tert-butyl-p-cresol:

Toxicity to fish : LC50 (Fish): 0,199 mg/l
Exposure time: 96 h
Test substance: Fresh water
Method: QSAR

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,48 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0,24 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,24 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to microorganisms : ErC50 (activated sludge): 1,7 mg/l
Exposure time: 24 h
Test Type: static test

Toxicity to fish (Chronic toxicity) : NOEC: 0,053 mg/l
Exposure time: 30 d
Species: Oryzias latipes (Orange-red killifish)
Test substance: Fresh water
Method: OECD Test Guideline 210

NOEC: >= 23,8 mg/l
Exposure time: 70 d
Species: Fish
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 0,096 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Fresh water
Method: OECD Test Guideline 211

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 20.05.2021
1.4	03.09.2021	400000001213	Date of first issue: 17.09.2015

Print Date 04.08.2022

NOEC: 0,069 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Fresh water
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

Components:

methyl methacrylate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 60 %
Exposure time: 28 d

3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0,132 %
Exposure time: 28 d
Method: QSAR
GLP: no

2,6-di-tert-butyl-p-cresol:

Biodegradability : Result: Not biodegradable

12.3 Bioaccumulative potential

Components:

methyl methacrylate:

Bioaccumulation : Bioconcentration factor (BCF): 3

Partition coefficient: n-octanol/water : log Pow: 1,38

3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine:

Partition coefficient: n-octanol/water : log Pow: > 6,5 (25 °C)
pH: 5,7
Method: OECD Test Guideline 117
GLP: yes

2,6-di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Exposure time: 28 d
Bioconcentration factor (BCF): 330 - 1 800
Method: flow-through test

Partition coefficient: n-octanol/water : log Pow: 5,2

12.4 Mobility in soil

Components:

2,6-di-tert-butyl-p-cresol:

Distribution among : Koc: 8183

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 20.05.2021
1.4	03.09.2021	400000001213	Date of first issue: 17.09.2015

Print Date 04.08.2022

environmental compartments

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1133
ADR : UN 1133
RID : UN 1133

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

IMDG : UN 1133

IATA : UN 1133

14.2 UN proper shipping name

ADN : ADHESIVES

ADR : ADHESIVES

RID : ADHESIVES

IMDG : ADHESIVES

IATA : Adhesives

14.3 Transport hazard class(es)

ADN : 3

ADR : 3

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADN

Packing group : II

Classification Code : F1

Hazard Identification Number : 33

Labels : 3

ADR

Packing group : II

Classification Code : F1

Hazard Identification Number : 33

Labels : 3

Tunnel restriction code : (D/E)

RID

Packing group : II

Classification Code : F1

Hazard Identification Number : 33

Labels : 3

IMDG

Packing group : II

Labels : 3

EmS Code : F-E, S-D

IATA (Cargo)

Packing instruction (cargo aircraft) : 364

Packing instruction (LQ) : Y341

Packing group : II

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 20.05.2021
1.4	03.09.2021	400000001213	Date of first issue: 17.09.2015

Print Date 04.08.2022

Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
P5c FLAMMABLE LIQUIDS

General Assessment Methodology (GAM)

Aquatic harmfulness : A3 Hazardous for aquatic organisms, may have long-term hazardous effects in aquatic environment.

Abatement effort : A

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 20.05.2021
1.4	03.09.2021	400000001213	Date of first issue: 17.09.2015

Print Date 04.08.2022

DSL	:	All components of this product are on the Canadian DSL
AIIC	:	On the inventory, or in compliance with the inventory
NZIoC	:	On the inventory, or in compliance with the inventory
ENCS	:	Not in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOIC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H302	:	Harmful if swallowed.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H335	:	May cause respiratory irritation.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2051 HARDENER

Version 1.4 Revision Date: 03.09.2021 SDS Number: 400000001213 Date of last issue: 20.05.2021
Date of first issue: 17.09.2015

Print Date 04.08.2022

Aquatic Chronic : Chronic aquatic toxicity
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT SE : Specific target organ toxicity - single exposure
2009/161/EU : Europe. COMMISSION DIRECTIVE 2009/161/EU establishing
a third list of indicative occupational exposure limit values in
implementation of Council Directive 98/24/EC and amending
Commission Directive 2000/39/EC
NL WG : Netherlands. Law on Labour conditions - Occupational
Exposure Limits
2009/161/EU / TWA : Limit Value - eight hours
2009/161/EU / STEL : Short term exposure limit
NL WG / TLV-8hr : Time Weighted Average
NL WG / TLV-15 min : Short Term Exposure Limit

Further information

Classification of the mixture:

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Skin Sens. 1 H317
STOT SE 3 H335

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 20.05.2021
1.4	03.09.2021	400000001213	Date of first issue: 17.09.2015

Print Date 04.08.2022



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006