

Advanced Materials

TDR 1100-11 Adhesive

ARCHERY BOW ADHESIVE THIXOTROPIC EPOXY ADHESIVE



DESCRIPTION:

TDR 1100-11 epoxy adhesive is a thixotropic system formulated for bonding glass laminate, wood and plastic components used in the construction of archery bows. Its convenient 2:1 by volume mixing ratio facilitates use of TDR 1100-11 epoxy adhesive with automated metering equipment. TDR 1100-11 epoxy adhesive has a long (> 90 minutes) pot life, cures quickly at temperatures above 170 °F (77 °C) and produces a clear bond line.

TYPICAL PROPERTIES:

Property	Test Method	Test Values ⁽¹⁾	
		<u>Resin</u>	<u>Hardener</u>
Color/Form	Visual	Creamy liquid	Amber liquid
Specific Gravity	ASTM D-792	1.16	0.99
Viscosity, cP @ 77 °F	ASTM D-2393	16,500	38,000
(25 °C)			

TYPICAL MIXED PROPERTIES:

Property	Test Method	Test Values ⁽¹⁾
Resin/Hardener Ratio (by weight)	ASTM D-2471	100/42
Resin/Hardener Ratio (by volume)		100/50
Pot Life, minutes @ 77 °F (25 °C)	ASTM D-2471	95
(4 fl oz mass)		
Mixed Viscosity, cP @ 77 °F (25 °C)	ASTM D-2393	13,000



TYPICAL CURED PROPERTIES:

@ 77 °F (25 °C)		
Cure	15 min. @ 180 °F (82 °C)	15 min. @ 215 °F (102 °C)
Heat deflection temperature, °F (°C)	164 (73)	192 (89)
Tensile Properties		
Ultimate strength, psi (Mpa)	9100 (62.7)	8900 (61.3)
0.2 % offset, psi (Mpa)	5800 (40)	6000 (41.3)
Elongation at break, %	3.6	4.6
Modulus of Elasticity, psi (Mpa)	396,000 (2,731)	342,000 (2,359)
Lap shear strength, psi (Mpa)	3520 (24.3)	4100 (28.3)
@ 77 °F (25 °C)	3000 (20.7)	>3300 (22.7)
@ 160 °F (71 °C)	1900 (13.1)	3200 (22)
@ 190 °F (88 °C)	, ,	, ,

^{* 2024}T3 alclad aluminum etched per ASTM D-2651

CAUTION:

Huntsman Advanced Material Americas Inc. maintains up-to-date Material Safety Data Sheet (MSDS) on all of its products. These sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products. Users should review the latest MSDS to determine possible health hazards and appropriate precautions to implement <u>prior to</u> using this material. Copies of the latest MSDS may be requested by calling our customer service group at 888-564-9318 or emailing your request to advanced_materials@huntsman.com

To protect against any potential health risks presented by our products, the use of proper personal protective equipment (PPE) is recommended. Eye and skin protection is normally advised. Respiratory protection may be needed if mechanical ventilation is not available or is insufficient to remove vapors. For detailed PPE recommendations and exposure control options consult the product MSDS or a Huntsman EHS representative.



FIRST AID:

<u>Eyes and skin</u>: Flush eyes with water for 15 minutes. Contact a physician if irritation persists. Wash skin thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

Inhalation: Remove subject to fresh air.

<u>Swallowing</u>: Dilute by giving water to drink and contact a physician promptly. Never give anything to drink to an unconscious person.

KEEP OUT OF REACH OF CHILDREN FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

IMPORTANT LEGAL NOTICE

Huntsman Advanced Materials warrants only that its products meet the specifications agreed with the user. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications.

The manufacture of materials is the subject of granted patents and patent applications; freedom to operate patented processes is not implied by this publication.

WHILE ALL THE INFORMATION AND RECOMMENDATIONS IN THIS PUBLICATION ARE, TO THE BEST OF HUNTSMAN ADVANCED MATERIAL'S KNOWLEDGE, INFORMATION AND BELIEF, ACCURATE AT THE DATE OF PUBLICATION, nothing herein is to be construed as a warranty, whether express or implied, including but without limitation, as to merchantability or fitness for a particular purpose. In all cases, it is the responsibility of the user to determine the applicability of such information and recommendations and the suitability of any product for its own particular purpose.

The behavior of the products referred to in this publication in manufacturing processes and their suitability in any given end-use environment are dependent upon various conditions such as chemical compatibility, temperature, and other variables, which are not known to Huntsman Advanced Materials. It is the responsibility of the user to evaluate the manufacturing circumstances and the final product under actual end-use requirements and to adequately advise and warn purchasers and users thereof.

Products may be toxic and require special precautions in handling. The user should obtain Safety Data Sheets from Huntsman Advanced Materials containing detailed information on toxicity, together with proper shipping, handling and storage procedures, and should comply with all applicable safety and environmental standards.

Hazards, toxicity and behavior of the products may differ when used with other materials and are dependent on manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.

Except where explicitly agreed otherwise, the sale of products referred to in this publication is subject to the general terms and conditions of sale of Huntsman Advanced Materials LLC or of its affiliated



companies including without limitation, Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas Inc., and Huntsman Advanced Materials (Hong Kong) Ltd.

Huntsman Advanced Materials is an international business unit of Huntsman Corporation. Huntsman Advanced Materials trades through Huntsman affiliated companies in different countries including but not limited to Huntsman Advanced Materials LLC in the USA and Huntsman Advanced Materials (Europe) BVBA in Europe.

Copyright © 2007 Huntsman Corporation or an affiliate thereof. All rights reserved.

Main Offices:
Huntsman Corporation
10003 Woodloch Forest Dr.
The Woodlands
Texas 77380
(281) 719-6000

Huntsman Advanced Technology Center 8600 Gosling Rd. The Woodlands Texas 77381 (281) 719-7400 Website: www.huntsman.com/advanced_materials

