

ARALDITE® 2023-30 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/28/2019

 1.1
 07/06/2021
 400000007157
 Date of first issue: 08/28/2019

Print Date 01/16/2024

SECTION 1. IDENTIFICATION

Product name : ARALDITE® 2023-30 RESIN



chemical-concepts.com 800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006

Manufacturer or supplier's details

Company name of supplier

: Huntsman Advanced Materials Americas LLC: P.O. Box 4980

Address

: P.O. Box 4980 The Woodlands,

TX 77387

United States of America (USA)

Telephone

Non-Emergency: (800) 257-5547

E-mail address of person responsible for the SDS

: Global_Product_EHS_AdMat@huntsman.com

Emergency telephone number

: Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Resin

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Specific target organ toxicity

- single exposure

: Category 3 (Respiratory system)

Short-term (acute) aquatic

hazard

: Category 3

GHS label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.



ARALDITE® 2023-30 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/28/2019

 1.1
 07/06/2021
 400000007157
 Date of first issue: 08/28/2019

Print Date 01/16/2024

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H402 Harmful to aquatic life.

Precautionary statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w.	w)
---------------	---------	---------------------	----



ARALDITE® 2023-30 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/28/2019

 1.1
 07/06/2021
 400000007157
 Date of first issue: 08/28/2019

		Print Date 01/16/2024
methyl methacrylate	80-62-6	30 - 50
titanium dioxide	13463-67-7	5 - 10
silica, amorphous, fumed, crystalline free	7631-86-9	1 - 5
octadecyl methacrylate	32360-05-7	1 - 5
methacrylic acid	79-41-4	1 - 2.5
hexadecyl methacrylate	2495-27-4	1 - 5
Talc (Mg3H2(SiO3)4)	14807-96-6	0.1 - 1
2,6-di-tert-butyl-p-cresol	128-37-0	0.1 - 0.25

SECTION 4. FIRST AID MEASURES

General advice : Treat symptomatically.

Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Get medical attention if irritation develops and persists.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

None known.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

No information available.

Hazardous combustion

products

Carbon oxides

Metal oxides



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019 1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Specific extinguishing

methods

: Standard procedure for chemical fires.

Further information : No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Refer to protective measures listed in sections 7 and 8.

Environmental precautions : No special environmental precautions required.

Methods and materials for containment and cleaning up

Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Conditions for safe storage : No special storage conditions required.

Keep in properly labelled containers.

Materials to avoid : For incompatible materials please refer to Section 10 of this

SDS.

Recommended storage

temperature

: 36 - 46 °F / 2 - 8 °C

Further information on

storage stability

: Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH



ARALDITE® 2023-30 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08/28/2019

 1.1
 07/06/2021
 400000007157
 Date of first issue: 08/28/2019

			Print Date	e 01/16/2024
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	100 ppm 410 mg/m3	NIOSH REL
		TWA	100 ppm 410 mg/m3	OSHA P0
titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
		TWA (Total dust)	10 mg/m3	OSHA P0
silica, amorphous, fumed, crystalline free	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m3 (Silica)	NIOSH REL
methacrylic acid	79-41-4	TWA	20 ppm	ACGIH
		TWA	20 ppm 70 mg/m3	NIOSH REL
		TWA	20 ppm 70 mg/m3	OSHA P0
2,6-di-tert-butyl-p-cresol	128-37-0	TWA (Inhalable fraction and vapor)	2 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : butyl-rubber

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

Material : Nitrile rubber Break through time : 10 - 480 min



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of

contact).

Eye protection : Tightly fitting safety goggles

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : white

Odour : No data is available on the product itself.

Odour Threshold : No data is available on the product itself.

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data is available on the product itself.

Boiling point : $> 212 \, ^{\circ}\text{F} / > 100 \, ^{\circ}\text{C}$

Flash point : 50 °F / 10 °C

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : 1.07 g/cm3

Method: Calculation method

Solubility(ies)

Water solubility : insoluble



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019 40000007157 1.1 07/06/2021 Date of first issue: 08/28/2019

Print Date 01/16/2024

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

Auto-ignition temperature

: No data is available on the product itself.

 $: > 752 \, ^{\circ}\text{F} / > 400 \, ^{\circ}\text{C}$

: > 392 °F / > 200 °C Decomposition temperature

Self-Accelerating

decomposition temperature

(SADT)

No data is available on the product itself.

Viscosity

Viscosity, dynamic : 180,000 - 200,000 mPa.s

Explosive properties No data is available on the product itself.

Oxidizing properties No data is available on the product itself.

Particle size No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No hazards to be specially mentioned.

Conditions to avoid None known.

Incompatible materials None known.

Hazardous decomposition

products

carbon dioxide carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : No data is available on the product itself.

exposure

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity -

Product

Acute toxicity estimate: 55.51 mg/l

Exposure time: 4 h

Test atmosphere: vapour



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019 07/06/2021 40000007157 1.1 Date of first issue: 08/28/2019

Print Date 01/16/2024

Method: Calculation method

Acute dermal toxicity -

: Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute toxicity (other routes of : No data available

administration)

Product

Skin corrosion/irritation

Components:

methyl methacrylate: Species: Rabbit

Method: OPPTS 870.2500 Result: Skin irritation

titanium dioxide: Species: Rabbit

Assessment: No skin irritation Method: OECD Test Guideline 404 Result: Normally reversible injuries

silica, amorphous, fumed, crystalline free:

Species: Rabbit

Assessment: No skin irritation Method: OECD Test Guideline 404

Result: No skin irritation

octadecyl methacrylate: Result: Skin irritation

methacrylic acid: Species: Rabbit

Assessment: Causes severe burns. Method: OECD Test Guideline 404

Result: Extremely corrosive and destructive to tissue.

GLP: yes

hexadecyl methacrylate: Result: Skin irritation

2,6-di-tert-butyl-p-cresol:

Species: Rabbit

Assessment: No skin irritation Method: OECD Test Guideline 404

Result: No skin irritation

Serious eye damage/eye irritation

Components:

titanium dioxide: Species: Rabbit

Result: Normally reversible injuries Assessment: No eye irritation



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019 1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Method: OECD Test Guideline 405

silica, amorphous, fumed, crystalline free:

Species: Rabbit Result: No eye irritation Assessment: No eye irritation Method: OECD Test Guideline 405

octadecyl methacrylate: Result: Eye irritation

methacrylic acid: Species: Rabbit

Result: Irreversible effects on the eye

Assessment: Risk of serious damage to eyes.

Method: Draize Test

GLP: no

hexadecyl methacrylate: Result: Eye irritation

2,6-di-tert-butyl-p-cresol:

Species: Rabbit

Result: No eye irritation Assessment: No eye irritation Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Components:

methyl methacrylate: Exposure routes: Skin Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

titanium dioxide:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin Species: Mouse

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 429 Result: Does not cause skin sensitisation.

Exposure routes: Skin Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

octadecyl methacrylate: Exposure routes: Skin Species: Mouse

Method: OECD Test Guideline 429 Result: Does not cause skin sensitisation.



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

methacrylic acid: Test Type: Buehler Test Exposure routes: Skin Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Method: OECD Test Guideline 406

Result: Did not cause sensitisation on laboratory animals.

hexadecyl methacrylate: Exposure routes: Skin Species: Mouse

Method: OECD Test Guideline 429 Result: Does not cause skin sensitisation.

2,6-di-tert-butyl-p-cresol: Exposure routes: Skin Species: Humans

Result: Does not cause skin sensitisation.

Components:

titanium dioxide:

Assessment: No skin irritation, No eye irritation

Does not cause skin sensitisation., Does not cause respiratory

sensitisation.

Germ cell mutagenicity

Components:

methyl methacrylate:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)

Test system: Salmonella typhimurium Method: OECD Test Guideline 471

Result: negative

titanium dioxide:

Genotoxicity in vitro : Test Type: Ames test

Concentration: 100 - 200 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Concentration: 31 - 500 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Concentration: 125 - 2500 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

silica, amorphous, fumed, crystalline free:



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

octadecyl methacrylate:

Genotoxicity in vitro : Concentration: .1 - 1200 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Concentration: 33 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Concentration: 14.5 - 2233 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

methacrylic acid:

Genotoxicity in vitro : Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

hexadecyl methacrylate:

Genotoxicity in vitro

: Concentration: .1 - 1200 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Concentration: 33 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Concentration: 14.5 - 2233 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

2,6-di-tert-butyl-p-cresol:

Genotoxicity in vitro : Test Type: reverse mutation assay

Metabolic activation: with and without metabolic activation

Result: negative



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Test Type: Chromosome aberration test in vitro

Metabolic activation: with and without metabolic activation

Result: negative

Components:

titanium dioxide:

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (males)
Application Route: Inhalation
Exposure time: 5 consecutive days
Dose: 0.8, 7.2, and 28.5 mg/m³
Method: OECD Test Guideline 474

Result: negative

Test Type: Micronucleus test Species: Rat (male and female)

Application Route: Oral Exposure time: once

Dose: 500, 1000, and 2000 mg/kg bw Method: OECD Test Guideline 474

Result: negative

silica, amorphous, fumed, crystalline free:

Genotoxicity in vivo : Application Route: Inhalation

Dose: 50 mg/m3 Result: negative

octadecyl methacrylate:

Genotoxicity in vivo : Application Route: Oral

Exposure time: 72 h Dose: 5000 mg/kg

Method: OECD Test Guideline 474

Result: negative

methacrylic acid:

Genotoxicity in vivo : Test Type: in vivo assay

Species: Rat (male) Cell type: Somatic

Application Route: Inhalation

Exposure time: 2 h

Dose: 0.4, 1.6, 2.8 and 4 mg/L Method: OECD Test Guideline 475

Result: Not classified due to inconclusive data.

GLP: no

Test Type: dominant lethal test

Species: Mouse (male)
Application Route: Inhalation

Exposure time: 6 h

Dose: 0.405, 4.05 and 36.45 mg/L Method: OECD Test Guideline 478

Result: negative

GLP: no

hexadecyl methacrylate:

Genotoxicity in vivo : Application Route: Oral



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Exposure time: 72 h Dose: 5000 mg/kg

Method: OECD Test Guideline 474

Result: negative

2,6-di-tert-butyl-p-cresol:

Genotoxicity in vivo : Application Route: Intraperitoneal injection

Dose: 75 mg/kg Result: negative

Application Route: Oral Exposure time: 9 Months Dose: ca 750 mg/kg Result: negative

Components:

titanium dioxide:

Germ cell mutagenicity-

Assessment

: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic

effects.

Carcinogenicity

Components:

methyl methacrylate:

Species: Rat, male and female Application Route: Oral

Exposure time: 2 Years Dose: 6, 60, 2000 ppm

Frequency of Treatment: once daily

NOAEL: 90.3 mg/kg bw/day

Result: negative

titanium dioxide:

Species: Rat, male and female Application Route: Oral Exposure time: 103 weeks Dose: 0, 25000, 50000 ppm

Frequency of Treatment: 7 days/week

NOAEL: > 50.000 ppm

Method: No information available.

Remarks: Titanium Dioxide: based on the results of chronic inhalation studies (with positive results only in a single species - rat), IARC has concluded that: "There is inadequate evidence in humans for the carcinogenicity of titanium dioxide." but that: "There is sufficient evidence in experimental animals for carcinogenicity of titanium dioxide". IARCs overall evaluation was that "titanium dioxide is possibly carcinogenic to humans (Group 2B)."

Huntsman has examined all of the available animal carcinogenicity and mechanistic data together with workplace epidemiology data for titanium dioxide and concludes that the weight of scientific evidence indicates that there is no causative link between titanium dioxide exposure and cancer risk in humans and that workplace exposures in compliance with applicable exposure standards will not result in lung cancer or chronic respiratory diseases in humans.



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

silica, amorphous, fumed, crystalline free:

Species: Rat, male and female Application Route: Oral Exposure time: 103 weeks Dose: 1800 - 3200 mg/kg Frequency of Treatment: 7 daily Method: OECD Test Guideline 453

Result: negative

methacrylic acid:

Species: Rat, male and female Application Route: inhalation (vapour)

Exposure time: 102 weeks

Frequency of Treatment: 5 days/week NOAEL: >= 2.05 mg/kg body weight

Method: OECD Test Guideline 451

Species: Mouse, male and female Application Route: inhalation (vapour)

Exposure time: 102 weeks Dose: ca. 2.05 and 4.1 mg/L

Frequency of Treatment: 5 days/week

LOAEL: ca. 2.05 mg/l

Method: OECD Test Guideline 451

2,6-di-tert-butyl-p-cresol: Species: Rat, male and female

Application Route: Oral

Result: negative

Components:

titanium dioxide:

Carcinogenicity - : Not classifiable as a human carcinogen.

Assessment

IARC Group 1: Carcinogenic to humans

Talc (Mg3H2(SiO3)4)

Group 2B: Possibly carcinogenic to humans

titanium dioxide

ACGIH Confirmed human carcinogen

Talc (Mg3H2(SiO3)4)

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

Talc (Mg3H2(SiO3)4)

(Silica, Crystalline (Respirable Size))



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Reproductive toxicity

Components:

octadecyl methacrylate:

Effects on fertility

: Species: Rat, male and female

Application Route: Oral

Dose: >= 1000 milligram per kilogram Frequency of Treatment: 7 days/week Method: OECD Test Guideline 422

Result: negative

Species: Rat, male and female

Application Route: Oral

Dose: 400 milligram per kilogram Frequency of Treatment: 7 days/week Method: OECD Test Guideline 416

Result: negative

methacrylic acid:

Test Type: Two-generation study Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 150, 450 mg/kg/day

General Toxicity - Parent: No observed adverse effect level:

50 mg/kg body weight

Fertility: No observed adverse effect level F1: 400 mg/kg body

weight

Symptoms: Reduced body weight Method: OECD Test Guideline 416

GLP: yes

hexadecyl methacrylate:

Species: Rat, male and female

Application Route: Oral

Dose: >=1000 milligram per kilogram Frequency of Treatment: 7 days/week Method: OECD Test Guideline 422

Result: negative

Species: Rat, male and female

Application Route: Oral

Frequency of Treatment: 7 days/week Method: OECD Test Guideline 416

Result: negative

2,6-di-tert-butyl-p-cresol:

Test Type: Two-generation study Species: Rat, male and female

Application Route: Oral

Dose: 25/100/500 mg/kg bw/day

General Toxicity - Parent: No observed adverse effect level:

100 mg/kg body weight

General Toxicity F1: No observed adverse effect level: 25

mg/kg body weight Result: negative



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Components:

methyl methacrylate:

Effects on foetal development

: Species: Rat

Application Route: Inhalation Dose: 99, 304, 1178 ppm

Teratogenicity: No observed adverse effect concentration F1:

8,300 mg/m³

Embryo-foetal toxicity: No observed adverse effect

concentration F1: 8,300 mg/m³ Method: OECD Test Guideline 414 Result: No teratogenic effects

titanium dioxide:

Species: Rat, male and female

Application Route: Oral

Dose: 100, 300, and 1000 mg/kg bw/ Duration of Single Treatment: 20 d Frequency of Treatment: 7 days/week

General Toxicity Maternal: No observed adverse effect level:

1,000 mg/kg body weight

Developmental Toxicity: No observed adverse effect level:

1,000 mg/kg body weight

Method: OECD Test Guideline 414

Result: No adverse effects

silica, amorphous, fumed, crystalline free:

Species: Mouse

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

1,340 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Species: Rabbit Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

1,600 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Species: Rat

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

1,350 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

octadecyl methacrylate:

Species: Rat, male and female

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

1,000 mg/kg body weight

Method: OECD Test Guideline 422 Result: No teratogenic effects

Species: Rat, female



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019 1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level:

100 ppm

Method: OECD Test Guideline 414 Result: No teratogenic effects

methacrylic acid:

Test Type: Pre-natal Species: Rat, female

Application Route: Inhalation
Dose: 0, 50, 100, 200 or 300 ppm
Duration of Single Treatment: 14 d
Frequency of Treatment: 7 days/week

General Toxicity Maternal: No observed adverse effect level:

200 ppm

Developmental Toxicity: No observed adverse effect level: >=

300 ppm

Embryo-foetal toxicity: No observed adverse effect

concentration F1: 300 ppm

Method: OECD Test Guideline 414

Result: No effects on fertility and early embryonic

development were detected.

Test Type: Pre-natal

Species: Rabbit, male and female

Application Route: Oral

Dose: 50, 150, 450 milligram per kilogram Duration of Single Treatment: 23 d Frequency of Treatment: 7 days/week

General Toxicity Maternal: No observed adverse effect level:

50 mg/kg body weight

Developmental Toxicity: No observed adverse effect level F1:

450 mg/kg body weight

Result: No effects on fertility and early embryonic

development were detected.

hexadecyl methacrylate:

Species: Rat, male and female

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

1,000 mg/kg body weight

Method: OECD Test Guideline 422 Result: No teratogenic effects

Species: Rat, female

Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level:

100 ppm

Method: OECD Test Guideline 414 Result: No teratogenic effects

2,6-di-tert-butyl-p-cresol:

Test Type: Pre-natal Species: Mouse, female Application Route: Oral

Duration of Single Treatment: 7 d



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

General Toxicity Maternal: No observed adverse effect level:

240 mg/kg body weight

Developmental Toxicity: No observed adverse effect level:

800 mg/kg body weight Target Organs: spleen, Kidney

Components:

titanium dioxide:

Reproductive toxicity - : No evidence of adverse effects on sexual function and fertility,

Assessment or on development, based on animal experiments.

STOT - single exposure

Components:

methyl methacrylate: Exposure routes: Inhalation Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

octadecyl methacrylate: Exposure routes: Inhalation Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

methacrylic acid:

Exposure routes: Inhalation Target Organs: Respiratory Tract

Assessment: The substance or mixture is classified as specific target organ toxicant, single

exposure, category 3 with respiratory tract irritation.

hexadecyl methacrylate: Exposure routes: Inhalation Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

methyl methacrylate:

Species: Rat, male and female

NOAEL: 124.1 mg/kg

Application Route: oral (drinking water)

Exposure time: 2 years Number of exposures: daily Dose: 6, 60, 2000 ppm



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

titanium dioxide:

Species: Rat, male and female

NOEC: 3500 mg/m3

Application Route: Ingestion Test atmosphere: dust/mist

Exposure time: 2 yr Number of exposures: 5 d Method: Chronic toxicity

Species: Rat, male and female

NOEC: 10 - 50 mg/m3 Application Route: Inhalation

Exposure time: 2 yr

Number of exposures: 6 hours/day, 5 days/week

Method: Chronic toxicity

silica, amorphous, fumed, crystalline free:

Species: Rat, male and female NOAEL: 7950 - 8980 mg/kg Application Route: Ingestion Exposure time: 4,320 h Number of exposures: 7 d Method: Subchronic toxicity

Species: Rat, male and female NOEC: 4000 - 4500 mg/m3 Application Route: Ingestion Test atmosphere: dust/mist Exposure time: 13 Weeks Number of exposures: 7 d

Method: OECD Test Guideline 413

octadecyl methacrylate:

Species: Rat, male and female

NOAEL: 1000 mg/kg

Application Route: Ingestion Number of exposures: 7 d Method: Subchronic toxicity

Species: Rat, male and female

NOAEL: 120 mg/kg

Application Route: Ingestion Exposure time: 2,160 h Number of exposures: 7 d Method: Subchronic toxicity

methacrylic acid:

Species: Rat, male and female NOEC: 352 - 1232 mg/m3

Application Route: inhalation (vapour)

Test atmosphere: vapour Exposure time: 90 d Number of exposures: 6 h



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019 1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Dose: 70/352/1232 mg/m3

Subsequent observation period: 5 days/week

Method: OECD Test Guideline 413

GLP: yes

hexadecyl methacrylate: Species: Rat, male and female

NOAEL: 1000 mg/kg Application Route: Ingestion Number of exposures: 7 d Method: Subchronic toxicity

Species: Rat, male and female

NOAEL: 120 mg/kg

Application Route: Ingestion Exposure time: 2,160 h Number of exposures: 7 d Method: Subchronic toxicity

2,6-di-tert-butyl-p-cresol: Species: Pig, male and female

NOAEL: >= 61 mg/kg

Application Route: oral (feed)

Exposure time: daily Method: Chronic toxicity

Components:

titanium dioxide:

Repeated dose toxicity -

Assessment

: No skin irritation, No eye irritation

No adverse effect has been observed in chronic toxicity tests.

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

methyl methacrylate:

Toxicity to fish : LC50: 191 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l

Exposure time: 96 h

Test Type: flow-through test

Method: Fish Early-life Stage Toxicity Test

titanium dioxide:

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): >

10,000 mg/l

Exposure time: 96 h
Test Type: semi-static test
Test substance: Marine water
Method: OECD Test Guideline 203

silica, amorphous, fumed, crystalline free:

Toxicity to fish : LL50 (Brachydanio rerio (zebrafish)): > 10,000 mg/l

Exposure time: 96 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

methacrylic acid:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 85 mg/l

End point: mortality Exposure time: 96 h

Test Type: flow-through test Test substance: Fresh water Method: Fish Acute Toxicity Test

GLP: yes

Remarks: Toxic to aquatic organisms.

Talc (Mg3H2(SiO3)4):

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l

Exposure time: 24 h

2,6-di-tert-butyl-p-cresol:

Toxicity to fish : LC50 (Fish): 0.199 mg/l

Exposure time: 96 h



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Test substance: Fresh water

Method: QSAR

Components:

methyl methacrylate:

Toxicity to daphnia and other : EC50: 69 mg/l aquatic invertebrates : Exposure time: 48 h

silica, amorphous, fumed, crystalline free:

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): >= 1,000 mg/l

aquatic invertebrates Exposure time: 24 h
Test Type: static test

Test substance: Fresh water
Method: OECD Test Guideline 202

methacrylic acid:

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 130 mg/l

End point: Immobilization Exposure time: 48 h

Test Type: flow-through test

Analytical monitoring: yes
Test substance: Fresh water

Method: Aquatic Invertebrate Acute Toxicity Test, Freshwater

Daphnids GLP: yes

2,6-di-tert-butyl-p-cresol:

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 0.48 mg/l

End point: Immobilization Exposure time: 48 h

Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Components:

methyl methacrylate:

Toxicity to algae/aquatic : EC50: > 110 mg/l plants : Exposure time: 72 h

silica, amorphous, fumed, crystalline free:

Toxicity to algae/aquatic : EL50 (Desmodesmus subspicatus (green algae)): > 10,000

plants mg/l

Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

methacrylic acid:

Toxicity to algae/aquatic

: ErC50 (Selenastrum capricornutum (green algae)): 45 mg/l

plants

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

I D: vee

GLP: yes



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

NOEC (Selenastrum capricornutum (green algae)): 8.2 mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

2,6-di-tert-butyl-p-cresol:

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 0.24

mg/l

Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.24

mg/l

Exposure time: 72 h Test Type: static test

Exposure time: 72 h

Test substance: Fresh water Method: OECD Test Guideline 201

M-Factor (Acute aquatic

toxicity)

: No data available

Components:

methacrylic acid:

Toxicity to fish (Chronic

toxicity)

: NOEC (Brachydanio rerio (zebrafish)): 10 mg/l

Exposure time: 35 d

Test Type: flow-through test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 210

GLP: yes

2,6-di-tert-butyl-p-cresol:

Toxicity to fish (Chronic

toxicity)

: NOEC (Oryzias latipes (Orange-red killifish)): 0.053 mg/l

Exposure time: 30 d

Test substance: Fresh water Method: OECD Test Guideline 210

NOEC (Fish): >= 23.8 mg/l Exposure time: 70 d

Test substance: Fresh water

Components:

methyl methacrylate:

Toxicity to daphnia and other aquatic invertebrates

(Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 37 mg/l

Exposure time: 21 d

Test Type: flow-through test Method: OECD Test Guideline 211

methacrylic acid:



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019 1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 53 mg/l

Exposure time: 21 d

Test Type: flow-through test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 211

GLP: yes

2,6-di-tert-butyl-p-cresol:

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: EC50 (Daphnia magna (Water flea)): 0.096 mg/l

Exposure time: 21 d

Test substance: Fresh water Method: OECD Test Guideline 211

NOEC (Daphnia magna (Water flea)): 0.069 mg/l

Exposure time: 21 d

Test substance: Fresh water Method: OECD Test Guideline 211

Components:

2,6-di-tert-butyl-p-cresol: M-Factor (Chronic aquatic

toxicity)

: 1

Components:

methacrylic acid:

Toxicity to microorganisms : EC50 (Pseudomonas putida): 270 mg/l

Exposure time: 16.5 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: DIN 38 412 Part 8

GLP: yes

2,6-di-tert-butyl-p-cresol:

Toxicity to microorganisms : ErC50 (activated sludge): 1.7 mg/l

Exposure time: 24 h Test Type: static test

Toxicity to soil dwelling

organisms

: No data available

Components:

titanium dioxide:

Plant toxicity : NOEC: 100,000 mg/kg

Exposure time: 480 h

Components:

titanium dioxide:

Sediment toxicity : (Gammarus pulex (Amphipod)): > 100000 mg/kgsedimentdw

Study: Acute

Test Type: semi-static test Water: Fresh water Exposure duration: 28 d



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Method: ASTM Method, other

(Gammarus pulex (Amphipod)): 100000 mg/kgsedimentdw

Study: Chronic

Test Type: semi-static test Water: Fresh water Exposure duration: 28 d Method: ASTM Method, other

(Gammarus pulex (Amphipod)): 14989 mg/kgsedimentdw

Study: Acute

Test Type: semi-static test Water: Marine water Exposure duration: 10 d

Components:

titanium dioxide:

Toxicity to terrestrial : NOEC: 10,000 mg/kg organisms Exposure time: 672 h

Ecotoxicology Assessment

Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to

the environment

: No data available

Persistence and degradability

Components:

methyl methacrylate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: > 60 % Exposure time: 28 d

methacrylic acid:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Concentration: 3 mg/l

Result: Readily biodegradable.

Biodegradation: 86 % Exposure time: 28 d

Method: OECD Test Guideline 301D

GLP: yes

2,6-di-tert-butyl-p-cresol:

Biodegradability : Result: Not biodegradable

Biochemical Oxygen

Demand (BOD)

: No data available



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

Chemical Oxygen Demand

(COD)

: No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon

(DOC)

: No data available

Physico-chemical

removability

: No data available

Stability in water : No data available

Photodegradation : No data available

Impact on Sewage

Treatment

: No data available

Bioaccumulative potential

Components:

methyl methacrylate:

Bioaccumulation : Bioconcentration factor (BCF): 3

titanium dioxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)

Bioconcentration factor (BCF): 19 - 352

Exposure time: 14 d

Test substance: Fresh water Method: semi-static test

Remarks: Does not bioaccumulate.

2,6-di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 330 - 1,800

Exposure time: 28 d Method: flow-through test

Components:

methyl methacrylate:

Partition coefficient: n-

octanol/water

: log Pow: 1.38

methacrylic acid:

Partition coefficient: n- : log Pow: 0.93 (72 °F / 22 °C)

octanol/water pH: 2.2

hexadecyl methacrylate:

Partition coefficient: n- : log Pow: 8.64 octanol/water : Method: QSAR

GLP: no



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019 40000007157 1.1 07/06/2021 Date of first issue: 08/28/2019

Print Date 01/16/2024

2,6-di-tert-butyl-p-cresol:

Partition coefficient: n-

octanol/water

: log Pow: 5.2

: Koc: 8183

Mobility in soil

Mobility : No data available

Components:

Stability in soil

2,6-di-tert-butyl-p-cresol:

Distribution among

environmental compartments

Other adverse effects

Environmental fate and

pathways

: No data available

: No data available

Results of PBT and vPvB

assessment

: No data available

Endocrine disrupting

potential

: No data available

Adsorbed organic bound

halogens (AOX)

: No data available

Hazardous to the ozone layer

Ozone-Depletion Potential Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

Additional ecological

information

: No data available

Global warming potential

(GWP)

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of contents/ container to an approved waste disposal

plant.



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1133
Proper shipping name : Adhesives

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo : 364

aircraft)

Packing instruction : 353

(passenger aircraft)

IMDG-Code

UN number : UN 1133
Proper shipping name : ADHESIVES

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1133
Proper shipping name : Adhesives

Class : 3 Packing group : II

Labels : FLAMMABLE LIQUID

ERG Code : 128 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
methyl methacrylate	80-62-6	1000	2072
arsenic	7440-38-2	1	
hydroquinone	123-31-9	100	
lead	7439-92-1	10	
nickel	7440-02-0	100	



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019 1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

			1 11111 Date 0 1/ 10/2024
zinc	7440-66-6	1000	
methanol	67-56-1	5000	
Cadmium	7440-43-9	10	
ethylene oxide	75-21-8	10	
Ethylene glycol	107-21-1	5000	

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitisation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

methyl methacrylate 80-62-6 >= 30 - < 50 %

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR

61):

methyl methacrylate 80-62-6

California Prop. 65

WARNING: This product can expose you to chemicals including titanium dioxide, Talc (Mg3H2(SiO3)4), ethylene oxide, which is/are known to the State of California to cause cancer, and

methanol, Ethylene glycol, ethylene oxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components listed in the

Canadian NDSL.

AIIC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.


US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Revision Date : 07/06/2021

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3

Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.



ARALDITE® 2023-30 RESIN

Version Revision Date: SDS Number: Date of last issue: 08/28/2019
1.1 07/06/2021 400000007157 Date of first issue: 08/28/2019

Print Date 01/16/2024

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.





HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024



SECTION 1. IDENTIFICATION

Product name : HARDENER 2023 B

chemical-concepts.com 800.220.1966 410 Pike Road • Huntingdon Valley, PA 19006

Manufacturer or supplier's details

Company name of supplier

: Huntsman Advanced Materials Americas LLC

Address

Telephone

: P.O. Box 4980 The Woodlands,

TX 77387

United States of America (USA): Non-Emergency: (800) 257-5547

E-mail address : Global_Product_EHS_AdMat@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Organic peroxides : Type E

Eye irritation : Category 2A

Skin sensitisation : Category 1

Short-term (acute) aquatic

hazard

Category 1

Long-term (chronic) aquatic

hazard

: Category 1

GHS label elements

Hazard pictograms







Signal word : Warning

Hazard statements : H242 Heating may cause a fire.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention**:



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023
1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P220 Keep/ Store away from clothing/ combustible materials.

P234 Keep only in original container.

P261 Avoid breathing dust.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

P363 Wash contaminated clothing before reuse.

P391 Collect spillage.

Storage:

P410 Protect from sunlight.

P411 + P235 Store at temperatures not exceeding .? °C/ .? °F.

Keep cool.

P420 Store away from other materials.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
dibenzoyl peroxide	94-36-0	20 - 30
silicon dioxide	7631-86-9	1 - 5
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	1 - 5
carbon black	1333-86-4	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

None known.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

Specific hazards during : Do not allow run-off from fire fighting to enter drains or water



Enriching lives through innovation

HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

firefighting courses.

Hazardous combustion

products

Carbon oxides

Halogenated compounds

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Remove all sources of ignition.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for

disposal according to local regulations (see section 13).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation

and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this

product.

Avoid formation of respirable particles.

Do not breathe vapours/dust.



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Store in cool place.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Keep in properly labelled containers.

Materials to avoid : For incompatible materials please refer to Section 10 of this

SDS.

Recommended storage

temperature

: 36 - 46 °F / 2 - 8 °C

Further information on

storage stability

Stable under normal conditions.

Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dibenzoyl peroxide	94-36-0	TWA	5 mg/m3	ACGIH
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA P0
silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
		TWA	6 mg/m3 (Silica)	NIOSH REL
		PEL (respirable)	0.05 mg/m3	OSHA CARC



HARDENER 2023 B

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/15/2023

 1.1
 03/21/2023
 400000012364
 Date of first issue: 03/15/2023

Print Date 01/16/2024 carbon black 1333-86-4 **TWA** 3 mg/m3 **ACGIH** (Inhalable particulate matter) TWA 3.5 mg/m3 OSHA Z-1 TWA 3.5 mg/m3 **NIOSH REL** TWA 3.5 mg/m3 OSHA P0 **NIOSH REL TWA** 0.1 mg/m3(PAHs)

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn.

unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : black

Odour : slight

Odour Threshold : No data is available on the product itself.



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flash point : No data is available on the product itself.

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : 1.1 g/cm3 (77 °F / 25 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Auto-ignition temperature :

: No data is available on the product itself.

Decomposition temperature : Decomposition energy (mass): 281 KJ/kg

Self-Accelerating

decomposition temperature

(SADT)

122 °F / 50 °C

Viscosity

Viscosity, dynamic : 60,000 - 80,000 mPa.s (77 °F / 25 °C)

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

Particle size : No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Dust may form explosive mixture in air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : None known.

Hazardous decomposition

products

Hazardous decomposition

products

No decomposition if stored and applied as directed.

carbon dioxide carbon monoxide

Halogenated compounds

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

dibenzoyl peroxide:

Acute oral toxicity : LD50 (Mouse, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat, male): > 24.3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute

inhalation toxicity

silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male and female): > 58.8 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral

toxicity

Remarks: No mortality observed at this dose.



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

carbon black:

Acute oral toxicity : LD50 (Rat, male and female): > 8,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/m3

Exposure time: 4 h

Test atmosphere: dust/mist

Skin corrosion/irritation

Components:

dibenzoyl peroxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

silicon dioxide:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rabbit Exposure time : 4 h

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

carbon black:

Species : Rabbit Exposure time : 4 h

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

Serious eye damage/eye irritation

Components:

dibenzoyl peroxide:

Species : Rabbit

Result : Irritating to eyes.

Method : OECD Test Guideline 405



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

silicon dioxide:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rabbit

Result : Irritating to eyes.
Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

carbon black:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

Respiratory or skin sensitisation

Components:

dibenzoyl peroxide:

Exposure routes : Skin Species : Mouse

Assessment : May cause sensitisation by skin contact.

Method : OECD Test Guideline 429
Result : Causes sensitisation.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin Species : Mouse

Method : OECD Test Guideline 429

Result : The product is a skin sensitiser, sub-category 1B.

carbon black:

Test Type : Buehler Test

Exposure routes : Skin Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Exposure routes : Respiratory Tract

Species : Mouse

Assessment : Does not cause respiratory sensitisation. Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Components:

dibenzoyl peroxide:



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Cell type: Somatic

Application Route: Intraperitoneal injection

Dose: 0, 50, 100, 200 mg/kg b.w. Method: OECD Test Guideline 474

Result: negative

silicon dioxide:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Application Route: Inhalation

Dose: 50 mg/m3 Result: negative

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: without metabolic activation

Result: positive

Test Type: reverse mutation assay Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse

mutation assay) Result: negative

Genotoxicity in vivo : Test Type: in vivo assay

Species: Mouse (male) Cell type: Germ Application Route: Oral Dose: 3333, 10000 mg/kg

Result: negative

Test Type: gene mutation test

Species: Rat (male) Cell type: Somatic Application Route: Oral



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

Dose: 50,250,500,1000 mg/kg bw/day Method: OECD Test Guideline 488

Result: negative

carbon black:

Genotoxicity in vitro : Test Type: sister chromatid exchange assay

Test system: Chinese hamster ovary cells

Concentration: 0.00032-1 mg/ml

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 479

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: in vivo assay

Species: Rat (females)
Cell type: Somatic

Application Route: Inhalation Dose: 10 - 100 mg/kg Result: positive

Test Type: in vivo assay Species: Rat (females) Application Route: Inhalation Exposure time: 13 Weeks Dose: 1 - 50 mg/m3 Result: negative

Test Type: in vivo assay Application Route: Oral Exposure time: 6 h

Dose: 1%

Method: OECD Test Guideline 477

Result: negative

Germ cell mutagenicity -

Assessment

Contains no ingredient listed as a mutagen

Carcinogenicity

Components:

dibenzoyl peroxide:

Species : Mouse, male and female

Application Route : Dermal Exposure time : 104 weeks



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

Result : negative

silicon dioxide:

Species : Rat, male and female

Application Route : Oral Exposure time : 103 weeks

Dose : 1800 - 3200 mg/kg

Frequency of Treatment : 7 daily

Method : OECD Test Guideline 453

Result : negative

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male
Application Route : Oral

Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week NOAEL : 15 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Mouse, male
Application Route : Dermal
Exposure time : 24 month(s)

Dose : 0, 0.1, 10, 100 mg/kg bw/day

Frequency of Treatment : 3 days/week

NOEL : 0.1 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Rat, female
Application Route : Dermal
Exposure time : 24 month(s)

Dose : 0.1, 100, 1000 mg/kg bw/day

Frequency of Treatment : 5 days/week

NOEL : 100 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative

Species : Rat, female
Application Route : Oral
Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week

NOAEL : 100 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Rat, females

Application Route : Oral Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

Frequency of Treatment : 7 days/week
NOEL : 2 mg/kg bw/d

NOEL : 2 mg/kg bw/day
Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

carbon black:

Species: Mouse, femaleApplication Route: InhalationExposure time: 13.5 month(s)Dose: 7.5 - 12 mg/m³

Frequency of Treatment : 5 daily

Method : OECD Test Guideline 451

Result : negative

Species : Mouse, male and female

Application Route : Dermal
Exposure time : 18 month(s)
Frequency of Treatment : 3 daily
Result : negative

Species : Rat, female

Application Route : Oral

Exposure time : 24 month(s)

Dose : 52 mg/kg

Frequency of Treatment : 7 daily

Result : negative

Species : Rat, male and female

Application Route : Inhalation

Exposure time : 24 month(s)

Dose : 7,5 - 12,2 mg/m³

Frequency of Treatment : 5 daily

Method : OECD Test Guideline 451

Result : positive Target Organs : Lungs

Species : Mouse Application Route : Dermal

Exposure time : 9 - 24 month(s)

Dose : 6 - 60%

Frequency of Treatment : 2 daily

Method : OECD Test Guideline 451

Result : negative

Species : Mouse, male and female

Application Route : Oral

Exposure time : 12 - 18 month(s)

Dose : 10%
Frequency of Treatment : 7 daily
Result : negative

Species : Rat, male and female

Application Route : Inhalation Exposure time : 24 month(s) Dose : 2,5 mg/m3



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 400000012364 1.1 03/21/2023 Date of first issue: 03/15/2023

Print Date 01/16/2024

Frequency of Treatment

16 hr/day, 5 d/wk

Method Result

OECD Test Guideline 451

positive **Target Organs** Lungs

Carcinogenicity -Assessment

Weight of evidence does not support classification as a carcinogen, Tumours produced in rats on inhalation of very high concentrations are believed to be the result of prolonged "lung overload" and are not considered relevant to man.

IARC Group 1: Carcinogenic to humans

> silicon dioxide 7631-86-9

(Silica dust, crystalline)

OSHA OSHA specifically regulated carcinogen

> silicon dioxide 7631-86-9

(crystalline silica)

NTP Known to be human carcinogen

> silicon dioxide 7631-86-9

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Components:

dibenzoyl peroxide:

Species: Rat. male and female Effects on fertility

Application Route: Oral

Dose: 0, 250, 500, 1,000 mg/kg b.w/

General Toxicity - Parent: NOAEL: 500 mg/kg body weight General Toxicity F1: NOAEL: 500 mg/kg body weight

Method: OECD Test Guideline 422

Effects on foetal development

Species: Rat

Dose: 100, 300 or 1000 mg/kg/day

General Toxicity Maternal: NOAEL: 300 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight

Method: OECD Test Guideline 414

silicon dioxide:

Effects on foetal development

Species: Mouse

Application Route: Oral

General Toxicity Maternal: NOAEL: 1,340 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Species: Rabbit Application Route: Oral

General Toxicity Maternal: NOAEL: 1,600 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Species: Rat

Application Route: Oral



HARDENER 2023 B

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03/15/2023

 1.1
 03/21/2023
 400000012364
 Date of first issue: 03/15/2023

Print Date 01/16/2024

General Toxicity Maternal: NOAEL: 1,350 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 180, 540 or 750 milligram per kilogram

Duration of Single Treatment: 238 d Frequency of Treatment: 1 daily

General Toxicity - Parent: NOEL: 540 mg/kg body weight General Toxicity F1: NOEL: 750 mg/kg body weight

Symptoms: No adverse effects Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Effects on foetal development

Species: Rabbit, female Application Route: Dermal

Dose: 0, 30, 100 or 300 milligram per kilogram

Duration of Single Treatment: 28 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight

Method: Other guidelines Result: No teratogenic effects

Test Type: Pre-natal Species: Rabbit, female Application Route: Oral

Dose: 0, 20, 60 or 180 milligram per kilogram

Duration of Single Treatment: 13 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 60 mg/kg body weight Developmental Toxicity: NOAEL: 180 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Test Type: Pre-natal Species: Rat, female Application Route: Oral

Dose: 0, 60, 180 and 540 milligram per kilogram

Duration of Single Treatment: 10 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 180 mg/kg body weight Developmental Toxicity: NOAEL: > 540 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

STOT - single exposure

No data available



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

STOT - repeated exposure

Components:

carbon black:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

dibenzoyl peroxide:

Species : Rat, male and female

NOAEL : > 100 mg/kg
Application Route : Skin contact
Number of exposures : 2 years

Method : OECD Test Guideline 451

silicon dioxide:

Species : Rat, male and female NOEC : 4000 - 4500 mg/m3

Application Route : Ingestion
Test atmosphere : dust/mist
Exposure time : 13 Weeks

Number of exposures : 7 d

Method : OECD Test Guideline 413

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male and female

NOAEL : 50 mg/kg
Application Route : oral (gavage)
Exposure time : 14 Weeks

Number of exposures : 7 d

Dose : 0, 50, 250, 1000 mg/kg/day Method : OECD Test Guideline 408

Species : Rat, male and female

NOAEL : >= 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks

Number of exposures : 5 d

Dose : 0, 10, 100, 1000 mg/kg/day Method : OECD Test Guideline 411

Species : Mouse, male NOAEL : 100 mg/kg
Application Route : Skin contact Exposure time : 13 Weeks

Number of exposures : 3 d

Dose : 0, 1, 10, 100 mg/kg/day
Method : OECD Test Guideline 411

carbon black:

Species : Mouse, male and female



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 400000012364 1.1 03/21/2023 Date of first issue: 03/15/2023

Print Date 01/16/2024

NOEL > 1000000 mg/kgApplication Route oral (feed) Exposure time 12 - 18 months Number of exposures continuously

Species Rat, females **NOEL** 52 mg/kg oral (feed) Application Route 52 Weeks Exposure time Number of exposures Continously Dose 2.05 g/kg

Species Mouse, females **NOEL** 137 mg/kg Application Route oral (feed) Exposure time 52 Weeks Number of exposures : Continously Dose : 2.05 g/kg

Method : OECD Test Guideline 413

Species Rat. male and female

LOEC 2.5 mg/m3

Application Route inhalation (dust/mist/fume)

Exposure time 24 Months

Number of exposures 16 h/day, 5 days/wk 2.5 or 6.5 mg/m3 Dose

OECD Test Guideline 452 Method

Target Organs Lungs

Mouse, male and female Species

Application Route Dermal Number of exposures 3 times/week

Dose 20%

Symptoms see user defined free text

Aspiration toxicity

No data available

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

dibenzoyl peroxide:



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.0602 mg/l

Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.11 mg/l

Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EbC50 (Selenastrum capricornutum (green algae)): 0.0422

mg/l

Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

M-Factor (Acute aquatic

toxicity)

10

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

EC10 (Daphnia magna (Water flea)): 0.001 mg/l

Exposure time: 21 d Test Type: semi-static test

Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

toxicity)

10

Toxicity to microorganisms : EC50 (activated sludge): 35 mg/l

Exposure time: 0.5 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 209

silicon dioxide:

Toxicity to fish : LL50 (Brachydanio rerio (zebrafish)): > 10,000 mg/l

Exposure time: 24 h

Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): >= 1,000 mg/l

Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Desmodesmus subspicatus (green algae)): > 10,000

mg/l

Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 400000012364 1.1 03/21/2023 Date of first issue: 03/15/2023

Print Date 01/16/2024

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Toxicity to fish

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50: 11 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: EPA-660/3-75-009

NOEC: 4.2 mg/l Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: EPA-660/3-75-009

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 0.3 mg/l

Exposure time: 21 d Test Type: semi-static test Test substance: Fresh water Method: OECD Test Guideline 211

Toxicity to microorganisms IC50 (activated sludge): > 100 mg/l

> Exposure time: 3 h Test Type: static test

Test substance: Fresh water

Ecotoxicology Assessment

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects.

carbon black:

Toxicity to fish LC50 : > 1,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 5,600 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50: > 10,000 mg/lExposure time: 72 h

Toxicity to microorganisms IC0: > 800 mg/l

Exposure time: 3 h



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

Persistence and degradability

Components:

dibenzoyl peroxide:

Biodegradability : Inoculum: activated sludge

Concentration: 4 mg/l

Result: Readily biodegradable.

Biodegradation: 68 % Exposure time: 28 d

Method: OECD Test Guideline 301D

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : aerobic

Inoculum: activated sludge, non-adapted

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C) pH: 4

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C) pH: 9

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C) pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

carbon black:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: < 60 % Exposure time: 28 d

Bioaccumulative potential

Components:

dibenzoyl peroxide:

Partition coefficient: n- : log Pow: 3.2 (72 °F / 22 °C)

octanol/water pH: 7.02

Method: OECD Test Guideline 117

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31

Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 3.242 (77 °F / 25 °C)

octanol/water pH: 7.1

Method: OECD Test Guideline 117



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

carbon black:

Bioaccumulation : Bioconcentration factor (BCF): 1

Mobility in soil

Components:

dibenzoyl peroxide:

Distribution among : Koc: 6309.57

environmental compartments Method: OECD Test Guideline 121

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among

environmental compartments

: Koc: 445

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3108

Proper shipping name : Organic peroxide type E, solid

Class : 5.2



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023
1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

Packing group : Not assigned by regulation

Labels : Organic Peroxides, Keep Away From Heat

Packing instruction (cargo : 570

aircraft)

Packing instruction : 570

(passenger aircraft)

IMDG-Code

UN number : UN 3108

Proper shipping name : ORGANIC PEROXIDE TYPE E, SOLID

Class : 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code : F-J, S-R

Marine pollutant : yes(DIBENZOYL PEROXIDE)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 3108

Proper shipping name : Organic peroxide type E, solid

Class : 5.2

Packing group : Not assigned by regulation Labels : ORGANIC PEROXIDE

ERG Code : 145

Marine pollutant : yes(DIBENZOYL PEROXIDE)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 311/312 Hazards : Organic peroxides

Respiratory or skin sensitisation Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

dibenzoyl peroxide 94-36-0 >= 20 - < 30 %

zinc distearate 557-05-1 >= 1 - < 5 %

This product does not contain any hazardous air pollutants (HAP) >=0.1%, as defined by the U.S. Clean Air Act Section 112 (40 CFR 61



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023
1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

California Prop. 65

WARNING: This product can expose you to chemicals including 4,4'-isopropylidenediphenol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not

on the Canadian DSL nor NDSL.

AllC : All components are listed on the inventory, regulatory

obligations/restrictions apply. Please contact your sales representative for more information before import into

Australia

ENCS : On the inventory, or in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On or in compliance with the active portion of the TSCA

inventory

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.



HARDENER 2023 B


Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Revision Date : 03/21/2023

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3

Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.



HARDENER 2023 B

Version Revision Date: SDS Number: Date of last issue: 03/15/2023 1.1 03/21/2023 400000012364 Date of first issue: 03/15/2023

Print Date 01/16/2024

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

