

SAFETY DATA SHEET



Date issued : 12/03/2007
 SDS number : 11730062_PT28
 Date revised : 10/24/2022
 Revision number : 11

1. Identification

Product code: 11730062_PT28

Product description: ZAP FOAM SAFE KICKER 2OZ (72)

Manufacturer / Supplier

Pacer Technology
 3281 E. Guasti Road, Suite 260
 Ontario, CA 91761

Emergency contact: Chemtrec

Emergency Phone: (800) 424-9300

Customer Service: (909) 987-0550

Emergency telephone number (24 hour)

CHEMTREC (800) 424-9300

2. Hazard identification

Classification of the substance or mixture

Health hazards:

Eye Irritation, Category 2

Specific Target Organ Toxicity Single Exposure, Category 3

Physical hazards:

Flammable Liquids, Category 2

Label elements

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.



Flame



Exclamation
mark

Signal word: DANGER

Hazard statement(s)

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Precautionary statement(s)

Prevention:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read carefully and follow all instructions.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271: Use only outdoors or in a well-ventilated area.

Response:

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006

SAFETY DATA SHEET



Date issued : 12/03/2007
 SDS number : 11730062_PT28
 Date revised : 10/24/2022
 Revision number : 11

do. Continue rinsing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P337: If eye irritation persists: seek medical attention.

P370+P378: In case of fire: Use water fog or spray, alcohol foam, carbon dioxide, or dry chemical to extinguish.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

3. Composition/information on ingredients

Chemical name	% w/w	CAS No.
2-Propanol	90 - 100	67-63-0
Dimethyltolylamine	< 2	99-97-8

4. First-aid measures

Eye: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

Skin: Flush skin with soap and water. Get medical attention if irritation occurs and persists. Remove and launder clothing before re-use.

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Keep the victim calm and warm. Get medical attention if you feel unwell.

Inhalation: Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention if symptoms persist.

Most important symptoms and effects, both acute and delayed

Eye: May cause moderate to severe eye irritation.

Inhalation: Inhalation of mists or vapors may cause headache, dizziness, nausea, and other symptoms of central nervous system depression.

5. Fire-fighting measures

General hazard: Flammable liquid and vapor.

Suitable extinguishing media: Use water fog or spray, alcohol foam, carbon dioxide or dry chemical.

Hazardous combustion products: Oxides of carbon and other toxic or irritating compounds.

Explosion hazards: Highly flammable liquid and vapor. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. Vapors may form explosive mixtures with air in confined areas.

Fire fighting equipment: Wear an approved, positive pressure, self-contained breathing apparatus and full protective clothing. Use water to cool exposed containers and disperse flammable vapors.

6. Accidental release measures

Small spill: Contain and collect using inert absorbent materials (such as sawdust or vermiculite) and place in appropriate containers for disposal. Use non-sparking tools and equipment.

Large spill: Contain and collect using inert absorbent materials (such as sawdust or vermiculite) and place in appropriate containers

SAFETY DATA SHEET



Date issued : 12/03/2007
 SDS number : 11730062_PT28
 Date revised : 10/24/2022
 Revision number : 11

for disposal. Use non-sparking tools and equipment.

General procedures: Remove all ignition sources such as open flames, spark producing equipment, pilot lights, etc. Avoid contact with eyes. Avoid prolonged contact with skin or clothing. Wear appropriate protective clothing to prevent eye and skin contact including impervious gloves, safety goggles and respirator if needed. Avoid breathing mists or vapors. Ventilated area.

7. Handling and storage

General procedures: Avoid breathing mists or vapors. Use with adequate ventilation. Avoid contact with the eyes, skin, and clothing. Wear appropriate protective clothing as described in section 8. Wash thoroughly after handling. Do not eat, drink, or smoke in the work area. Keep product away from heat, sparks, flames, and all other sources of ignition. No smoking in storage or use areas. Keep containers close when not in use. Use with non-sparking tools.

Conditions for safe storage: Store container in a cool, well-ventilated location away from strong oxidizers and other incompatible materials. Keep container tightly closed when not in use. Keep away from sources of ignition.

Storage temperature: 30°C (86°F)

8. Exposure controls/personal protection

Exposure controls

Control parameters				
Occupational exposure limit values				
Chemical name	Type		ppm	mg/m ³
2-Propanol	ACGIH	TWA	200	
		STEL	400	
Dimethyltolylamine	OSHA PEL	TWA	0.50 ppm	Not Established
		STEL	Not Established	Not Established
	ACGIH TLV	TWA	Not Established	Not Established
		STEL	Not Established	Not Established

Appropriate engineering controls: Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits. Use explosion proof electrical equipment and wiring where required.

Individual protection measures, such as personal protective equipment

Eye / face protection: Chemical safety goggles are recommended where splashing is possible.

Skin protection - hand protection: Impervious gloves are suggested to prevent prolonged skin contact. Contact your glove supplier for selection assistance.

Respiratory protection: If needed, an approved respirator with organic vapor cartridges may be used. For higher exposures, supplied air respirator may be required. Respirator selection and use should be based on contaminant type, form, and concentration. follow applicable regulations and good Industrial Hygiene practice.

Skin protection - other: Impervious clothing is required to prevent skin contact and contamination of personal clothing. An eye wash facility and safety shower should be available in work area.

9. Physical and chemical properties

Physical state: Liquid

Appearance: Water-white to straw colored liquid

SAFETY DATA SHEET



Date issued : 12/03/2007
 SDS number : 11730062_PT28
 Date revised : 10/24/2022
 Revision number : 11

Color: Colorless
Odor: Mild odor
Odor threshold: Not Established
pH: Not Established
Melting point: No data available
Freezing point: No data available
Initial boiling point and boiling range: 82°C (179.6°F) to 92°C (197.6°F)
Flash point: 12°C (53.6°F) TCC
Evaporation rate (n-butyl acetate = 1): 1.7
Notes: Butyl Acetate = 1
Flammability: No data available
Lower explosion limit / flammability limit: 2% vol
Upper explosion limit / flammability limit: 12% vol
Vapor pressure: No data available
Relative vapor density: 2.1 (Air=1)
Density: No data available
Relative density: 0.79
Solubility: Soluble
Partition coefficient n-octanol/water (logarithmic value): No data available
Auto-ignition temperature: No data available
Decomposition temperature: No data available
Viscosity: < 10 Centipoise
Molecular weight: No data available
Pour point: No data available
Percent volatiles: No data available

10. Stability and reactivity

Reactivity: Not reactive
Dangerous polymerization: Hazardous polymerization will not occur.
Chemical stability: Stable under normal storage and handling conditions.
Conditions to avoid: Keep away from heat, sparks, flames, and other sources of ignition. Avoid temperatures over 30C(86F) or freezing temperatures.
Possibility of hazardous reactions: Hazardous reactions are possible when exposed to incompatible materials such as nitrates, chlorine, ammonia, strong oxidizers, alkalis, and acids
Hazardous decomposition products: Combustion will produce oxides of carbon and other toxic or irritating compounds.
Incompatible materials: Strong oxidizing agents, aluminum, acetaldehyde, chlorine, ethylene oxide, hydrogen palladium, hydrogen peroxide-sulfuric acid, isocyanates, nitro form, phosgene, alkalis, amines, halogens, and anhydrides.

11. Toxicological information

Acute toxicity

SAFETY DATA SHEET



Date issued : 12/03/2007
 SDS number : 11730062_PT28
 Date revised : 10/24/2022
 Revision number : 11

Chemical name	LD ₅₀ (oral) mg/kg(rat)	LD ₅₀ (dermal) mg/kg(rabbit)	LC ₅₀ (inhalation) mg/l
Dimethyltolylamine	1650 mg/kg (rat)	> 2000 mg/kg (rat)	498 mL/m3

Notes: Product ATE: 5000 mg/kg (oral), 70 mg/L (inhalation), 46750 mg/kg (dermal)

Isopropanol: Oral rat LD50- 5045 mg/kg; Skin rabbit LD50- 12800 mg/kg; inhalation rat LC50 72.6 mg/L/4hr

N, N-Dimethyl-p-Toluidine: Oral mouse LD50- 139 mg/kg, Oral rat LD50- 980-1650 mg/kg, Inhalation rat LC50: 1.4-1.92 mg/L/4hr,
 Skin rabbit LD50: <935 mg/kg

Skin corrosion / irritation: Isopropanol: Non-irritating to rabbit skin. N,N-Dimethyl-p-Toluidine: not irritating in rabbit skin.

Serious eye damage / irritation: Isopropanol: Irritating to rabbit eyes. N,N-Dimethyl-p-Toluidine: Not irritating to rabbit eyes.

Respiratory or skin sensitization: No data available

Germ cell mutagenicity: Isopropanol: Negative in a mammalian gene mutation assay and in vivo mammalian bone marrow cytogenetic test.

Carcinogenicity

IARC: Not listed

NTP: Not listed.

OSHA: Not listed

Notes: None of the components of this product are listed as carcinogens by OSHA, IARC, NTP, ACGIH, and the EU CLP.

Reproductive toxicity: Isopropanol: in a one generation study with rats, NOEL was 2.5%. At 2.0% and 2.5% there was evidence of embryo toxicity. At 1.25%, 2.0%, and 2.5%, all rats showed signs of liver and kidney effects. At 2.5% the rats showed signs of anemia.

Specific Target Organ Toxicity - single exposure: No data available

Specific Target Organ Toxicity - repeated exposure: Isopropanol: 13 week inhalation study with rats found that effects of narcosis at 5000 ppm. These effects are reversible at the cessation of exposure. A 73 week chronic study in rats found male reproductive effects at 2500 and 5000 ppm and liver effects at 2500 ppm.

N,N-Dimethyl-p-Toluidine: In a repeated dose toxicity study, rats were exposed to N,N-Dimethyl-p-Toluidine by oral gavage in the concentrations of 0,6,20, and 60 mg/kg. The results showed toxic effects such as significant histopathological changes in the liver, nose, thyroid gland, spleen, bone marrow and mesenteric lymph node, kidney, forestomach, tongue, mammary gland, urinary bladder and uterus effects. The LOAEL is considered to be 6 mg/kg.

Aspiration hazard: Components are not aspiration hazards.

12. Ecological information

Ecotoxicological information: No data available

Aquatic toxicity, both acute and chronic: Isopropanol: 96hr LC50 Fathead minnow (flow through) - 9640 mg/L; 48 hr EC50 Daphnia magna - 13299 mg/L

N,N-Dimethyl-p-Toluidine: 96 hr LC50 Fathead minnow - 46 mg/L, 48 hr EC50 Daphnia magna - 13.7 mg/L

Bioaccumulative potential: No data available

Other adverse effects: No data available

General comments: Persistence and Degradability: Isopropanol: Readily biodegradable - 95% after 21 days. N,N-Dimethyl-p-Toluidine: expected to be readily biodegradable in water while it is likely to be persistent in sediment - 50% degradation in 38 days in water, 50% degradation in 540 days in sediment.

13. Disposal considerations

Disposal methods: Dispose of in accordance with all local, state, and federal regulations.

SAFETY DATA SHEET



Date issued : 12/03/2007
 SDS number : 11730062_PT28
 Date revised : 10/24/2022
 Revision number : 11

14. Transport information

USA Department of Transport Regulations (DOT)

UN proper shipping name: UN1219, ISOPROPANOL SOLUTION, 3, II (LTD QTY, IP VOL LESS THAN OR EQUAL TO 1.0 L)

ICAO / IATA - air

UN proper shipping name: ID8000 CONSUMER COMMODITY, 9 (IP VOL LESS THAN OR EQUAL TO 0.5 L); or UN1219, ISOPROPANOL SOLUTION, 3, II, (LTD QTY, IP VOL LESS THAN OR EQUAL TO 0.5 L) *

IMO / IMDG - International

UN proper shipping name: UN1219, ISOPROPANOL SOLUTION, 3, II, (LTD QTY, IP VOL LESS THAN OR EQUAL TO 1.0 L) *
Comments: * This product may be shipped as EXCEPTED QUANTITIES OF CLASS 3, UN1219 (IP VOL LESS THAN OR EQUAL TO 0.03 L, OP VOL LESS THAN OR EQUAL TO 0.5 L)

The transport information provided in this section only applies to the material formulation/itself, and is not specific to any package/configuration. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organizations to follow all applicable laws, regulations, and rules relating to the transportation of the material.

15. Regulatory information

UNITED STATES

SARA Section 311/312 Hazard Categories

EPCRA Section 313 Toxic Chemicals

Chemical name	% w/w	CAS No.
2-Propanol	90 - 100	67-63-0

TSCA (The Toxic Substances Control Act)

Chemical name	CAS No.
2-Propanol	67-63-0
Dimethyltolylamine	99-97-8

TSCA Status: All components are listed on or are exempt from listing on the Toxic Substances Control Act.

California Proposition 65: **WARNING:** This product can expose you to chemicals including *N,N*-Dimethyl-*p*-toluidine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical name	% w/w	Listed
Dimethyltolylamine	< 2	● Cancer

16. Other information

Approved by: Pacer Technology Regulatory Affairs Department

Prepared by: Pacer Technology Regulatory Affairs Department **Date revised:** 10/24/2022

Revision summary: This SDS replaces the 09/14/2017 SDS. Revised: **Section 1:** Approved by, SDS number, Prepared by,

SAFETY DATA SHEET




Date issued : 12/03/2007
 SDS number : 11730062_PT28
 Date revised : 10/24/2022
 Revision number : 11

Product code. **Section 2:** Classification of the substance or mixture, Label elements, Precautionary statement(s).

HMIS rating

Health	<input type="checkbox"/>	2
Flammability	<input type="checkbox"/>	3
Physical hazard	<input type="checkbox"/>	0
Personal protection	<input type="checkbox"/>	

NFPA codes



Manufacturer disclaimer: To the best of our knowledge, the information contained herein is accurate. However, Pacer Technology does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.



chemical-concepts.com

800.220.1966

410 Pike Road • Huntingdon Valley, PA 19006