# SAFETY DATA SHEET TensorGrip P331 Edge Stiffener

# 1. Identification

Product identifier

Product name TensorGrip P331 Edge Stiffener

Product number USA

Recommended use of the chemical and restrictions on use

**Application** Canister Spray Adhesive

Details of the supplier of the safety data sheet

**Supplier** Quin Global

5710 F St

Omaha NE 68117 (402) 731 3636 (402) 731 1473

marketing.us@quin-global.com



Emergency telephone number

Emergency telephone Chemtrec: 1 800 424 9300

# 2. Hazard(s) identification

#### Classification of the substance or mixture

Physical hazards Press. Gas, Compressed - H280

Health hazards Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 -

H351 STOT SE 3 - H335, H336 STOT RE 2 - H373

Environmental hazards Not Classified

Human health The liquid may be irritating to eyes, respiratory system and skin. Symptoms following

overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

#### Label elements

# **Pictogram**









#### Signal word

# Danger

Hazard statements Hazard state

H301 Toxic if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements** P271 Use only outdoors or in a well-ventilated area.

P301+P310 If swallowed: Immediately call a poison center/ doctor.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308+P313 If exposed or concerned: Get medical advice/ attention.

Contains Methylene Chloride

#### Other hazards

This product does not contain any substances classified as PBT or vPvB.

# 3. Composition/information on ingredients

#### **Mixtures**

Methylene Chloride 60-100%

CAS number: 75-09-2

#### Classification

Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 - H351

STOT SE 3 - H335, H336 STOT RE 2 - H373

The full text for all hazard statements is displayed in Section 16.

# 4. First-aid measures

#### Description of first aid measures

General information Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Get medical attention if any

discomfort continues.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen. Get medical attention.

**Ingestion** Never give anything by mouth to an unconscious person. Do not induce vomiting. Move

affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Get medical attention.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the

person is conscious, coherent and they can remove them themselves If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get

medical attention promptly. Show this Safety Data Sheet to the medical personnel.

# Most important symptoms and effects, both acute and delayed

**Inhalation** May cause coughing and difficulties in breathing. May cause eye and respiratory system

irritation. Overexposure may depress the central nervous system, causing dizziness and

intoxication.

Revision date: 12/1/2017 Revision: 5 Supersedes date: 8/20/2015

# TensorGrip P331 Edge Stiffener

**Ingestion** Aspiration hazard if swallowed. May be fatal if swallowed and enters airways. Ingestion may

cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may

cause chemical pneumonitis.

Skin contact May be absorbed through the skin. Product has a defatting effect on skin. The product is

irritating to eyes and skin. A single exposure may cause the following adverse effects:

Dryness and/or cracking.

Eye contact Causes serious eye irritation. Burns can occur. A single exposure may cause the following

adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged

contact causes serious eye and tissue damage.

## 5. Fire-fighting measures

#### Special hazards arising from the substance or mixture

Specific hazards Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers

can burst violently or explode when heated, due to excessive pressure build-up.

#### Advice for firefighters

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8.

**Environmental precautions** 

**Environmental precautions** Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-

combustible material.

#### Methods and material for containment and cleaning up

Methods for cleaning up

Stop leak if possible without risk. Provide adequate ventilation. Avoid the spillage or runoff

entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place

into containers. Wash thoroughly after dealing with a spillage.

# 7. Handling and storage

# Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation

of vapors. Use approved respirator if air contamination is above an acceptable level.

Container must be kept tightly closed when not in use.

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product.

#### Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the

original container. Pressurized container: Must not be exposed to temperatures above

50°C/120°F

# 8. Exposure Controls/personal protection

#### Control parameters

## Occupational exposure limits

#### Methylene Chloride

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm

**A**3

Short-term exposure limit (15-minute): OSHA 125 ppm Long-term exposure limit (8-hour TWA): OSHA 25 ppm

ACGIH = American Conference of Governmental Industrial Hygienists. A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans. OSHA = Occupational Safety and Health Administration.

# **Exposure controls**

#### Protective equipment





Appropriate engineering

controls

This product must not be handled in a confined space without adequate ventilation. Provide

adequate general and local exhaust ventilation.

Eye/face protection Wear chemical splash goggles.

**Hand protection** Use protective gloves.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapor contact.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating,

smoking and using the toilet. Wash promptly with soap and water if skin becomes

contaminated. Promptly remove any clothing that becomes contaminated. When using do not

eat, drink or smoke.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended

occupational exposure limit. If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level

exposures, compressed airline breathing apparatus should be used.

## 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

Appearance Aerosol.

Relative density 1.3

Volatile organic compound This product contains a maximum VOC content of 0 g/l.

# 10. Stability and reactivity

Stability Stable at normal ambient temperatures and when used as recommended.

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Oxidizing agents. Reducing agents.

Hazardous decomposition

products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). Nitrous

gases (NOx).

# 11. Toxicological information

## Information on toxicological effects

Acute toxicity - oral

**ATE oral (mg/kg)** 149.25

Revision date: 12/1/2017 Revision: 5 Supersedes date: 8/20/2015

# TensorGrip P331 Edge Stiffener

Acute toxicity - dermal

**ATE dermal (mg/kg)** 1,641.79

Toxicological information on ingredients.

Methylene Chloride

Acute toxicity - oral

Acute toxicity oral (LD50

/50

mg/kg)

Species

Rat

ATE oral (mg/kg)

100.0

2,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 2,000.0

mg/kg)

**Species** 

ATE dermal (mg/kg)

1,100.0

Rat

Acute toxicity - inhalation

Acute toxicity inhalation

52.0

(LC₅₀ vapours mg/l)

Species Rat

ATE inhalation (vapours

mg/l)

11.0

Carcinogenicity

Carcinogenicity - rat - inhalation Limited evidence of carcinogenicity in animal

studies

Target organ for

carcinogenicity

Tumerigenic: Carcinogenic by RTECS criteria. Endochrine: Tumors

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

Specific target organ toxicity - single exposure

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Inhalation - May cause damage to organs through prolonged or repeated exposure

-Central nervous system Oral - May cause damage to organs through prolonged or

repeated exposure -Liver, blood.

General information RTECS: PA8050000

12. Ecological Information

13. Disposal considerations

Waste treatment methods

**Disposal methods**Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

## 14. Transport information

Air transport notes 1. <75kg, 2. <150kg

**UN Number** 

UN No. (TDG) 3500 UN No. (ICAO) 3500 UN No. (DOT) 3500

UN proper shipping name

Proper shipping name (TDG) Chemical Under Pressure, N.O.S. (Air, Compressed)

Proper shipping name (DOT) Chemical Under Pressure, N.O.S. (Air, Compressed)

Transport hazard class(es)

TDG class 2
TDG label(s) 2.2

#### Transport labels



# Packing group

Not applicable.

# 15. Regulatory information

#### 16. Other information

Revision date 12/1/2017

Revision 5

Supersedes date 8/20/2015

**SDS No.** 22177

Hazard statements in full H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H312 Harmful in contact with skin. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs (Oral (Category 2), Inhalation (Category 2), Blood,

Central nervous system, Liver) through prolonged or repeated exposure.

ACA HMIS Health rating.

**ACA HMIS Flammability** 

rating.

Will not burn. (0)

Moderate hazard. (2)

ACA HMIS Physical hazard

Normally stable. (0)

В

rating.

ACA HMIS Personal

protection rating.



The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.