



## SAFETY DATA SHEET

### Tensorgrip P300AA High Temp General Purpose Contact Adhesive

#### 1. Identification

##### Product identifier

**Product name** Tensorgrip P300AA High Temp General Purpose Contact Adhesive

**Product number** USA

##### Recommended use of the chemical and restrictions on use

**Application** Aerosol Spray Adhesive

##### Details of the supplier of the safety data sheet

**Supplier** Tensorgrip  
5710 F St  
Omaha NE 68117  
(402) 731 3636  
(402) 731 1473  
marketing.us@quin-global.com

##### Emergency telephone number

**Emergency telephone** Chemtrec: 1 800 424 9300

#### 2. Hazard(s) identification

##### Classification of the substance or mixture

**Physical hazards** Flam. Aerosol 1 - H222 Press. Gas, Compressed - H280

**Health hazards** Acute Tox. 3 - H301 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 - H351 STOT SE 3 - H335, H336 STOT RE 2 - H373

**Environmental hazards** Not Classified

**Human health** The liquid may be irritating to eyes, respiratory system and skin. Symptoms following overexposure may include the following: Headache. Dizziness. Nausea, vomiting.

##### Label elements

##### Pictogram



**Signal word**

Danger



chemical-concepts.com

**800.220.1966**

410 Pike Road • Huntingdon Valley, PA 19006

## Tensorgrip P300AA High Temp General Purpose Contact Adhesive

<b>Hazard statements</b>	<p>H222 Extremely flammable aerosol.</p> <p>H280 Contains gas under pressure; may explode if heated.</p> <p>H301 Toxic if swallowed.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H351 Suspected of causing cancer.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p>
<b>Precautionary statements</b>	<p>P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.</p> <p>P260 Do not breathe vapor/ spray.</p> <p>P302+P352 If on skin: Wash with plenty of water.</p> <p>P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Call a poison center/ doctor if you feel unwell.</p>
<b>Supplemental label information</b>	AT(o) 15.0% of the mixture consists of ingredient(s) of unknown acute oral toxicity.
<b>Contains</b>	Methylene Chloride, Isobutane, Propane

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Mixtures

<b>Methylene Chloride</b> <span style="float: right;"><b>30-60%</b></span> CAS number: 75-09-2
<b>Classification</b> Acute Tox. 3 - H301 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 2 - H351 STOT SE 3 - H335, H336 STOT RE 2 - H373
<b>Isobutane</b> <span style="float: right;"><b>10-25%</b></span> CAS number: 75-28-5
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas, Compressed - H280

## Tensorgrip P300AA High Temp General Purpose Contact Adhesive

<b>Propane</b>	<b>10-25%</b>
CAS number: 74-98-6	
<b>Classification</b>	
Flam. Gas 1 - H220	
Press. Gas, Liquefied - H280	
Acute Tox. 4 - H332	
Simple Asphyxiant - USH03	

The full text for all hazard statements is displayed in Section 16.

### 4. First-aid measures

#### Description of first aid measures

<b>General information</b>	Remove affected person from source of contamination. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
<b>Ingestion</b>	Get medical attention immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Skin Contact</b>	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Only remove contact lenses if the person is conscious, coherent and they can remove them themselves. If adhesive bonding occurs, do not force eyelids apart. Continue to rinse for at least 15 minutes. If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

#### Most important symptoms and effects, both acute and delayed

<b>General information</b>	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Prolonged or repeated exposure may cause the following adverse effects: Irritation of nose, throat and airway. Coughing. Headache.
<b>Ingestion</b>	Prolonged or repeated exposure may cause the following adverse effects: Gastrointestinal symptoms, including upset stomach. Nausea, vomiting. Diarrhea.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin.
<b>Eye contact</b>	Prolonged or repeated exposure may cause the following adverse effects: Irritation and redness, followed by blurred vision.

### 5. Fire-fighting measures

#### Extinguishing media

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

#### Special hazards arising from the substance or mixture

## Tensorgrip P300AA High Temp General Purpose Contact Adhesive

**Specific hazards** Pressurized container: Must not be exposed to temperatures above 50°C/120°F Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

### Advice for firefighters

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8. No smoking, sparks, flames or other sources of ignition near spillage.

### Environmental precautions

**Environmental precautions** Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material.

### Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

## 7. Handling and storage

### Precautions for safe handling

**Usage precautions** Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Container must be kept tightly closed when not in use. Use explosion proof electric equipment. Avoid discharge into drains or watercourses or onto the ground.

**Advice on general occupational hygiene** Do not eat, drink or smoke when using this product.

### Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container. Pressurized container: Must not be exposed to temperatures above 50°C/120°F

### Specific end uses(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.

## 8. Exposure Controls/personal protection

### Control parameters

### Occupational exposure limits

#### **Methylene Chloride**

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm  
A3

Short-term exposure limit (15-minute): OSHA 125 ppm

Long-term exposure limit (8-hour TWA): OSHA 25 ppm

#### **Isobutane**

## Tensorgrip P300AA High Temp General Purpose Contact Adhesive

Long-term exposure limit (8-hour TWA): ACGIH 1000 ppm

Long-term exposure limit (8-hour TWA): NIOSH: National Institute of Occupational Safety and Health 800 ppm 1900 mg/m<sup>3</sup>

### Propane

Long-term exposure limit (8-hour TWA): NIOSH: National Institute of Occupational Safety and Health 1800 mg/m<sup>3</sup> 1000 ppm

Long-term exposure limit (8-hour TWA): OSHA 1800 ppm 1000 mg/m<sup>3</sup>

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

OSHA = Occupational Safety and Health Administration.

### Exposure controls

#### Protective equipment



#### Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapors and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist.

#### Eye/face protection

Wear chemical splash goggles.

#### Hand protection

Use protective gloves.

#### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

#### Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

#### Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

## 9. Physical and Chemical Properties

### Information on basic physical and chemical properties

Appearance	Aerosol.
Color	Clear Red.
Odor	Organic solvents.
Initial boiling point and range	Not determined.
Flash point	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapor density	Not determined.
Relative density	1.22
Solubility(ies)	Negligibly soluble in water
Volatile organic compound	This product contains a maximum VOC content of 160.5 g/l.

## Tensorgrip P300AA High Temp General Purpose Contact Adhesive

### 10. Stability and reactivity

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended.
<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidizing agents. Reducing agents.
<b>Materials to avoid</b>	Strong oxidizing agents. Aluminum. Magnesium. Amines. Strong alkalis.
<b>Hazardous decomposition products</b>	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). Aldehydes. Hydrocarbons.

### 11. Toxicological information

#### Information on toxicological effects

##### Acute toxicity - oral

ATE oral (mg/kg) 160.07532957

##### Acute toxicity - dermal

ATE dermal (mg/kg) 2,071.56308851

##### Acute toxicity - inhalation

ATE inhalation (gases ppm) 30,000.0

ATE inhalation (vapours mg/l) 73.33333333

#### Toxicological information on ingredients.

#### Methylene Chloride

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 2,000.0

Species Rat

ATE oral (mg/kg) 100.0

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 2,000.0

Species Rat

ATE dermal (mg/kg) 1,100.0

##### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 52.0

Species Rat

ATE inhalation (vapours mg/l) 11.0

##### Carcinogenicity

Carcinogenicity Cancinogenicity - rat - inhalation Limited evidence of carcinogenicity in animal studies

## Tensorgrip P300AA High Temp General Purpose Contact Adhesive

**Target organ for carcinogenicity** Tumerigenic: Carcinogenic by RTECS criteria. Endocrine: Tumors

**IARC carcinogenicity** IARC Group 2B Possibly carcinogenic to humans.

**NTP carcinogenicity** Reasonably anticipated to be a human carcinogen.

### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Inhalation - May cause damage to organs through prolonged or repeated exposure  
-Central nervous system Oral - May cause damage to organs through prolonged or repeated exposure  
-Liver, blood.

**General information** RTECS: PA8050000

### Isobutane

**Toxicological effects** No information available.

### Carcinogenicity

**Carcinogenicity** Does not contain any substances known to be carcinogenic.

**Inhalation** Suffocation (asphyxiant) hazard

**Skin Contact** Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

**Eye contact** Spray will evaporate and cool quickly and may cause frostbite or cold burns if in contact with skin.

### Propane

### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> gases ppmV)** 1,442.0

**Species** Rat

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 1,442.0

**Species** Rat

**ATE inhalation (gases ppm)** 4,500.0

**ATE inhalation (vapours mg/l)** 11.0

## 12. Ecological Information

## 13. Disposal considerations

### Waste treatment methods

## Tensorgrip P300AA High Temp General Purpose Contact Adhesive

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### 14. Transport information

**Air transport notes** 1. <75kg, 2. <150kg

**UN Number**

**UN No. (ICAO)** 1950

**UN No. (DOT)** Limited Quantity <1L, Aerosol

**UN proper shipping name**

**Proper shipping name (DOT)** Aerosols, Flammable

**Transport hazard class(es)**

**Transport labels**



**Packing group**

Not applicable.

### 15. Regulatory information

**US Federal Regulations**

**CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

Present.

*Methylene Chloride*

Final CERCLA RQ: 1000(454) pounds (Kilograms)

**SARA 313 Emission Reporting**

Present.

*Methylene Chloride*

0.1 %

**SARA (311/312) Hazard Categories**

Present.

*Isobutane*

Fire  
Pressure  
Hazard

*Propane*

Yes.

*Methylene Chloride*

Acute  
Health hazard  
Chronic  
Health hazard

**US State Regulations**

**California Proposition 65 Carcinogens and Reproductive Toxins**

Present.



## Tensorgrip P300AA High Temp General Purpose Contact Adhesive

### *Isobutane*

This product does not contain any chemicals known to the State of California to cause cancer, birth or any other reproductive harm.

### *Methylene Chloride*

Known to the State of California to cause cancer.

### **Massachusetts "Right To Know" List**

Present.

### *Isobutane*

### *Propane*

### *Methylene Chloride*

### **New Jersey "Right To Know" List**

Present.

### *Isobutane*

### *Propane*

### *Methylene Chloride*

### **Pennsylvania "Right To Know" List**

Present.

### *Isobutane*

### *Propane*

### *Methylene Chloride*

### **Inventories**

#### **Canada - DSL/NDSL**

### *Propane*

DSL

Present.

#### **US - TSCA**

Present.

### *Propane*

### *Methylene Chloride*

### **16. Other information**

<b>Revision date</b>	4/3/2017
<b>Revision</b>	3
<b>Supersedes date</b>	11/9/2016
<b>SDS No.</b>	20704

## Tensorgrip P300AA High Temp General Purpose Contact Adhesive

<b>Hazard statements in full</b>	USH03 May displace oxygen and cause rapid suffocation H220 Extremely flammable gas. H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H301 Toxic if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H373 May cause damage to organs (Oral (Category 2), Inhalation (Category 2), Blood, Central nervous system, Liver) through prolonged or repeated exposure.
<b>ACA HMIS Health rating.</b>	Moderate hazard. (2)
<b>ACA HMIS Flammability rating.</b>	Ignites easily. (3)
<b>ACA HMIS Physical hazard rating.</b>	Normally stable. (0)
<b>ACA HMIS Personal protection rating.</b>	B



The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, many of which are solely within the user's knowledge and control, the user is responsible for determining whether the usage of this product is fit for a particular purpose and suitable for the user's method of use or application. It is essential that the user, not the manufacturer, evaluates this product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.